

Package ‘expressionCurator’

March 24, 2021

Title expressionCurator

Version 1.36.0-1

API version v0.1

Description This is the API for layer 3 of the Roche pRed project. This swagger page describes the expressionCurator APIs. Before carrying out any API calls you will need an API token. API tokens can be obtained under your profile within the Genestack software. To try out calls in this swagger page: 1. Click the 'Authorize' button below to enter your API token 2. Scroll to the 'Parameters' section for the method you wish to try out and click the 'Try it out' button 3. Enter parameter values that you wish to try 4. Scroll to the bottom of the Parameters section and click the 'Execute' bar that appears The server response will be in the section that follows.

Depends R (>= 3.3.2)

License Proprietary

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

R topics documented:

ExpressionSPoTApi_add_atomic_expression	1
ExpressionSPoTApi_add_expression	2
ExpressionSPoTApi_delete_atomic	2
ExpressionSPoTApi_delete_group	3
ExpressionSPoTApi_get_expression	3
ExpressionSPoTApi_get_expression_by_version	4
ExpressionSPoTApi_get_expression_data	4
ExpressionSPoTApi_get_expression_versions	6
ExpressionSPoTApi_get_group	6
ExpressionSPoTApi_get_group_by_run	7
ExpressionSPoTApi_get_group_curation_status	7
ExpressionSPoTApi_search_groups	8
ExpressionSPoTApi_search_runs	9
ExpressionSPoTApi_update_atomic_metadata	9

ExpressionSPoTApi_update_expression_run	10
ExpressionSPoTApi_update_group	10

ExpressionSPoTApi_add_atomic_expression
<i>Create a single new object from a given data file with optional supplied metadata.</i>

Description

Create a single new object from a given data file with optional supplied metadata.

Usage

ExpressionSPoTApi_add_atomic_expression(source, ...)

ExpressionSPoTApi_add_expression
<i>Create multiple new objects from a multi-row data file with optional supplied metadata</i>

Description

Create multiple new objects from a multi-row data file with optional supplied metadata

Usage

ExpressionSPoTApi_add_expression(source, ...)

Arguments

source

ExpressionSPoTApi_delete_atomic
<i>Delete the object</i>

Description

Delete the object

Usage

ExpressionSPoTApi_delete_atomic(id, ...)

Arguments

id Unique identifier (accession) of the object.

ExpressionSPoTApi_delete_group
Delete the object

Description

Delete the object

Usage

ExpressionSPoTApi_delete_group(id, ...)

Arguments

id Unique identifier (accession) of the object.

ExpressionSPoTApi_get_expression
Retrieve a single expression object by ID (accession)

Description

Retrieve a single expression object by ID (accession)

Usage

ExpressionSPoTApi_get_expression(id, returned_metadata_fields, ...)

Arguments

id Unique identifier (accession) of the object.

returned_metadata_fields

The parameter defines amount of metadata attributes to return: 1. `template` - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. `all` - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.

`ExpressionSPoTApi_get_expression_by_version`*Retrieve a single expression object by ID (accession)*

Description

Retrieve a single expression object by ID (accession)

Usage

```
ExpressionSPoTApi_get_expression_by_version(  
    id,  
    version,  
    returned_metadata_fields,  
    ...  
)
```

Arguments

`id` Unique identifier (accession) of the object.

`version` Unique version of the object.

`returned_metadata_fields`

The parameter defines amount of metadata attributes to return: 1. `template` - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. `all` - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.

`ExpressionSPoTApi_get_expression_data`*Retrieve multiple expression data and metadata objects*

Description

Retrieve multiple expression data and metadata objects

Usage

```
ExpressionSPoTApi_get_expression_data(  
    filter,  
    query,  
    search_specific_terms,  
    run_filter,  
    min_expression_level,
```

```

    feature_list,
    use_versions,
    returned_metadata_fields,
    page_limit,
    cursor,
    ...
)

```

Arguments

filter	Filter by expression metadata (key-value metadata pair(s)). E.g. "Normalization Method"=TPM.
query	Search for expression objects via a full text query over all expression metadata. E.g. TPM.
search_specific_terms	If the full-text query term is present in an ODM dictionary, enabling this parameter will modify the query to include child terms of the full-text query. For example, the search query "Body fluid" can be expanded to include the term "Blood" (a child term of "Body fluid") so files containing either "Body fluid" or "Blood" in their metadata will be returned in the search results. The parent-child relationship is defined by the key "broaders" in the dictionary. If the full query term is not present in a dictionary then this parameter has no effect.
run_filter	Genestack accession that corresponds to the gct column used to link expression data from the same run to a sample.
min_expression_level	Minimum threshold (inclusive) for returned expression values.
feature_list	List of features to return. These features must match exactly the probe IDs in the GCT file. Example: featureList=1552256_a_at&featureList=1552269_at
use_versions	Specify which versions of omics data files are used in the query. By default the active version is used. See Versioning above. Syntax: * or v<version number> or <CHAIN_ID>:v<version number> or <CHAIN_ID>:<accession1,accession2,...>
returned_metadata_fields	The parameter defines amount of metadata attributes to return: 1. template - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. all - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.
page_limit	Maximum number of results to return per page (see Paging above). This value must be between 0 and 2000 (inclusive). The default is 2000.
cursor	The page tag to resume results from (see paging above).

ExpressionSPoTApi_get_expression_versions

Retrieve a list of object versions by ID

Description

Retrieve a list of object versions by ID

Usage

ExpressionSPoTApi_get_expression_versions(id, ...)

Arguments

id	Unique identifier (accession) of the object.
----	--

ExpressionSPoTApi_get_group

Retrieve a single group object by ID (accession)

Description

Retrieve a single group object by ID (accession)

Usage

ExpressionSPoTApi_get_group(id, returned_metadata_fields, ...)

Arguments

id	Unique identifier (accession) of the object.
----	--

returned_metadata_fields	
--------------------------	--

The parameter defines amount of metadata attributes to return: 1. template - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. all - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.

`ExpressionSPoTApi_get_group_by_run`*Retrieve a single group object by run ID (accession)*

Description

Retrieve a single group object by run ID (accession)

Usage

```
ExpressionSPoTApi_get_group_by_run(id, returned_metadata_fields, ...)
```

Arguments

`id` Unique identifier (accession) of the object.

`returned_metadata_fields`

The parameter defines amount of metadata attributes to return: 1. `template` - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. `all` - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.

`ExpressionSPoTApi_get_group_curation_status`*Get curation status of a group by ID (accession)*

Description

Get curation status of a group by ID (accession)

Usage

```
ExpressionSPoTApi_get_group_curation_status(id, ...)
```

Arguments

`id` Unique identifier (accession) of the object.

ExpressionSPoTApi_search_groups

Retrieve groups that match a query

Description

Retrieve groups that match a query

Usage

```
ExpressionSPoTApi_search_groups(
    filter,
    query,
    search_specific_terms,
    returned_metadata_fields,
    use_versions,
    page_offset,
    page_limit,
    ...
)
```

Arguments

filter	Filter by expression metadata (key-value metadata pair(s)). E.g. "Normalization Method"=TPM.
query	Search for expression objects via a full text query over all expression metadata. E.g. TPM.
search_specific_terms	If the full-text query term is present in an ODM dictionary, enabling this parameter will modify the query to include child terms of the full-text query. For example, the search query "Body fluid" can be expanded to include the term "Blood" (a child term of "Body fluid") so files containing either "Body fluid" or "Blood" in their metadata will be returned in the search results. The parent-child relationship is defined by the key "broaders" in the dictionary. If the full query term is not present in a dictionary then this parameter has no effect.
returned_metadata_fields	The parameter defines amount of metadata attributes to return: 1. template - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. all - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.
use_versions	Specify which versions of omics data files are used in the query. By default the active version is used. See Versioning above. Syntax: * or v<version number> or <CHAIN_ID>:v<version number> or <CHAIN_ID>:<accession1,accession2,...>
page_offset	Show the page pageOffset+1 results from the start of the results. E.g. 100 will show a page of results starting from the 101st result. The default value is 0.

page_limit	Maximum number of results to return per page (see Paging above). This value must be between 0 and 2000 (inclusive). The default is 2000.
------------	--

ExpressionSPoTApi_search_runs

Retrieve run objects related to the given group

Description

Retrieve run objects related to the given group

Usage

ExpressionSPoTApi_search_runs(id, page_offset, page_limit, ...)

Arguments

id	Unique identifier (accession) of the object.
page_offset	Show the page pageOffset+1 results from the start of the results. E.g. 100 will show a page of results starting from the 101st result. The default value is 0.
page_limit	Maximum number of results to return per page (see Paging above). This value must be between 0 and 2000 (inclusive). The default is 2000.

ExpressionSPoTApi_update_atomic_metadata

Update object metadata

Description

Update object metadata

Usage

ExpressionSPoTApi_update_atomic_metadata(id, body, ...)

Arguments

id	Unique identifier (accession) of the object.
body	Metadata in the form of {key: value, key2: value2, ...}

ExpressionSPoTApi_update_expression_run
<i>Update object metadata</i>

Description

Update object metadata

Usage

ExpressionSPoTApi_update_expression_run(id, body, ...)

Arguments

- | | |
|------|---|
| id | Unique identifier (accession) of the object. |
| body | Metadata in the form of {key: value, key2: value2, ...} |

ExpressionSPoTApi_update_group
<i>Set curation status of a group by ID (accession)</i>

Description

Set curation status of a group by ID (accession)

Usage

ExpressionSPoTApi_update_group(id, body, ...)

Arguments

- | | |
|----|--|
| id | Unique identifier (accession) of the object. |
|----|--|