

Package ‘preparationCurator’

March 24, 2021

Title preparationCurator

Version 1.36.0-1

API version v0.1

Description This swagger page describes the preparationCurator APIs. Before carrying out any API calls you will need an API token. API tokens can be obtained under your profile within the Genestack software. To try out calls in this swagger page: 1. Click the 'Authorize' button below to enter your API token 2. Scroll to the 'Parameters' section for the method you wish to try out and click the 'Try it out' button 3. Enter parameter values that you wish to try 4. Scroll to the bottom of the Parameters section and click the 'Execute' bar that appears The server response will be in the section that follows.

Depends R (>= 3.3.2)

License Proprietary

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

R topics documented:

PreparationSPoTApi_add_preparations	1
PreparationSPoTApi_delete_preparation	2
PreparationSPoTApi_delete_preparation_group	2
PreparationSPoTApi_get_preparation	3
PreparationSPoTApi_get_preparations_by_group	3
PreparationSPoTApi_get_preparation_by_version	4
PreparationSPoTApi_get_preparation_versions	5
PreparationSPoTApi_search_preparations	5
PreparationSPoTApi_update_preparation	6

PreparationSPoTApi_add_preparations
Add new preparation object

Description

Add new preparation object

Usage

PreparationSPoTApi_add_preparations(source, ...)

Arguments

source

PreparationSPoTApi_delete_preparation
Delete a preparation object

Description

Delete a preparation object

Usage

PreparationSPoTApi_delete_preparation(id, ...)

Arguments

id Unique identifier (accession) of the object.

PreparationSPoTApi_delete_preparation_group
Delete a preparation group with all related preparation objects

Description

Delete a preparation group with all related preparation objects

Usage

PreparationSPoTApi_delete_preparation_group(id, ...)

Arguments

id Unique identifier (accession) of the object.

`PreparationSPoTApi_get_preparation`*Retrieve a single preparation object by ID (accession)*

Description

Retrieve a single preparation object by ID (accession)

Usage

```
PreparationSPoTApi_get_preparation(id, returned_metadata_fields, ...)
```

Arguments

`id` Unique identifier (accession) of the object.

`returned_metadata_fields`

The parameter defines amount of metadata attributes to return: 1. `template` - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. `all` - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.

`PreparationSPoTApi_get_preparations_by_group`*Retrieve preparations related to the given group*

Description

Retrieve preparations related to the given group

Usage

```
PreparationSPoTApi_get_preparations_by_group(  
    id,  
    returned_metadata_fields,  
    page_offset,  
    page_limit,  
    ...  
)
```

Arguments

<code>id</code>	Unique identifier (accession) of the object.
<code>returned_metadata_fields</code>	The parameter defines amount of metadata attributes to return: 1. <code>template</code> - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. <code>all</code> - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.
<code>page_offset</code>	Show the page <code>pageOffset+1</code> results from the start of the results. E.g. 100 will show a page of results starting from the 101st result. The default value is 0.
<code>page_limit</code>	Maximum number of results to return per page (see Paging above). This value must be between 0 and 2000 (inclusive). The default is 2000.

```
PreparationSPoTApi_get_preparation_by_version
```

Retrieve a single preparation object by ID (accession)

Description

Retrieve a single preparation object by ID (accession)

Usage

```
PreparationSPoTApi_get_preparation_by_version(
    id,
    version,
    returned_metadata_fields,
    ...
)
```

Arguments

<code>id</code>	Unique identifier (accession) of the object.
<code>version</code>	Unique version of the object.
<code>returned_metadata_fields</code>	The parameter defines amount of metadata attributes to return: 1. <code>template</code> - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. <code>all</code> - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.

`PreparationSPoTApi_get_preparation_versions`*Retrieve a list of object versions by ID*

Description

Retrieve a list of object versions by ID

Usage

```
PreparationSPoTApi_get_preparation_versions(id, ...)
```

Arguments

<code>id</code>	Unique identifier (accession) of the object.
-----------------	--

`PreparationSPoTApi_search_preparations`*List or search for preparation metadata objects*

Description

List or search for preparation metadata objects

Usage

```
PreparationSPoTApi_search_preparations(  
    filter,  
    query,  
    search_specific_terms,  
    returned_metadata_fields,  
    sort,  
    page_limit,  
    page_offset,  
    ...  
)
```

Arguments

<code>filter</code>	Filter by preparation metadata (key-value metadata pair(s)). E.g. Digestion=Trypsin
<code>query</code>	Search for preparation objects via a full-text query over all preparation metadata fields. E.g. "reversed-phase liquid chromatography"

search_specific_terms	If the full-text query term is present in an ODM dictionary, enabling this parameter will modify the query to include child terms of the full-text query. For example, the search query "Body fluid" can be expanded to include the term "Blood" (a child term of "Body fluid") so files containing either "Body fluid" or "Blood" in their metadata will be returned in the search results. The parent-child relationship is defined by the key "broaders" in the dictionary. If the full query term is not present in a dictionary then this parameter has no effect.
returned_metadata_fields	The parameter defines amount of metadata attributes to return: 1. template - return metadata attributes according to applied template, if object doesn't have applied template default template will be used. This is the default for User endpoints. 2. all - return all metadata attributes with values and null attributes, if they are present in the applied template. This is the default for Curator endpoints.
sort	Attribute to sort by, with optional ascending/descending marker, of the form "[+ -]<key_name>". No marker or "+" indicates ascending sort, and "-" indicates descending sort. *Default:* sort by ID in ascending order.
page_limit	Maximum number of results to return per page (see Paging above). This value must be between 0 and 2000 (inclusive). The default is 2000.
page_offset	Show the page pageOffset+1 results from the start of the results. E.g. 100 will show a page of results starting from the 101st result. The default value is 0.

PreparationSPoTApi_update_preparation
Update a preparation object

Description

Update a preparation object

Usage

PreparationSPoTApi_update_preparation(id, body, ...)

Arguments

id	Unique identifier (accession) of the object.
body	Metadata in the form of {key: value, key2: value2, ...}