



Bars / Ice Cream / Table Service / Quick Service



Dusty Environments Like Pizza and Bakeries



Cafeterias / Discount Stores



Convenience Stores / Small Grocery Stores



Tobacco Stores / Liquor Stores

Fanless POS Terminal Designed For Optimum Performance and Dependability



The Histone HK568 15.6" widescreen touch terminal presents a contemporary look with ultimate flexibility and high performance. Extra workspace and adjustable design make the HK568 an excellent option for any application. Rotate the display vertically and add the SNBC BTP-S80 Cube printer to create aesthetically pleasing kiosk stations with a small form factor.

- Intel Elkhart Lake Quad Core J6412 Fanless Processor
- Solid State Drive
- Projected Capacitive Touch (PCT) For Optimum Performance and Reliability
- 15.6" Screen / 16:9 Aspect Ratio
- Vivid LED Backlight
- Reduce Workstation Footprint and Cable Clutter With the Optional CUBE-X Housing For an Integrated 2D Scanner and Thermal Printer Solution
- Compatible with Popular Application Software



HK568 Touch Screen Terminal



Conserve Counter Space With the Optional Cube X Combination Integrated Printer / Scanner



Screen Can Be Rotated – Place a Printer Under the Screen Using the Optional Extension Bracket



Optional Integrated Rear 2 Lines by 20 Characters VFD Customer Display



Optional Integrated 10.1" (Shown) or 15.6" Rear LCD Customer Display

Options and Upgrades

Configure your system with these easy to add options:

- Integrated VFD Customer Display – 2 Lines x 20 Characters
- Integrated 15.6" or 10.1" Customer LCD
- Integrated 15.6" or 10.1" Customer Touch LCD
- Integrated Fingerprint Reader
- Extension Bracket
- Cube X Combination Printer/Scanner
- Wall Mount Bracket with Standard VESA Configuration

Applications

The attractive, powerful HK568 fanless terminal is ideal for harsh environments like pizza, quick service restaurants, bakeries, industrial shop floors, and many more:

- Airline Counters
- Automotive Services
- Convenience Stores
- Digital Signage
- Dry Cleaners
- Financial/Banking
- Food & Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks
- Kitchen Video
- Medical
- Message Stations
- Point of Sale
- Quick Service
- Rental Car
- Rental Stores
- Retail Scanning
- Self Service
- Streaming Video
- Table Service
- Training
- Unattended Workstations

Connectivity

Ports are located below the touch screen. Cable management keeps cables hidden and organized. Three RJ48-DB9M adaptors are included.

- A** Cash Drawer (RJ11 – 24V)
- B** DC In (24V)
- C** Powered USB (One V2.0 – 24V)
- D** LAN
- E** USB (V3.0)
- F** COM1 (RJ48)
- G** USB (V2.0)
- H** Audio Line-Out
- I** HDMI
- J** DC Out (12V)
- K** COM2 (RJ48)
- L** COM3 (RJ48)

Specifications

Processor:	Intel Celeron Quad Core J6412
Cores / Threads	4 Cores / 4 Threads
Cache Memory:	2MB
Display LCD:	True Flat 15.6" LCD with LED Backlighting
Resolution:	1920 x 1080
Aspect Ratio:	16:9
Brightness:	220 cd/m ²
Integrated Speakers:	Integrated 2 Watt Speaker
Chipset (PCH):	CPU Integrated
Touch:	Projected Capacitive Touch (PCT)
MCR:	Integrated USB Interface Triple Track MCR
Mass Storage Device:	128GB 2.5" Solid State Drive
RAM Memory (1 Slot):	4GB SODIMM DDR4(3200MHz) Expandable To 16GB
Video Memory:	Shared System Memory Up To 256MB
Tilt Adjustment:	0° ~ 45° (Vertical)
Serial Ports – External:	COM1 / COM2 / COM3 = RJ48
Internal:	COM4 = for Rear VFD
USB Ports:	One USB 24V Powered (120W Power Supply Required) / Four V2.0 / Two V3.0
Cash Drawer Port:	RJ12 (24V) – Dual Cash Drawer – Supports Open/Close
Display Port:	One HDMI
LAN Port:	RJ45 100M/1000M Gigabit LAN
Audio Port:	One Line-Out
Mic Port:	Not Applicable
Power Supply:	60W, 24V/2.5A External Power Adaptor 100-240V 50-60Hz
Current / Power Usage:	0.20A / 24V
Environment – Operating:	32° F to 113° F / 10% to 90% RH Non-Condensing
Storage:	14° F to 158° F / 10% to 90% RH Non-Condensing
Compatible O/S:	Windows 10 / Windows 11 / Professional
Dim. / Weight – Overall:	15-3/4"W x 8"D x 15"H 14.33 lbs.
Shipping Carton:	18-3/8"L x 12-1/2"W x 19"H 15 lbs.
Safety and EMI:	FCC / CE / RoHS

