# How to Be Better Than Most in GenAl

#### Contents

Core LLM Building Blocks	2
Advanced Architectures	3
Training & Tuning	3
Generation Controls	4
Knowledge & Retrieval	4
Efficiency & Scaling	5
Data & Preprocessing	6
Evaluation & Benchmarks	6
Extensions	7
Production & MLOps	7
Safety & Limits	8

## Core LLM Building Blocks

- 1. **Transformer Architecture** → Core design (encoder-only like BERT, decoder-only like GPT/Claude/Gemini etc [autoregressive], encoder-decoder like T5)
- 2. **Tokenization** → Break text into tokens and map them to numbers
- 3. **Embedding Spaces**  $\rightarrow$  Map tokens into a semantic space where closer vectors mean similar meaning
- 4. **Positional Encoding** → Adds sequence order information to token embeddings
- 5. **Attention** → Highlights the most relevant tokens in context
- 6. **Self-Attention** → Each token attends to every other token for context
- 7. **Cross-Attention** → Connect encoder and decoder (in encoder-decoder models)
- 8. **Multi-Head Attention** → Several attention heads capture different patterns in parallel
- 9. **Feed-Forward Networks** → Nonlinear layers that transform representations between attention blocks
- 10. **Residual Connections** → Shortcut links that preserve signals and help gradient flow
- 11. Layer Normalization → Normalizes activations to stabilize and speed up training
- 12. **Output Projection (LM Head)** → Final linear layer mapping hidden states into logits
- 13. **Logits** → Raw prediction scores for each token before probabilities
- 14. **Softmax** → Turns logits into a probability distribution
- 15. Sampling from Probabilities → Chooses the next token based on probability weights
- 16. **RoPE** → Rotary Positional Encoding, adds relative position info for longer sequences
- 17. ALiBi / Relative Positional Encoding → Alternative to RoPE for long contexts
- 18. **Linear / Performer Attention** → Efficient attention variants for very long sequences
- 19. **Grouped Query Attention (GQA)** → Reduces memory use by sharing keys/values across heads
- 20. **Multi-Head Latent Attention** → Extends attention into hidden spaces for richer context
- 21. **SwiGLU/GeLU Activations** → Smooth nonlinear functions that improve expressiveness
- 22. **RMSNorm** → Root-mean-square normalization, a lighter alternative to LayerNorm

#### **Advanced Architectures**

- 1. **Diffusion Models** → Generate images/video by learning to reverse noise process (DALL-E, Midjourney, Stable Diffusion)
- 2. VAEs (Variational Autoencoders) → Probabilistic generative models with latent spaces
- 3. **GANs (Generative Adversarial Networks)** → Generator vs discriminator training for realistic outputs
- 4. **State Space Models (Mamba/SSMs)** → Efficient alternatives to transformers for long sequences
- 5. **Autoregressive Models** → Generate sequences one token at a time (GPT family, Claude, Gemini etc)
- 6. Flow-Based Models → Invertible neural networks for exact likelihood estimation
- 7. **Hybrid Architectures** → Combine multiple approaches (transformer + CNN, etc.)

### **Training & Tuning**

- 1. **Pretraining** → Build general world knowledge from large datasets
- 2. **Mixed Precision Training** → Speed up training with lower-precision arithmetic
- 3. **Sharded / Distributed Training** → Scale across multiple GPUs/nodes
- 4. **Continual / Lifelong Learning** → Update models without forgetting old knowledge
- 5. **Self-Instruction / Self-Play** → Al generates its own training examples
- 6. Fine-Tuning → Adapt the model for specific domains or tasks
- 7. **Supervised Fine-Tuning (SFT)** → Train on curated input-output pairs
- 8. **LoRA** → Parameter-efficient adapters for cheap fine-tuning
- 9. QLoRA → LoRA + quantization, enabling fine-tuning of huge models on modest hardware
- 10.  $PEFT \rightarrow$  Family of methods (e.g., LoRA, QLoRA, adapters) updating only small parts of the model
- 11. **Instruction Tuning** → Teach models to follow natural language instructions
- 12. **RLHF** → Align model outputs with human preferences via feedback
- 13. **Constitutional AI** → AI-written principles for safer alignment
- 14. **DPO / PPO / GRPO** → Optimization algorithms for preference alignment
- 15. **Distillation** → Transfer knowledge from a large model into a smaller one
- 16. **Gradient Descent & Backpropagation** → Core optimization mechanics

- 17. Loss Functions → Cross-entropy loss, perplexity, etc. that guide learning
- 18. **Learning Rate Scheduling** → Adjust training speed for stability
- 19. **Batch Size & Gradient Accumulation** → Control efficiency and memory use
- 20. **Scaling Laws** → Predictable links between size, data, and performance
- 21. Mixture-of-Experts Fine-Tuning → Activate only subsets of parameters for efficiency
- 22. **Preference Optimization (IPO, KTO, etc.)** → Newer RLHF alternatives without full RL
- 23. **Curriculum Learning** → Strategic ordering of training data for better convergence
- 24. **Meta-Learning** → Learning to learn quickly from few examples
- 25. **Transfer Learning** → Leveraging pre-trained models for new tasks
- 26. **Domain Adaptation** → Adapting models across different domains

#### **Generation Controls**

- 1. **Entropy** → Measures uncertainty, higher entropy = more diverse but less predictable outputs
- 2. **Temperature** → Controls randomness; higher = creative, lower = precise
- 3. **Top-k / Top-p**  $\rightarrow$  Sampling filters, Higher = safer, looser = more diverse
- 4. **Repetition Penalty** → Discourages loops; too strong may block valid words
- 5. **Beam Search** → Finds higher-probability outputs, safer but less creative
- 6. **Stop Sequences** → Force model to end at defined markers, too strict may cut off early
- 7. **Context Window** → Defines memory size, longer = more context, but costly
- 8. **Chain-of-Thought** → Stepwise reasoning, improves logic but can slow generation
- 9. **Speculative Decoding** → Drafts with a smaller model, faster but may need corrections
- 10. **Contrastive Decoding** → Balances fluency vs factuality
- 11. **Medusa / Speculative Multi-Path Decoding** → Multi-hypothesis generation for speed + accuracy

### **Knowledge & Retrieval**

- 1. **RAG** → Combine LLMs with external knowledge sources for up-to-date answers
- 2. **Vector Databases** → Store embeddings and perform fast similarity search
- 3. In-Context Learning → Model adapts using examples provided in the prompt

- 4. **Knowledge Graphs** → Represent facts as structured entities and relationships
- 5. **Semantic Search** → Retrieve information based on meaning, not exact keywords
- 6. **Few-Shot Learning** → Learn from a small number of examples
- 7. **Zero-Shot Learning** → Generalize to new tasks without any examples
- 8. **Hybrid Search** → Combine semantic, keyword, and graph-based retrieval
- 9. **Retrieval Augmentation via Loops** → Iteratively refine queries to improve results
- 10. **Reranker** → Re-rank retrieved results to prioritize the most relevant content
- 11. **Dense Passage Retrieval (DPR)** → Embedding-based retrieval for large corpora
- 12. **Sparse Retrieval / BM25** → Keyword-based retrieval for efficiency and baseline
- 13. Feedback-Augmented Retrieval → Use human or model feedback to improve relevance
- 14. **Chain-of-Retrieval** → Multi-step retrieval pipelines for complex queries
- 15. **Retriever-Generator Loops** → Iterative retrieval + generation for difficult queries
- 16. **Hybrid Dense-Sparse Retrieval** → Combine semantic + keyword retrieval for better accuracy
- 17. **Multi-hop Reasoning** → Retrieve multiple connected facts to answer complex queries
- 18. **Embedding Updates / Incremental Indexing** → Keep retrieval database fresh efficiently

# **Efficiency & Scaling**

- 1. **Quantization** → Compress model size and memory usage with minimal accuracy loss
- 2. **Sparse Models / MoE** → Activate only relevant experts to save compute
- 3. **Model Parallelism**  $\rightarrow$  Distribute large models across multiple devices
- 4. **Data Parallelism** → Process multiple batches simultaneously for faster training
- 5. **Gradient Checkpointing**  $\rightarrow$  Save memory by recomputing intermediate activations on demand
- 6. **KV Caching** → Cache key-value pairs to accelerate inference
- 7. **Latency vs. Cost Tradeoff** → Larger models = slower & costlier, smaller = faster & lighter
- 8. **Model Serving** → Efficient deployment using batching and request queuing
- 9. **Edge Deployment** → Run models on local or mobile devices with limited resources
- 10. **Mixed Precision Training** → Use FP16/BF16 to speed up training and reduce memory

- 11. **Sharded / Distributed Training** → Split model parameters across devices for massive models
- 12. **Pipeline Parallelism** → Overlap sequential layer computation across devices for speed
- 13. **Activation & Parameter Offloading** → Move parts of model to CPU to save GPU memory
- 14. **Sparse Attention** → Compute attention only for relevant tokens, reducing cost
- 15. **Memory-Mapped Checkpoints** → Load large models efficiently without full RAM usage
- 16. **Elastic / Dynamic Batching** → Adjust batch size dynamically to optimize throughput
- 17. **Inference Optimization** → Operator fusion, kernel tuning, and caching for faster runtime
- 18. Quantization-Aware Training (QAT)  $\rightarrow$  Fine-tune models with quantization to retain accuracy

# **Data & Preprocessing**

- 1. Data Cleaning & Filtering → Ensure high-quality, relevant, and consistent training data
- 2. **Tokenizer Training** → Build vocabularies using BPE, SentencePiece, or Unigram models
- 3. **Data Deduplication** → Remove repeated or near-duplicate examples to improve learning
- 4. **Data Mixing & Curriculum Learning** → Present data strategically for better convergence
- 5. **Data Augmentation** → Expand dataset with synthetic or modified examples
- 6. **Synthetic Data Generation** → Al-generated data to fill gaps or rare cases
- 7. **Balanced Sampling** → Ensure diverse representation across domains/classes
- 8. **Data Quality Assessment** → Measuring and ensuring training data meets standards
- 9. **Active Learning** → Strategically selecting the most informative data for labeling
- 10. **Data Versioning** → Track changes and maintain reproducibility in datasets

#### **Evaluation & Benchmarks**

- 1. **Perplexity** → Measures how well a model predicts text (core LM metric)
- 2. **BLEU / ROUGE / BERTScore** → Compare generated text to reference quality
- 3. **Benchmark Suites** → Standardized tests like MMLU, HellaSwag, BIG-bench for model evaluation
- 4. **Human Evaluation** → Collect human judgments for accuracy, coherence, and safety
- 5. **Factuality / Truthfulness Metrics** → Specialized evaluation for hallucination-prone outputs

- 6. **Consistency / Contradiction Metrics** → Check if model outputs are logically consistent across queries
- 7. Bias & Fairness Metrics → Quantify demographic or cultural biases in outputs
- 8. **Adversarial Robustness** → Test resilience to malicious or tricky prompts
- 9. **Knowledge Probing** → Evaluate stored factual knowledge (e.g., LAMA, TruthfulQA)
- 10. **Efficiency & Cost Metrics** → Measure latency, throughput, memory, and compute requirements
- 11. Explainability / Interpretability Evaluation  $\rightarrow$  Assess clarity and transparency of model reasoning

#### **Extensions**

- 1. **Multimodality** → Combine text, images, audio, and video for richer understanding
- 2. **Agents** → LLMs that plan, reason, and take actions autonomously
- 3. **Agentic AI**  $\rightarrow$  LLMs with autonomous decision-making, memory, and goal-oriented behaviour
- 4. **Multi-Agent Systems** → Teams of LLMs with specialized roles for complex tasks
- 5. **Tool Use / Function Calling** → LLMs interact with APIs, databases, and external tools
- 6. **Prompt Engineering** → Design inputs to guide models toward better outputs
- 7. Few-Shot & One-Shot Learning → Adapt from minimal examples for quick generalization
- 8. Auto-Prompting / Self-Instruction  $\rightarrow$  Models generate their own prompts to improve learning
- 9. Chain of Thought (CoT) → Break problems into step-by-step reasoning
- 10. **ReAct** → Combine reasoning with tool use and actions
- 11. **Self-Consistency**  $\rightarrow$  Compare multiple reasoning paths  $\rightarrow$  pick best answer
- 12. Tree of Thoughts (ToT)  $\rightarrow$  Explore many reasoning branches before deciding
- 13. **Reflexion** → Model critiques, learns, and refines its own answers
- 14. **Memory** → Agents recall past interactions for long-term context

# **Production & MLOps**

- 1. **Model Versioning & Lineage** → Track model evolution and dependencies
- 2. **A/B Testing for Models** → Compare model performance in production environments

- 3. **Model Monitoring & Drift Detection** → Ensure continued performance over time
- 4. **Continuous Learning** → Updating models with new data without full retraining
- 5. **Model Registry** → Centralized storage and management of model artifacts
- 6. **Feature Stores** → Manage and serve features for model inference
- 7. **Model Serving Infrastructure** → Scalable deployment and serving systems
- 8. **Experiment Tracking** → Log and compare training runs and hyperparameters
- 9. **Data Pipelines** → Automated data processing and validation workflows
- 10. **Model Governance** → Policies and processes for responsible model deployment
- 11. **Rollback Strategies** → Safe deployment and quick recovery from model issues
- 12. **Performance Monitoring** → Track model accuracy, latency, and resource usage

## Safety & Limits

- 1. **Hallucination**  $\rightarrow$  Fluent but incorrect or nonsensical outputs
- 2. Alignment → Ensure model behaviour is safe, ethical, and policy-compliant
- 3. **Guardrails** → Rule-based or learned filters to prevent harmful outputs
- 4. Bias & Fairness → Detect and mitigate demographic or cultural prejudices
- 5. **Privacy & Data Leakage** → Protect sensitive information during training and inference
- 6. Adversarial Attacks → Malicious inputs designed to mislead or exploit the model
- 7. Interpretability 

  Understand how and why the model makes decisions
- 8. Calibration / Uncertainty Estimation → Avoid overconfident wrong predictions
- 9. **Red-Teaming** → Stress-test models for safety, robustness, and alignment
- 10. **Robustness Evaluation** → Test model resilience against noise, domain shifts, and edge cases
- 11. **Mechanistic Interpretability** → Understanding model internals and how features are computed
- 12. Watermarking → Methods to detect Al-generated content
- 13. **Model Editing** → Updating specific knowledge without full retraining
- 14. Constitutional  $AI \rightarrow$  Training models to follow ethical principles and safety guidelines
- 15. **Jailbreaking Prevention** → Protecting against attempts to bypass safety measures