

Description:

- Create _ex1.txt
- Link it to $-ex1_1.txt$ and $-ex1_2.txt$
- Check i-node numbers of all the files and save the output to the file ex1.txt

- You have created the file _ex1.txt.
- The file should include some content, for example, your name.
- You have linked the created file to two different files.
- You have checked the i-nodes of all 3 files and saved the output in a file ex1.txt.
- You have to put all commands that you executed in a script ex1.sh.
- \bullet You have submitted all files ex1.sh, _ex1.txt, _ex1_1.txt, _ex1_2.txt and ex1.txt.
- The results should be reproducible by running the script ex1.sh



Description:

• Create file.txt in week01 directory and access this file from week10 directory via

```
$ link <source> ex2.txt
```

• Trace all links to file.txt:

```
$ find <path> -inum inodenumber
```

• Remove all links from file.txt

```
$ find <path> -inum inodenumber -exec rm {} \;
```

• Save output of all the steps to file ex2.txt



- You have created week01 directory if it doesn't exist.
- You have created file.txt in week01 directory.
- The file should have some content, for example, your name.
- You have created week10 directory if it doesn't exist.
- You have linked the file *file.txt* with _*ex2.txt* which resides in *week10* directory.
- You have to find all links to the file *file.txt* and store the output in a file *ex2.txt*.
- You have to remove all links from the file *file.txt* and append the output to the file *ex2.txt*.
- You have to put all commands that you executed in a script ex2.sh.
- You have submitted all files ex2.sh, file.txt, ex2.txt.
- The results should be reproducible by running the script ex2.sh



Description:

- Make a file $_{-}ex3.txt$ and try the following:
- Remove execute permission for everybody
- Grant all permissions to owner and others (not group)
- Make group permissions equal to user permissions
 - What does 660 mean for ex3.txt?
 - What does 775 mean for ex3.txt?
 - What does 777 mean for ex3.txt?
- After each step save the output/answer to the ex3.txt



- You have created _ex3.txt file.
- The file should have some content, for example, your name.
- You have removed the execute permission from everyone for _ex3.txt file and saved the output in a file ex3.txt
- You have granted all permissions to only the owner and others for _ex3.txt file and appended the output in a file ex3.txt
- You have to make all group permissions equal to user permissions for _ex3.txt file and appended the output in a file ex3.txt
- You have answered the 3 questions and appended the answers to the file ex3.txt
- You have to put all commands that you executed in a script ex3.sh.
- You have submitted all files ex3.sh, _ex3.txt, ex3.txt.
- The results should be reproducible by running the script ex3.sh



Description:

- Create tmp directory with two empty files (file1, file2)
- Create one hard link named link1 to file1
- Write a program that scans *tmp* directory, locates all i-nodes with a hard link count of two or more
- For each such file it should display **together** all file names that point to the file
- Save the output of the program to ex4.txt and also submit the code ex4.c



- You have created *tmp* directory.
- You have created two empty files file1 and file2 in the folder tmp.
- You have created a hard link link1 to file1
- You should write a C program ex4.c. The program should find all files from tmp directory in which they have two or more hard links. The program should display all file names linked to the file under consideration.
- The output should look like this:
 - File Hard Links
 - file1 link1, link2, link3, ...
- You have to put all commands that you executed in a script ex4.sh.
- You have to run the program ex4.c and add the command to the script ex4.sh, also save the output of the program in a file ex4.txt
- You have submitted all files ex4.sh, ex4.txt, ex4.c.
- The results should be reproducible by running the script ex4.sh



Example: (to test your implementation)

- Based on the previous constraints. Your program should give a similar output:
 - File Hard Links
 - file1 file1, link1
 - link1 file1, link1



Exercise 5 (Optional)

Implement a simulated file system that will be fully contained in a single regular file stored on the disk. This disk file will contain directories, i-nodes, free-block information, file data blocks, etc. Choose appropriate algorithms for maintaining free-block information and for allocating data blocks (contiguous, indexed, linked). Your program will accept system commands from the user to create/delete directories, create/delete/open files, read/write from/to a selected file, and to list directory contents