





Cold
Spring
Harbor
Laboratory

RNA-Seq Module 3

Abundance Estimation

Arpad Danos, Felicia Gomez, Obi Griffith, Malachi Griffith,
My Hoang, Mariam Khanfar, Chris Miller, Kartik Singhal
Bfx workshop, October 28, 2024



Washington University in St. Louis
SCHOOL OF MEDICINE

To-do



- Open docker desktop app in the background. Then in terminal, type:
`$ docker pull griffithlab/rnabio:0.0.1`

Overview

Last week: Module 1 + 2
Alignment (HISAT2)

This week: Module 3
Expression estimation (StringTie, htseq count)


... Next week: Module 3 (continued)
Differential expression (Ballgown, edgeR)



Learning Objectives of Module 3

- Review basic concepts and popular metrics of abundance estimation:
 - raw counts vs normalized counts
- Discuss normalized count estimation tool: StringTie
- Discuss raw count estimation tool: HTSeq

Expression estimation for known genes and transcripts



3' bias
→


↓
Down-regulated

Popular metrics for abundance estimation

- Raw counts
- Normalized counts:
 - RPKM, FPKM
 - TPM


Normalized counts combat technical biases in sequenced data

- Sequencing depth



Compare expression of 1 gene in 2 samples
Sample with higher sequencing depth has more reads
→ Divided by mapped reads

- Gene length



Compare expression of 2 genes in 1 sample
Longer gene (gene B) has more reads
→ Divided by gene(transcript) length

Image adapted from novogene

What is FPKM (RPKM)?

- RPKM: **R**eads Per Kilobase of transcript per Million mapped reads.
- FPKM: **F**ragments Per Kilobase of transcript per Million mapped reads.
- Similar concept, RPKM is for single-end reads, FPKM is for paired-end reads



What is FPKM (RPKM)?

- RPKM: **R**eads Per Kilobase of transcript per Million mapped reads.
- FPKM: **F**ragments Per Kilobase of transcript per Million mapped reads.
- Similar concept, RPKM is for single-end reads, FPKM is for paired-end reads





Image: StatQuest

What is FPKM?

- FPKM attempts to normalize for **library depth** and **gene size**
 - remember – RPKM is essentially the same!
- C = number of mappable fragments for a gene (transcript)
- N = total number of mappable fragments in the library
- L = number of base pairs in the gene (transcript)
 - $$\text{FPKM} = \left(C / \left(N / 1,000,000 \right) \right) / \left(L / 1000 \right)$$

Per Million mapped reads **Per Kilobase of transcript**

$$= (10^9 \times C) / (N \times L)$$
- More reading:
 - <http://www.biostars.org/p/11378/>
 - <http://www.biostars.org/p/68126/>



How do FPKM and TPM differ?

- TPM: Transcript per Kilobase Million
- The difference is in the order of operations:

FPKM

- 1) Determine total fragment count, divide by 1,000,000 (per Million)
- 2) Divide each gene/transcript fragment count by #1 (Fragments Per Million)
- 3) Divide each FPM by length of each gene/transcript in kilobases (FPKM)

Normalize for **sequencing depth**, then normalize for **gene length**

TPM

- 1) Divide each gene/transcript fragment count by length of the transcript in kilobases (Fragments Per Kilobase)
- 2) Sum all FPK values for the sample and divide by 1,000,000 (per Million)
- 3) Divide #1 by #2 (TPM)

Normalize for **gene length**, then normalize for **sequencing depth**

- The sum of all TPMs in each sample is the same. Easier to compare across samples!
- <http://www.rna-seqblog.com/rpkm-fpkm-and-tpm-clearly-explained/>
- <https://www.ncbi.nlm.nih.gov/pubmed/22872506>

RPKM – step 1: normalize for read depth.

Gene Name	Rep1 Counts	Rep2 Counts	Rep3 Counts
A (2kb)	10	12	30
B (4kb)	20	25	60
C (1kb)	5	8	15
D (10kb)	0	0	1
Total reads:	35	45	106
Tens of reads:	3.5	4.5	10.6

For the purpose of this 4 gene example, we're scaling the total read counts by 10 instead of 1,000,000.

RPKM – step 2: normalize for gene length.

Gene Name	Rep1 RPM	Rep2 RPM	Rep3 RPM
A (2kb)	2.86	2.67	2.83
B (4kb)	5.71	5.56	5.66
C (1kb)	1.43	1.78	1.42
D (10kb)	0	0	0.09



Reads are scaled for depth (M) and gene length (K).

Gene Name	Rep1 RPKM	Rep2 RPKM	Rep3 RPKM
A (2kb)	1.43	1.33	1.42
B (4kb)	1.43	1.39	1.42
C (1kb)	1.43	1.78	1.42
D (10kb)	0	0	0.009

TPM – step 1: normalize for gene length

Original data:

Gene Name	Rep1 Counts	Rep2 Counts	Rep3 Counts
A (2kb)	10	12	30
B (4kb)	20	25	60
C (1kb)	5	8	15
D (10kb)	0	0	1

RPK – scaled by gene length:

Gene Name	Rep1 RPK	Rep2 RPK	Rep3 RPK
A (2kb)	5	6	15
B (4kb)	5	6.25	15
C (1kb)	5	8	15
D (10kb)	0	0	0.1

TPM – step 2: normalize for sequencing depth

Gene Name	Rep1 RPK	Rep2 RPK	Rep3 RPK
A (2kb)	5	6	15
B (4kb)	5	6.25	15
C (1kb)	5	8	15
D (10kb)	0	0	0.1

Total RPK: 15 20.25 45.1
Tens of RPK: 1.5 2.025 4.51

TPM – scaled by gene length and sequencing depth (M):

Gene Name	Rep1 TPM	Rep2 TPM	Rep3 TPM
A (2kb)	3.33	2.96	3.326
B (4kb)	3.33	3.09	3.326
C (1kb)	3.33	3.95	3.326
D (10kb)	0	0	0.02

Image: StatQuest

<https://www.youtube.com/watch?v=TTUrtCY2k-w>

RPKM vs TPM

RPKM

... the sums of each column are very different.

Gene Name	Rep1 RPKM	Rep2 RPKM	Rep3 RPKM
A (2kb)	1.43	1.33	1.42
B (4kb)	1.43	1.39	1.42
C (1kb)	1.43	1.78	1.42
D (10kb)	0	0	0.009
Total:	4.29	4.5	4.25

TPM

Gene Name	Rep1 TPM	Rep2 TPM	Rep3 TPM
A (2kb)	3.33	2.96	3.326
B (4kb)	3.33	3.09	3.326
C (1kb)	3.33	3.95	3.326
D (10kb)	0	0	0.02
Total:	10	10	10

$$TPM = \frac{RPKM}{\sum(RPKM)} \times 10^6$$

RPKM

Gene Name	Rep1 RPKM	Rep2 RPKM	Rep3 RPKM
A (2kb)	1.43	1.33	1.42
B (4kb)	1.43	1.39	1.42
C (1kb)	1.43	1.78	1.42
D (10kb)	0	0	0.009
Total:	4.29	4.5	4.25

With RPKM, it is harder to compare the proportion of total reads because each replicate has different total (each pie has a different size)

A 1.43 size slice represents a different proportion of reads in in different pies.



Consider 3 pies, each the same size (10).

A 3.33 sized slice is the same in each pie, and is always larger than 3.32.

TPM makes it clear that in Rep1, more of its total reads mapped to gene A than in Rep3.



TPM

Gene Name	Rep1 TPM	Rep2 TPM	Rep3 TPM
A (2kb)	3.33	2.96	3.326
B (4kb)	3.33	3.09	3.326
C (1kb)	3.33	3.95	3.326
D (10kb)	0	0	0.02
Total:	10	10	10

Image: StatQuest

Summary

- Normalized counts account for sequencing depth and gene length biases
 - RPKM \sim single-end sequencing, FPKM \sim paired-end sequencing
 - The sum of all TPMs in each sample is the same. Easier to compare across samples!

Learning Objectives of Module 3


- Review basic concepts and popular metrics of abundance estimation:
 - raw counts vs normalized counts
- Discuss normalized count estimation tool: StringTie
- Discuss raw count estimation tool: HTSeq

How does StringTie work?

- Align reads to the genome, optionally assemble super-reads and re-align
- Group reads into clusters


Infer isoforms:

- Build alternative splice graph (ASG)
- Iteratively extract the heaviest path from a splice graph
- construct a flow network
- compute maximum flow to estimate abundance
- update the splice graph by removing reads that were assigned by the flow algorithm
- This process repeats until all reads have been assigned.



Pertea et al. Nature Biotechnology, 2015

From flow network for each transcript, maximum flow is used to assemble transcript and estimate abundance



StringTie uses basic graph theory (splice graph), custom heuristics (heaviest path), more graph theory (flow network) and optimization theory (maximum flow). See StringTie paper for definitions and math.

StringTie Modes


- Expression estimation mode (“Reference Only”) ← What we will use
 - “-G \$GTF_File” AND “-e” option
 - no "novel" transcript assemblies (isoforms)
 - read alignments not overlapping reference transcripts ignored
 - Faster, especially when given limited set of reference transcripts
 - Avoids complicated steps of clustering and building alternative splice graph from scratch, skipping straight to abundance estimation
- “Reference guided mode”
 - “-G \$GTF_File” WITHOUT “-e” option
 - Both known and novel transcript assemblies
- “De novo” mode
 - NEITHER “-G \$GTF_File” NOR “-e” option
 - Novel transcript assemblies only

Pertea et al. Nature Protocols, 2016

StringTie -merge

- Merge together all gene structures from all samples
 - Some samples may only partially represent a gene structure
- Incorporates known transcripts with assembled, potentially novel transcripts
- For de novo or reference guided mode, we will rerun StringTie with the merged transcript assembly.


Pertea et al. Nature Protocols, 2016



This is the workflow we use in the exercise:

1 step: use StringTie -G and -e

Expression estimation mode ("Reference Only")



But in case you want to run Reference-guide or 'Denovo' mode, will need 3 steps: run StringTie, then StringTie --merge, then StringTie -e .

<https://ccb.jhu.edu/software/stringtie/index.shtml?t=manual>

gffcompare

- gffcompare will compare a merged transcript GTF with known annotation, also in GTF/GFF3 format
- <https://ccb.jhu.edu/software/stringtie/gff.shtml#gffcompare>

Priority	Code	Description
1	=	Complete match of intron chain
2	c	Contained
3	j	Potentially novel isoform (fragment): at least one splice junction is shared with a reference transcript
4	e	Single exon transfrag overlapping a reference exon and at least 10 bp of a reference intron, indicating a possible pre-mRNA fragment.
5	i	A transfrag falling entirely within a reference intron
6	o	Generic exonic overlap with a reference transcript
7	p	Possible polymerase run-on fragment (within 2Kbases of a reference transcript)
8	r	Repeat. Currently determined by looking at the soft-masked reference sequence and applied to transcripts where at least 50% of the bases are lower case
9	u	Unknown, intergenic transcript
10	x	Exonic overlap with reference on the opposite strand
11	s	An intron of the transfrag overlaps a reference intron on the opposite strand (likely due to read mapping errors)
12	.	(.tracking file only, indicates multiple classifications)

Learning Objectives of Module 3

- Review basic concepts and popular metrics of abundance estimation:
 - raw counts vs normalized counts
- Discuss normalized count estimation tool: StringTie
- Discuss raw count estimation tool: HTSeq

HTseq

- Raw read counts for differential expression analysis
 - Assign reads/fragments to defined genes/transcripts, get “raw counts”
 - Transcript structures could still be defined by something like Stringtie

- HTSeq (htseq-count)






- <https://htseq.readthedocs.io/>

```
htseq-count --mode intersection-strict --stranded no --minqual 1 --type exon --idattr transcript_id  
accepted_hits.sam chr22.gff > transcript_read_counts_table.tsv
```

- Caveats of ‘transcript’ analysis by htseq-count:

- Designed for genes - ambiguous reads from overlapping transcripts may not be handled!
 - <http://seqanswers.com/forums/showthread.php?t=18068>

HTSeq-count basically counts reads supporting a feature (exon, gene) by assessing overlapping coordinates

	union	intersection_strict	intersection_nonempty
	gene_A	gene_A	gene_A
	gene_A	no_feature	gene_A
	gene_A	no_feature	gene_A
	gene_A	gene_A	gene_A
	gene_A	gene_A	gene_A
	ambiguous	gene_A	gene_A
	ambiguous	ambiguous	ambiguous

Note, if gene_A and gene_B on opposite strands, sequence data is stranded, and correct HTSeq parameter set then this read may not be ambiguous

Whether a read is counted depends on the nature of overlap and “mode” selected

Summary

- Normalized counts account for sequencing depth and gene length biases
 - RPKM \sim single-end sequencing, FPKM \sim paired-end sequencing
 - The sum of all TPMs in each sample is the same. Easier to compare across samples!
- Abundance estimation tool that calculates normalized count (FPKM, TPM): StringTie
- Abundance estimation tool that calculates raw count: HTseq

Set up

- Open docker desktop app in the background. Then in terminal, type:
- `$ docker pull griffithlab/rnabio:0.0.1`
- `$ cd bfx-workshop/rnabio-workspace`
- `$ docker run -v $PWD:/workspace:rw -it griffithlab/rnabio:0.0.1 /bin/bash`

(or in case it throws error

- `$ docker run --platform linux/amd64 -v $PWD:/workspace:rw -it griffithlab/rnabio:0.0.1 /bin/bash`

)

- `$ cd workspace`
- `$ su ubuntu`
- `$ source ~/.bashrc`

Stringtie outputs

- Stringtie gives 3 metrics for expression levels: coverage, FPKM, TPM ; for 2 types : transcript and gene.
- Focus on the 'transcript.gtf' and 'gene_abundance.tsv'

+ 'e_data.ctab' : exon coordinate and corresponding coverage
 + 'i_data.ctab' : intron and corresponding coverage
 + 't_data.ctab' : transcript and corresponding coverage
 + e2t.ctab: table with two columns, e_id and t_id, denoting which exons belong to which transcripts
 + i2t.ctab: table with two columns, i_id and t_id, denoting which introns belong to which transcripts

 + transcripts.gtf : transcripts, the exons made up each transcript, coordinates, gene id/ transcript id, cov / fpkm / tpm

 + gene_abundance.tsv: genes, coordinates, and expr levels

```
# stringtie --rf -p 8 -G /home/ubuntu/workspace/rnaseq/refs/chr22_with_ERCC92.gtf -e -B -o HBR_Rep1/transcripts.gtf -A HBR_Rep1/gene_abundances.tsv /home/ubuntu/workspace/rnaseq/alignments/hisat2/HBR_Rep1.bam
# StringTie version 2.1.6
22  havana  transcript  16869478 16871126 . + . gene_id "ENSG00000237689"; transcript_id "ENST00000442403"; ref_gene_name "AC007064.24"; cov "0.0"; FPKM "0.000000"; TPM "0.000000";
22  havana  exon  16869478 16869626 . + . gene_id "ENSG00000237689"; transcript_id "ENST00000442403"; exon_number "1"; ref_gene_name "AC007064.24"; cov "0.0";
22  havana  exon  16870776 16871126 . + . gene_id "ENSG00000237689"; transcript_id "ENST00000442403"; exon_number "2"; ref_gene_name "AC007064.24"; cov "0.0";
22  havana  transcript  15790709 15791814 . + . gene_id "ENSG00000206195"; transcript_id "ENST00000458623"; ref_gene_name "DUXAP8"; cov "0.0"; FPKM "0.000000"; TPM "0.000000";
22  havana  exon  15790709 15790798 . + . gene_id "ENSG00000206195"; transcript_id "ENST00000458623"; exon_number "1"; ref_gene_name "DUXAP8"; cov "0.0";
22  havana  exon  15791017 15791152 . + . gene_id "ENSG00000206195"; transcript_id "ENST00000458623"; exon_number "2"; ref_gene_name "DUXAP8"; cov "0.0";
22  havana  exon  15791628 15791814 . + . gene_id "ENSG00000206195"; transcript_id "ENST00000458623"; exon_number "3"; ref_gene_name "DUXAP8"; cov "0.0";
```

e_data.ctab

Q~ 16869478

1

264	22	+	16869478	16869626	0	0	0.00	0.0000	0.0000	0.0000	0.0000
265	22	+	16870776	16871126	2	2	2.00	0.5698	0.5992	0.5698	0.5992

t_data.ctab

t_id	chr	strand	start	end	t_name	num_exons	length	gene_id	gene_name	cov	FPKM
1	22	-	10736171	10736283	ENST00000615943	1	113	ENSG00000277248	U2	0.000000	0.000000
2	22	-	10939388	10961338	ENST00000635667	9	749	ENSG00000283047	FRG1FP	0.000000	0.000000

gene_abundances.tsv

Gene ID	Gene Name	Reference	Strand	Start	End	Coverage	FPKM	TPM
ENSG00000237689	AC007064.24	22	+	16869478	16871126	0.000000	0.000000	0.000000
ENSG00000206195	DUXAP8	22	+	15784959	15829984	0.282236	52.024742	77.325455

Stringtie outputs

- `e_data.ctab` : exon-level expression measurements. One row per exon. Columns are `e_id` (numeric exon id), `chr`, `strand`, `start`, `end` (genomic location of the exon), and the following expression measurements for each sample:
 - `rcount` : reads overlapping the exon
 - `ucount` : uniquely mapped reads overlapping the exon
 - `mrcount` : multi-map-corrected number of reads overlapping the exon
 - `cov` : average per-base read coverage
 - `cov_sd` : standard deviation of per-base read coverage
 - `mcov` : multi-map-corrected average per-base read coverage
 - `mcov_sd` : standard deviation of multi-map-corrected per-base coverage
- `i_data.ctab` : intron- (i.e., junction-) level expression measurements. One row per intron. Columns are `i_id` (numeric intron id), `chr`, `strand`, `start`, `end` (genomic location of the intron), and the following expression measurements for each sample:
 - `rcount` : number of reads supporting the intron
 - `ucount` : number of uniquely mapped reads supporting the intron
 - `mrcount` : multi-map-corrected number of reads supporting the intron
- `t_data.ctab` : transcript-level expression measurements. One row per transcript. Columns are:
 - `t_id` : numeric transcript id
 - `chr`, `strand`, `start`, `end` : genomic location of the transcript
 - `t_name` : Cufflinks-generated transcript id
 - `num_exons` : number of exons comprising the transcript
 - `length` : transcript length, including both exons and introns
 - `gene_id` : gene the transcript belongs to
 - `gene_name` : HUGO gene name for the transcript, if known
 - `cov` : per-base coverage for the transcript (available for each sample)
 - `FPKM` : Cufflinks-estimated FPKM for the transcript (available for each sample)
- `e2t.ctab` : table with two columns, `e_id` and `t_id`, denoting which exons belong to which transcripts. These ids match the ids in the `e_data` and `t_data` tables.
- `i2t.ctab` : table with two columns, `i_id` and `t_id`, denoting which introns belong to which transcripts. These ids match the ids in the `i_data` and `t_data` tables.

<https://github.com/alyssafrazee/ballgown>

StringTie gene expression = sum of all related transcripts expressions

- Example

Gene ID	Gene Name	Reference	Strand	Start	End	Coverage	FPKM	TPM
ENSG00000206195	DUXAP8	22 +		15784959	15829984	0.282236	52.024742	77.325455

gene_abundances.tsv

52.024796


=1.711444+3.964907+41.748577
+1.772668+2.827200

Sum of expressions of all related transcripts
(transcript.gtf)

```
transcripts.gtf
# stringtie --rf -p 4 -6 /home/ubuntu/workspace/rnaseq/refs/chr22_with_ERCC92.gtf -e -B -o HBR_Repl/transcripts.gtf -A HBR_Repl/gene_abundances.tsv /home/ubuntu/workspace/rnaseq/alignments/hisat2/HBR_Repl.bam
# StringTie version 2.2.1
22   havana   transcript 15790789 15791814   +   .   gene_id "ENSG00000206195"; transcript_id "ENST00000458623"; ref_gene_name "DUXAP8"; cov "0.0"; FPKM "0.000000"; TPM "0.000000";
22   havana   exon      15790789 15790798   +   .   gene_id "ENSG00000206195"; transcript_id "ENST00000458623"; exon_number "1"; ref_gene_name "DUXAP8"; cov "0.0";
22   havana   exon      15791017 15791152   +   .   gene_id "ENSG00000206195"; transcript_id "ENST00000458623"; exon_number "2"; ref_gene_name "DUXAP8"; cov "0.0";
22   havana   exon      15791628 15791814   +   .   gene_id "ENSG00000206195"; transcript_id "ENST00000458623"; exon_number "3"; ref_gene_name "DUXAP8"; cov "0.0";
22   havana   transcript 15790959 15798346   +   .   gene_id "ENSG00000271127"; transcript_id "ENST00000603308"; ref_gene_name "LL2ZNC03-N64E9.1"; cov "0.0"; FPKM "0.000000"; TPM "0.000000";
22   havana   exon      15790959 15798346   +   .   gene_id "ENSG00000271127"; transcript_id "ENST00000603308"; exon_number "1"; ref_gene_name "LL2ZNC03-N64E9.1"; cov "0.0";
22   havana   transcript 15805263 15815897   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000448946"; ref_gene_name "BMS1P22"; cov "0.0"; FPKM "0.000000"; TPM "0.000000";
22   havana   exon      15805263 15806011   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000448946"; exon_number "1"; ref_gene_name "BMS1P22"; cov "0.0";
22   havana   exon      15813394 15813481   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000448946"; exon_number "2"; ref_gene_name "BMS1P22"; cov "0.0";
22   havana   exon      15815575 15815897   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000448946"; exon_number "3"; ref_gene_name "BMS1P22"; cov "0.0";
22   havana   transcript 15805812 15820884   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000609679"; ref_gene_name "BMS1P22"; cov "0.0"; FPKM "0.000000"; TPM "0.000000";
22   havana   exon      15805812 15806011   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000609679"; exon_number "1"; ref_gene_name "BMS1P22"; cov "0.0";
22   havana   exon      15813394 15813481   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000609679"; exon_number "2"; ref_gene_name "BMS1P22"; cov "0.0";
22   havana   exon      15820621 15820884   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000609679"; exon_number "3"; ref_gene_name "BMS1P22"; cov "0.0";
22   havana   transcript 15805847 15806593   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000414726"; ref_gene_name "BMS1P22"; cov "0.0"; FPKM "0.000000"; TPM "0.000000";
22   havana   exon      15805847 15806011   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000414726"; exon_number "1"; ref_gene_name "BMS1P22"; cov "0.0";
22   havana   exon      15806356 15806593   -   .   gene_id "ENSG00000232775"; transcript_id "ENST00000414726"; exon_number "2"; ref_gene_name "BMS1P22"; cov "0.0";
22   havana   transcript 15826566 15827187   +   .   gene_id "ENSG00000271672"; transcript_id "ENST00000456786"; ref_gene_name "DUXAP8"; cov "0.0"; FPKM "0.000000"; TPM "0.000000";
22   havana   exon      15826566 15827187   +   .   gene_id "ENSG00000271672"; transcript_id "ENST00000456786"; exon_number "1"; ref_gene_name "DUXAP8"; cov "0.0";
22   StringTie transcript 15784959 15827434 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000413768"; ref_gene_name "DUXAP8"; cov "0.033293"; FPKM "1.711444"; TPM "2.543754";
22   StringTie exon      15784959 15785057 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000413768"; exon_number "1"; ref_gene_name "DUXAP8"; cov "0.048116";
22   StringTie exon      15787172 15787282 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000413768"; exon_number "2"; ref_gene_name "DUXAP8"; cov "0.056671";
22   StringTie exon      15788585 15788699 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000413768"; exon_number "3"; ref_gene_name "DUXAP8"; cov "0.176835";
22   StringTie exon      15788828 15788931 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000413768"; exon_number "4"; ref_gene_name "DUXAP8"; cov "0.194825";
22   StringTie exon      15790661 15790798 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000413768"; exon_number "5"; ref_gene_name "DUXAP8"; cov "0.095874";
22   StringTie exon      15791018 15791152 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000413768"; exon_number "6"; ref_gene_name "DUXAP8"; cov "0.000000";
22   StringTie exon      15815476 15815566 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000413768"; exon_number "7"; ref_gene_name "DUXAP8"; cov "0.048895";
22   StringTie transcript 15826142 15827434 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000413768"; exon_number "8"; ref_gene_name "DUXAP8"; cov "0.000000";
22   StringTie exon      15784963 15785057 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000437781"; ref_gene_name "DUXAP8"; cov "0.077138"; FPKM "3.064907"; TPM "5.893124";
22   StringTie exon      15784963 15785057 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000437781"; exon_number "1"; ref_gene_name "DUXAP8"; cov "0.129166";
22   StringTie exon      15787172 15787282 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000437781"; exon_number "2"; ref_gene_name "DUXAP8"; cov "0.145905";
22   StringTie exon      15788552 15788699 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000437781"; exon_number "3"; ref_gene_name "DUXAP8"; cov "0.384827";
22   StringTie exon      15788828 15788931 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000437781"; exon_number "4"; ref_gene_name "DUXAP8"; cov "0.499899";
22   StringTie exon      15790661 15790798 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000437781"; exon_number "5"; ref_gene_name "DUXAP8"; cov "0.246972";
22   StringTie exon      15791017 15791152 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000437781"; exon_number "6"; ref_gene_name "DUXAP8"; cov "0.000000";
22   StringTie exon      15815476 15815566 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000437781"; exon_number "7"; ref_gene_name "DUXAP8"; cov "0.185346";
22   StringTie transcript 15826142 15827780 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000437781"; exon_number "8"; ref_gene_name "DUXAP8"; cov "0.000000";
22   StringTie transcript 15784968 15819165 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000383838"; ref_gene_name "DUXAP8"; cov "0.812142"; FPKM "41.748577"; TPM "62.051777";
22   StringTie exon      15784968 15785057 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000383838"; exon_number "1"; ref_gene_name "DUXAP8"; cov "0.736258";
22   StringTie exon      15787172 15787282 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000383838"; exon_number "2"; ref_gene_name "DUXAP8"; cov "0.183195";
22   StringTie exon      15788552 15788699 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000383838"; exon_number "3"; ref_gene_name "DUXAP8"; cov "0.473784";
22   StringTie exon      15788828 15788931 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000383838"; exon_number "4"; ref_gene_name "DUXAP8"; cov "0.299822";
22   StringTie exon      15790661 15790798 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000383838"; exon_number "5"; ref_gene_name "DUXAP8"; cov "0.195341";
22   StringTie exon      15791017 15791152 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000383838"; exon_number "6"; ref_gene_name "DUXAP8"; cov "0.000000";
22   StringTie exon      15815476 15815566 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000383838"; exon_number "7"; ref_gene_name "DUXAP8"; cov "0.568808";
22   StringTie transcript 15826142 15829984 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000383838"; exon_number "8"; ref_gene_name "DUXAP8"; cov "0.382325";
22   StringTie transcript 15784992 15829984 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000447898"; ref_gene_name "DUXAP8"; cov "0.034848"; FPKM "1.772668"; TPM "2.634753";
22   StringTie exon      15784992 15785057 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000447898"; exon_number "1"; ref_gene_name "DUXAP8"; cov "0.192464";
22   StringTie exon      15791017 15791152 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000447898"; exon_number "2"; ref_gene_name "DUXAP8"; cov "0.000000";
22   StringTie exon      15815476 15815566 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000447898"; exon_number "3"; ref_gene_name "DUXAP8"; cov "0.189854";
22   StringTie transcript 15826142 15829984 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000447898"; exon_number "4"; ref_gene_name "DUXAP8"; cov "0.831267";
22   StringTie transcript 15818493 15819134 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000607933"; ref_gene_name "DUXAP8"; cov "0.054998"; FPKM "2.827200"; TPM "4.202127";
22   StringTie exon      15818493 15819134 1000 + . gene_id "ENSG00000206195"; transcript_id "ENST00000607933"; exon_number "1"; ref_gene_name "DUXAP8"; cov "0.054998";
22   StringTie transcript 15823197 15823980 1000 + . gene_id "ENSG00000272872"; transcript_id "ENST00000602865"; ref_gene_name "LL2ZNC03-N14H1.1"; cov "0.749288"; FPKM "38.517124"; TPM "57.248798";
```

Strandedness

<https://rnabio.org/module-09-appendix/0009/12/01/StrandSettings/>



The second read (read 2) is from the original RNA strand


The first read (read 1) is from the original RNA strand

Why is this so important?

- If you use wrong directionality parameter in the read counting step with HTSeq, the reads are considered to be from the wrong strand. This means that in the case where there is no gene on that other strand, you won't get any counts, and if there is a gene in the same location on the other strand, your reads are counted for the wrong gene.
- If you use wrong directionality parameter in the reference alignment step, the XS tag in the resulting BAM file will contain wrong strand information. The XS tag is used by transcript assembly programs like Cufflinks and Stringtie, and also Cuffdiff uses it.


<https://chipster.csc.fi/manual/library-type-summary.html#:~:text=second%2Dstrand%20%3D%20directional%2C%20where,is%20from%20the%20opposite%20strand.>

Non-Stranded Library Prep



<https://www.azenta.com/blog/stranded-versus-non-stranded-rna-seq>

Stranded Library Prep



Library Preparation Selection Guide

Choosing the right library preparation method depends on several factors, including your experimental objective, budget, and availability of a reference transcriptome for your organism.

The most important consideration is the objective of your experiment. Stranded RNA-Seq is strongly recommended if you're trying to accomplish one or more of the following, as it's important to capture information about transcript directionality:

- Identify antisense transcripts
- Annotate a genome
- Discover novel transcripts

Non-stranded RNA-Seq, on the other hand, is often sufficient for measuring gene expression in organisms with well-annotated genomes. With a reference transcriptome, you can infer orientation for most of the sequencing reads. Since there are fewer steps than stranded library prep, the benefits of this approach are lower cost, simpler execution, and greater recovery of material.

Also, when comparing the results of a new experiment to older ones, many researchers prefer using the same RNA-Seq approach. It enables an apples-to-apples comparison of the data.

Key Takeaways

- Stranded RNA-Seq enables you to determine RNA orientation from each sequencing read; this information can't be directly obtained from non-stranded approaches
- By differentiating the first and second strands of cDNA, stranded library preparation preserves the directionality of the RNA molecule
- Certain applications require a stranded approach; however, non-stranded RNA-Seq is suitable for many NGS projects

<https://www.azenta.com/blog/stranded-versus-non-stranded-rna-seq>