

40 Days and 40 Nights

Martin Morgan L. Shawn Matott

2020-04-17

Contents

Motivation	7
Introduction	7
What to expect	7
1 Basics	11
1.1 Day 1 (Monday) Zoom orientation	11
1.2 Day 2: Vectors and variables	21
1.3 Day 3: <code>factor()</code> , <code>Date()</code> , and <code>NA</code>	23
1.4 Day 4: Working with variables	27
1.5 Day 5 (Friday) Zoom check-in	30
1.6 Day 6: <i>R</i> scripts	39
1.7 Day 7: Saving data	41
2 The data frame	45
2.1 Day 8 (Monday) Zoom check-in	45
2.2 Day 9: Creation and manipulation	53
2.3 Day 10: <code>subset()</code> , <code>with()</code> , and <code>within()</code>	60
2.4 Day 11: <code>aggregate()</code> and an initial work flow	62
2.5 Day 12 (Friday) Zoom check-in	69
2.6 Day 13:	69
2.7 Day 14	69

3	Packages and the ‘tidyverse’	71
3.1	Day 15 (Monday) Zoom check-in	72
3.2	CRAN	72
3.3	The ‘tidyverse’ of packages	72
3.4	Day 16	72
3.5	Day 17	72
3.6	Day 18	72
3.7	Day 19 (Friday) Zoom check-in	72
3.8	Day 20	72
3.9	Day 21	72
4	Maps and spatial statistics	73
4.1	Day 22 (Monday) Zoom check-in	73
4.2	Day 23	73
4.3	Day 24	73
4.4	Day 25	73
4.5	Day 26 (Friday) Zoom check-in	73
4.6	Day 27	73
4.7	Day 28	73
5	Bioinformatics with Bioconductor	75
5.1	Day 29 (Monday) Zoom check-in	75
5.2	Day 30	75
5.3	Day 31	75
5.4	Day 32	75
5.5	Day 33 (Friday) Zoom check-in	75
5.6	Day 34	75
5.7	Day 35	75

<i>CONTENTS</i>	5
6 Collaboration	77
6.1 5 Days (Monday) Zoom check-in	77
6.2 4 Days	77
6.3 3 Days	77
6.4 2 Days	77
6.5 Today! (Friday) Zoom check-in	77
Frequently asked questions	79

Motivation

This is a WORK IN PROGRESS.

This course was suggested and enabled by Adam Kisailus and Richard Hersherberger. It is available for Roswell Park graduate students.

Introduction

The word ‘quarantine’ is from the 1660’s and refers to the forty days (Italian *quaranta giorni*) a ship suspected of carrying disease was kept in isolation.

What to do in a quarantine? The astronaut Scott Kelly spent nearly a year on the International Space Station. In a New York Times opinion piece he says, among other things, that ‘you need a hobby’, and what better hobby than a useful one? Let’s take the opportunity provided by COVID-19 to learn R for statistical analysis and comprehension of data. Who knows, it may be useful after all this is over!

What to expect

We’ll meet via zoom twice a week, Mondays and Fridays, for one hour. We’ll use this time to make sure everyone is making progress, and to introduce new or more difficult topics. Other days we’ll have short exercises and activities that hopefully provide an opportunity to learn at your own speed.

We haven’t thought this through much, but roughly we might cover:

- Week 1: We’ll start with the basics of installing and using R. We’ll set up *R* and *RStudio* on your local computer, or if that doesn’t work use a cloud-based *RStudio*. We’ll learn the basics of *R* – numeric, character, logical, and other vectors; variables; and slightly more complicated representations of ‘factors’ and dates. We’ll also use *RStudio* to write a

script that allows us to easily re-create an analysis, illustrating the power concept of *reproducible research*.


```
activity <- c("check e-mail", "breakfast", "conference call", "webinar", "walk")
minutes_per_activity <- c(20, 30, 60, 60, 60)
minutes_per_activity >= 60
## [1] FALSE FALSE TRUE TRUE TRUE
activity[minutes_per_activity >= 60]
## [1] "conference call" "webinar" "walk"
```

- Week 2: The `data.frame`. This week is all about *R*'s `data.frame`, a versatile way of representing and manipulating a table (like an Excel spreadsheet) of data. We'll learn how to create, write, and read a `data.frame`; how to go from data in a spreadsheet in Excel to a `data.frame` in *R*; and how to perform simple manipulations on a `data.frame`, like creating a subset of data, summarizing values in a column, and summarizing values in one column based on a grouping variable in another column.

```
url = "https://raw.githubusercontent.com/nytimes/covid-19-data/master/us-counties.csv"
cases <- read.csv(url)
erie <- subset(cases, county == "Erie" & state == "New York")
tail(erie)
##           date county    state fips cases deaths
## 50071 2020-04-11  Erie New York 36029  1472    62
## 52744 2020-04-12  Erie New York 36029  1571    75
## 55428 2020-04-13  Erie New York 36029  1624    86
## 58128 2020-04-14  Erie New York 36029  1668    99
## 60844 2020-04-15  Erie New York 36029  1751   110
## 63572 2020-04-16  Erie New York 36029  1850   115
```

- Week 3: Packages for extending *R*. A great strength of *R* is its extensibility through packages. We'll learn about CRAN, and install and use the 'tidyverse' suite of packages. The tidyverse provides us with an alternative set of tools for working with tabular data, and We'll use publicly available data to explore the spread of COVID-19 in the US. We'll read, filter, mutate (change), and select subsets of the data, and group data by one column (e.g., 'state') to create summaries (e.g., cases per state). We'll also start to explore data visualization, creating our first plots of the spread of COVID-19.

```
library(dplyr)
library(ggplot2)
## ...additional commands
```

- Week 4: Maps. This week will be a specialized topic, tackling relatively advanced challenges associated with spatial visualization.
- Week 5: Bioinformatic analysis with *Bioconductor*. *Bioconductor* is a collection of more than 1800 *R* packages for the statistical analysis and comprehension of high-throughput genomic data. We'll use *Bioconductor* to look at COVID-19 genome sequences, and to explore emerging genomic data relevant to the virus.
- Week 6: COVID-19 has really shown the value of open data and collaboration. In the final week of our quarantine, we'll explore collaboration; developing independent and group projects that synthesize the use of *R* to explore data. We'll learn tools of collaboration including git and github, and develop 'best practices' for robust, reproducible research. We'll learn about writing 'markdown' reports to share our project with others.

Chapter 1

Basics

1.1 Day 1 (Monday) Zoom orientation

1.1.1 Logistics (10 minutes)

Course material

- Available at <https://mtmorgan.github.io/QuaRantine>

Cadence

- Monday and Friday group zoom sessions – these will review and troubleshoot previous material, and outline goals for the next set of independent activities.
- Daily independent activities – most of your learning will happen here!

Communicating

- We'll use Microsoft Teams (if most participants have access to the course)
- Visit [Microsoft teams](#) and sign in with your Roswell username (e.g., MA38727@RoswellPark.org) and the password you use to check email, etc. Join the 'QuaRantine' team.

1.1.2 Installing *R* and *RStudio* (25 minutes, Shawn)

What is R?

- A programming language for statistical computing, data analysis and scientific graphics.
- Open-source with a large (and growing) user community.
- Currently in the top 10 most popular languages according to the tiobe index.

What is RStudio?


- RStudio provides an integrated editor and shell environment to make R programming easier. Some of the more useful features include:
 - Syntax highlighting and color coding
 - Easy switching between shell and editor
 - Dynamic help and docs

Installing *R* and *RStudio*

- Two ways to “get” RStudio:
 - Install on your laptop or desktop
 - * Download the free desktop installer [here](#)
 - Use the [rstudio.cloud](#) resource
 - * Visit [rstudio.cloud](#), sign-up, and sign-on


The preferred approach for this course is to try to install R and RStudio on your own computer

- Windows Users:
 - Download R for Windows and run the installer. Avoid, if possible, installing as administrator.
 - Download RStudio for Windows and run the installer.
 - Test the installation by launching RStudio. You should end up with a window like the screen shot below.
- Mac Users:
 - Download R for macOS (OS X 10.11, El Capitan, and later) or older macOS and run the installer.
 - Download RStudio for macOS and run the installer.
 - Test the installation by launching RStudio. You should end up with a window like the screen shot below.




An ALTERNATIVE, if installing on your own computer does not work:

- Do the following only if you are NOT ABLE TO INSTALL R and RStudio.
- Visit rstudio.cloud. Click the 'Get Started' button, and create an account (I used my gmail account...). You should end up at a screen like the following.



- Click on the 'New Project' button, to end up with a screen like the one below. Note the 'Untitled Project' at the top of the screen; click on it to name your project, e.g., 'QuaRantine'.





Breakout Room

At this point you should have RStudio running either via your desktop installation or through rstudio.cloud. If not, please let us know via the chat window and we'll invite you to a breakout room to troubleshoot your installation.

1.1.3 Basics of *R* (25 minutes)

R as a simple calculator

```
1 + 2  
## [1] 3
```

R Console Output

Enter this in the console:

```
2 + 3 * 5  
## [1] 17
```

Q: what's the [1] all about in the output?

A: It's the index of the first entry in each line.

This is maybe a better example:

```
1:30
## [1] 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25
## [26] 26 27 28 29 30
```

Displaying help in the R Console

? <command-name>

- Some examples:

```
? cat
? print
```

Variables

Naming variables in *R*

- A variable name can contain letters, numbers, and the dot . or underline _ characters. Variables should start with a letter.
- Try entering these in the console:


```
y = 2
try.this = 33.3
oneMoreTime = "woohoo"
```

- Now try these:


```
2y = 2
_z = 33.3
function = "oops, my bad"
```

R is case sensitive (*R* != *r*)

```
R = 2
r = 3
R == r
## [1] FALSE
```

Variable Assignment

- You may use = or <- (and even ->) to assign values to a variable.


```
x <- 2 + 3 * 5
y = 2 + 3 * 6
2 + 3 * 7 -> z
cat(x, y, z)
## 17 20 23
```

R's four basic 'atomic' data types

- Numeric (includes integer, double, etc.)
 - 3.14, 1, 2600
- Character (string)
 - "hey, I'm a string"
 - 'single quotes are ok too'
- Logical
 - TRUE or FALSE (note all caps)
- NA
 - not assigned (no known value)

Use `class()` to query the class of data:

```
a <- 5
class(a)
## [1] "numeric"
```

Use `as.` to coerce a variable to a specific data type

```
a <- as.integer(5)
class(a)
## [1] "integer"
```

```
d <- as.logical(a)
d
## [1] TRUE
class(d)
## [1] "logical"
```

Using Logical Operators

Equivalence test (`==`):

```
1 == 2
## [1] FALSE
```

Not equal test (!=):

```
1 != 2
## [1] TRUE
```

less-than (<) and greater-than (>):

```
18 > 44
## [1] FALSE
3 < 204
## [1] TRUE
```

Logical Or (|):

```
(1 == 2) | (2 == 2)
## [1] TRUE
```

Logical And (&):

```
(1 == 2) & (2 == 2)
## [1] FALSE
```

Objects and Vectors in R

Objects

- R stores everything, variables included, in ‘objects’.

```
x <- 2.71


# print the value of an object
print(x)
## [1] 2.71

# determine class or internal type of an object
class(x)
## [1] "numeric"

# TRUE if an object has not been assigned a value
is.na(x)
## [1] FALSE
```

Vectors

- ‘Vectors’ and ‘data frames’ are the bread and butter of R
- Vectors consist of several elements of the same class
 - e.g. a vector of heart rates, one per patient



Data frames (data.frame)

- Data frames are structures that can contain columns of various types
 - e.g. height, weight, age, heart rate, etc.
 - Handy containers for experimental data
 - Analogous to spreadsheet data
 - More on Data Frames throughout the week!

Working with Vectors

Creating a Vector

- Use the `c()` function

```
name <- c("John Doe", "Jane Smith", "MacGillicuddy Jones", "Echo Shamus")
age <- c(36, 54, 82, 15)
favorite_color <- c("red", "orange", "green", "black")

## print the vectors
name
## [1] "John Doe"           "Jane Smith"          "MacGillicuddy Jones"
## [4] "Echo Shamus"
age
## [1] 36 54 82 15
favorite_color
## [1] "red"    "orange" "green"  "black"
```

Accessing vector data

- Use numerical indexing
- R uses 1-based indexing
 - 1st vector element has index of 1
 - 2nd has an index of 2
 - 3rd has an index of 3
 - and so on

```
name[1]
## [1] "John Doe"
age[3]
## [1] 82
```

- R supports “slicing” (i.e. extracting multiple items)

```
favorite_color[c(2, 3)]
## [1] "orange" "green"
```

- Negative indices are omitted

```
age[-2]
## [1] 36 82 15
```

Some Useful Vector Operations

- `length()`: number of elements
- `sum()`: sum of all element values
- `unique()`: distinct values
- `sort()`: sort elements, omitting NAs
- `order()`: indices of sorted elements, NAs are last
- `rev()`: reverse the order
- `summary()`: simple statistics

```
a <- c(5, 5, 6, 7, 8, 4)
sum(a)
## [1] 35
length(a)
## [1] 6
unique(a)
## [1] 5 6 7 8 4
sort(a)
```

```
## [1] 4 5 5 6 7 8
order(a)
## [1] 6 1 2 3 4 5
a[order(a)]
## [1] 4 5 5 6 7 8
rev(a)
## [1] 4 8 7 6 5 5
summary(a)
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##    4.000   5.000   5.500   5.833   6.750   8.000
```

Handling Missing Data

- First consider the reason(s) for the missing data
 - e.g. concentrations that are below detectable levels?
- Sometimes NAs in data require special statistical methods
- Other times we can safely discard / ignore NA entries
- To remove NAs prior to a calculation:

```
y = c(1,NA,3,2,NA)
sum(y, na.rm=TRUE)
## [1] 6
```

Wrapping up day 1

The goal for today was to rapidly cover some of the essential aspects of R programming. For the remainder of the week you'll work at your own pace to get more of a hands-on deep dive into this material. If you run into trouble please don't hesitate to ask for help via Teams (QuaRantine Team), slack (QuaRantine Course), or email (Drs. Matott and Morgan) — whatever works best for you!

1.2 Day 2: Vectors and variables

Our overall goal for the next few days is to use *R* to create a daily log of quarantine activities.

Our goal for today is to become familiar with *R* vectors. Along the way we'll probably make data entry and other errors that will start to get us comfortable with *R*.

If you run into problems, reach out to the slack channel for support!

The astronaut Scott Kelly said that to survive a year on the International Space Station he found it essential to

- Follow a schedule – plan your day, and stick to the plan
- Pace yourselves – you’ve got a long time to accomplish tasks, so don’t try to get everything done in the first week.
- Go outside – if Scott can head out to space, we should be able to make it to the back yard or around the block!
- Get a hobby – something not work related, and away from that evil little screen. Maybe it’s as simple as rediscovering the joy of reading.
- Keep a journal
- Take time to connect – on a human level, with people you work with and people you don’t!
- Listen to experts – Scott talked about relying on the mission controllers; for us maybe that’s watching webinars or taking courses in new topics!
- Wash your hands!

I wanted to emphasize ‘follow a schedule’ and ‘keep a journal’. How can *R* help? Well, I want to create a short record of how I spend today, day 2 of my quarantine.

My first goal is to create *vectors* describing things I plan to do today. Let’s start with some of these. To get up to speed, type the following into the *R* console, at the `>` prompt

```
1 + 2
```

Press the carriage return and remind yourself that *R* is a calculator, and knows how to work with numbers!

Now type an activity in your day, for instance I often start with

```
"check e-mail"
```

Now try assigning that to a variable, and displaying the variable, e.g.,

```
activity <- "check e-mail"
activity
## [1] "check e-mail"
```

OK, likely you have several activities scheduled. Create a *vector* of a few of these by concatenating individual values

```
c("check e-mail", "breakfast", "conference call", "webinar", "walk")
## [1] "check e-mail"      "breakfast"         "conference call"   "webinar"
## [5] "walk"
```

Assign these to a variable

```
activity <- c("check e-mail", "breakfast", "conference call", "webinar", "walk")
activity
## [1] "check e-mail"      "breakfast"         "conference call"   "webinar"
## [5] "walk"
```

Create another vector, but this time the vector should contain the minutes spent on each activity

```
minutes <- c(20, 30, 60, 60, 60)
minutes
## [1] 20 30 60 60 60
```

So I spent 20 minutes checking email, 30 minutes having breakfast and things like that, I was in a conference call for 60 minutes, and then attended a webinar where I learned new stuff for another 60 minutes. Finally I went for a walk to clear my head and remember why I'm doing things.

Apply some basic functions to the variables, e.g., use `length()` to demonstrate that you for each `activity` you have recorded the `minutes`.

```
length(activity)
## [1] 5
length(minutes)
## [1] 5
```

Use `tail()` to select the last two activities (or `head()` to select the first two...)

```
tail(activity, 2)
## [1] "webinar" "walk"
tail(minutes, 2)
## [1] 60 60
```

R has other types of vectors. Create a logical vector that indicates whether each activity was 'work' activity' or something you did for your own survival. We'll say that checking email is a work-related activity!

```
is_work <- c(TRUE, FALSE, TRUE, TRUE, FALSE)
is_work
## [1] TRUE FALSE TRUE TRUE FALSE
```

1.3 Day 3: `factor()`, `Date()`, and `NA`

Yesterday we learned about `character`, `numeric`, and `logical` vectors in *R* (you may need to revisit previous notes and re-create these variables)

```

activity
## [1] "check e-mail"      "breakfast"          "conference call" "webinar"
## [5] "walk"
minutes
## [1] 20 30 60 60 60
is_work
## [1] TRUE FALSE TRUE TRUE FALSE

```

Today we will learn about slightly more complicated vectors.

We created the logical vector `is_work` to classify each `activity` as either work-related or not. What if we had several different categories? For instance, we might want to classify the activities into categories inspired by astronaut Kelly's guidance. Categories might include: `connect` with others; go outside and `exercise`; `consult` experts; get a `hobby`; and (my own category, I guess) perform `essential` functions like eating and sleeping. So the values of `activity` could be classified as

```

classification <-
  c("connect", "essential", "connect", "consult", "exercise")

```

I want to emphasize a difference between the `activity` and `classification` variables. I want `activity` to be a character vector that could contain any description of an activity. But I want `classification` to be terms only from a limited set of possibilities. In *R*, I want `classification` to be a special type of vector called a **factor**, with the *values* of the vector restricted to a set of possible *levels* that I define. I create a factor by enumerating the possible *levels* that the factor can take on

```

levels <- c("connect", "exercise", "consult", "hobby", "essential")

```

And then tell *R* that the vector `classification` should be a factor with values taken from a particular set of levels

```

classification <- factor(
  c("connect", "essential", "connect", "consult", "exercise"),
  levels = levels
)
classification
## [1] connect essential connect consult exercise
## Levels: connect exercise consult hobby essential

```

Notice that `activity` (a character vector) displays differently from `classification` (a factor)


```
activity
## [1] "check e-mail"      "breakfast"         "conference call" "webinar"
## [5] "walk"
classification
## [1] connect essential connect consult exercise
## Levels: connect exercise consult hobby essential
```

Also, some of the levels (e.g., `hobby`) have not been part of our schedule yet, but the factor still ‘knows’ about the level.

Notice also what happens when I try to use a value (`disconnect`) that is not a level of a factor

```
factor(c("connect", "disconnect"), levels = levels)
## [1] connect <NA>
## Levels: connect exercise consult hobby essential
```

The value with the unknown level is displayed as `NA`, for ‘not known’. `NA` values can be present in any vector, e.g.,

```
c(1, 2, NA, 4)
## [1] 1 2 NA 4
c("walk", "talk", NA)
## [1] "walk" "talk" NA
c(NA, TRUE, FALSE, TRUE, TRUE)
## [1] NA TRUE FALSE TRUE TRUE
```

This serves as an indication that the value is simply not available. Use `NA` rather than adopting some special code (e.g., ‘-99’) to indicate when a value is not available.

One other type of vector we will work a lot with are dates. All of my activities are for today, so I’ll start with a character vector with the same length as my activity vector, each indicating the date in a consistent month-day-year format

```
dates <- c("04-14-2020", "04-14-2020", "04-14-2020", "04-14-2020", "04-14-2020")
dates
## [1] "04-14-2020" "04-14-2020" "04-14-2020" "04-14-2020" "04-14-2020"
```

Incidentally, I could do this more efficiently using the `replicate` function

```
rep("04-14-2020", 5)
## [1] "04-14-2020" "04-14-2020" "04-14-2020" "04-14-2020" "04-14-2020"
```

And even better use `length()` to know for sure how many times I should replicate the character vector

```
rep("04-14-2020", length(activity))
## [1] "04-14-2020" "04-14-2020" "04-14-2020" "04-14-2020" "04-14-2020"
```

`dates` is a character vector, but it has special meaning as a calendar date, *R* has a `Date` class that knows how to work with dates, for instance to calculate the number of days between two dates. We will *coerce* `date` to an object of class `Date` using a function `as.Date`. Here's our first attempt...

```
as.Date(dates)
```

... but this results in an error:

```
Error in charToDate(x) :
  character string is not in a standard unambiguous format
```

R doesn't know the format (month-day-year) of the dates we provide. The solution is to add a second argument to `as.Date()`. The second argument is a character vector that describes the date format. The format we use is `"%m-%d-%Y"`, which says that we provide the %month first, then a hyphen, then the %day, another hyphen, and finally the four-digit %Year.

```
as.Date(dates, format = "%m-%d-%Y")
## [1] "2020-04-14" "2020-04-14" "2020-04-14" "2020-04-14" "2020-04-14"
```

Notice that the format has been standardized to year-month-day. Also notice that although the original value of `date` and the return from `as.Date()` look the same, they are actually of different *class*.

```
class(date)
## [1] "function"
class(as.Date(dates, format = "%m-%d-%Y"))
## [1] "Date"
```

R will use the information about class to enable specialized calculation on dates, e.g., to sort them or to determine the number of days between different dates. So here's our `date` vector as a `Date` object.

```
dates <- rep("04-14-2020", length(activity))
date <- as.Date(dates, format = "%m-%d-%Y")
date
## [1] "2020-04-14" "2020-04-14" "2020-04-14" "2020-04-14" "2020-04-14"
```

OK, time for a walk! See you tomorrow!

1.4 Day 4: Working with variables

Remember that *R* can act as a simple calculator, and that one can create new variables by assignment

```
x <- 1
x + 1
## [1] 2
y <- x + 1
y
## [1] 2
```

Let's apply these ideas to our `minutes` vector from earlier in the week.

```
minutes <- c(20, 30, 60, 60, 60)
```

We can perform basic arithmetic on vectors. Suppose we wanted to increase the time of each activity by 5 minutes

```
minutes + 5
## [1] 25 35 65 65 65
```

or to increase the time of the first two activities by 5 minutes, and the last three activities by 10 minutes

```
minutes + c(5, 5, 10, 10, 10)
## [1] 25 35 70 70 70
```

R has a very large number of *functions* that can be used on vectors. For instance, the average time spent on activities is

```
mean(minutes)
## [1] 46
```

while the total amount of time is

```
sum(minutes)
## [1] 230
```

Explore other typical mathematical transformations, e.g., `log()`, `log10()`, `sqrt()` (square root), ... Check out the help pages for each, e.g., `?log`.

Explore the consequences of `NA` in a vector for functions like `mean()` and `sum()`.

```
x <- c(1, 2, NA, 3)
mean(x)
## [1] NA
```

R is saying that, since there is an unknown (NA) value in the vector, it cannot possibly know what the mean is! Tell *R* to remove the missing values before performing the calculation by adding the `na.rm = TRUE` argument

```
mean(x, na.rm = TRUE)
## [1] 2
```

Check out the help page `?mean` to find a description of the `na.rm` and other arguments.

It's possible to perform logical operations on vectors, e.g., to ask which activities lasted 60 minutes or more

```
minutes >= 60
## [1] FALSE FALSE TRUE TRUE TRUE
```

Here's our activity vector

```
activity <- c("check e-mail", "breakfast", "conference call", "webinar", "walk")
```

The elements of this vector are numbered from 1 to 5. We can create a new vector that is a subset of this vector using `[` and an integer index, e.g., the second activity is

```
activity[2]
## [1] "breakfast"
```

The index can actually be a vector, so we could choose the second and fourth activity as

```
index <- c(2, 4)
activity[index]
## [1] "breakfast" "webinar"
```

In fact, we can use logical vectors for subsetting. Consider the activities that take sixty minutes or longer:

```
index <- minutes >= 60
activity[index]
## [1] "conference call" "webinar"          "walk"
```

We had previously characterized the activities as ‘work’ or otherwise.

```
is_work <- c(TRUE, FALSE, TRUE, TRUE, FALSE)
```

Use `is_work` to subset `activity` and identify the work-related activities

```
activity[is_work]
## [1] "check e-mail"      "conference call" "webinar"
```

How many minutes were work-related?

```
work_minutes <- minutes[is_work]
sum(work_minutes)
## [1] 140
```

What about not work related? `!` negates logical vectors, so

```
is_work
## [1] TRUE FALSE TRUE TRUE FALSE
!is_work
## [1] FALSE TRUE FALSE FALSE TRUE
non_work_minutes <- minutes[!is_work]
sum(non_work_minutes)
## [1] 90
```

Note that it doesn’t make sense to take the `mean()` of a character vector like `activity`, and *R* signals a warning and returns `NA`

```
mean(activity)
## Warning in mean.default(activity): argument is not numeric or logical: returning
## NA
## [1] NA
```

Nonetheless, there are many functions that *do* work on character vectors, e.g., the number of letters in each element `nchar()`, or transformation to upper-case

```
nchar(activity)
## [1] 12 9 15 7 4
toupper(activity)
## [1] "CHECK E-MAIL"      "BREAKFAST"          "CONFERENCE CALL" "WEBINAR"
## [5] "WALK"
```

1.5 Day 5 (Friday) Zoom check-in

1.5.1 Review and trouble shoot (25 minutes; Martin)

Data representations

‘Atomic’ vectors

```
activity <- c("check e-mail", "breakfast", "conference call", "webinar", "walk")
minutes <- c(20, 30, 60, 60, 60)
is_work <- c(TRUE, FALSE, TRUE, TRUE, FALSE)
```

factor() and date()

```
levels <- c("connect", "exercise", "consult", "hobby", "essential")
classification <- factor(
  c("connect", "essential", "connect", "consult", "exercise"),
  levels = levels
)

dates <- rep("04-14-2020", length(activity))
date <- as.Date(dates, format = "%m-%d-%Y")
```

Missing values

```
x <- c(1, 3, NA, 5)
sum(x)
## [1] NA
sum(x, na.rm = TRUE)
## [1] 9

factor(c("connect", "disconnect"), levels = levels)
## [1] connect <NA>
## Levels: connect exercise consult hobby essential
```

Functions and logical operators

```
x <- c(1, 3, NA, 5)
sum(x)
## [1] NA
sum(x, na.rm = TRUE)
## [1] 9

minutes >= 60
## [1] FALSE FALSE TRUE TRUE TRUE
```

Subsetting vectors

- 1-based numeric indexes

```
activity
## [1] "check e-mail"      "breakfast"      "conference call" "webinar"
## [5] "walk"

idx <- c(1, 3, 1)
activity[idx]
## [1] "check e-mail"      "conference call" "check e-mail"
```

- logical index

```
is_work
## [1] TRUE FALSE TRUE TRUE FALSE
activity[is_work]
## [1] "check e-mail"      "conference call" "webinar"

sum(minutes[is_work])
## [1] 140
```

- Maybe more interesting...

```
short <- minutes < 60
short
## [1] TRUE TRUE FALSE FALSE FALSE
minutes[short]
## [1] 20 30
activity[short]
## [1] "check e-mail" "breakfast"
```

Other fun topics

`%in%`: a *binary operator*

- is each of the vector elements on the left-hand side *in* the set of elements on the right hand side

```
fruits <- c("banana", "apple", "grape", "orange", "kiwi")
c("apple", "orange", "hand sanitizer") %in% fruits
## [1] TRUE TRUE FALSE
```

named vectors (see Annual Estimates... table from census.gov)

- Define a named vector

```
state_populations <- c(
  Alabama = 4903185, Alaska = 731545, Arizona = 7278717, Arkansas = 3017804,
  California = 39512223, Colorado = 5758736, Connecticut = 3565287,
  Delaware = 973764, `District of Columbia` = 705749, Florida = 21477737,
  Georgia = 10617423, Hawaii = 1415872, Idaho = 1787065, Illinois = 12671821,
  Indiana = 6732219, Iowa = 3155070, Kansas = 2913314, Kentucky = 4467673,
  Louisiana = 4648794, Maine = 1344212, Maryland = 6045680, Massachusetts = 6892,
  Michigan = 9986857, Minnesota = 5639632, Mississippi = 2976149,
  Missouri = 6137428, Montana = 1068778, Nebraska = 1934408, Nevada = 3080156,
  `New Hampshire` = 1359711, `New Jersey` = 8882190, `New Mexico` = 2096829,
  `New York` = 19453561, `North Carolina` = 10488084, `North Dakota` = 762062,
  Ohio = 11689100, Oklahoma = 3956971, Oregon = 4217737, Pennsylvania = 12801989,
  `Rhode Island` = 1059361, `South Carolina` = 5148714, `South Dakota` = 884659,
  Tennessee = 6829174, Texas = 28995881, Utah = 3205958, Vermont = 623989,
  Virginia = 8535519, Washington = 7614893, `West Virginia` = 1792147,
  Wisconsin = 5822434, Wyoming = 578759
)
```

- Computations on named vectors

```
## US population
sum(state_populations)
## [1] 328239523

## smallest states
head(sort(state_populations))
##           Wyoming           Vermont District of Columbia
##           578759           623989           705749
##           Alaska           North Dakota           South Dakota
##           731545           762062           884659

## largest states
head(sort(state_populations, decreasing = TRUE))
## California Texas Florida New York Pennsylvania Illinois
## 39512223 28995881 21477737 19453561 12801989 12671821

## states with more than 10 million people
big <- state_populations[state_populations > 10000000]
big
## California Florida Georgia Illinois New York
## 39512223 21477737 10617423 12671821 19453561
## North Carolina Ohio Pennsylvania Texas
## 10488084 11689100 12801989 28995881
names(big)
```



```
## [1] "California"      "Florida"      "Georgia"      "Illinois"
## [5] "New York"        "North Carolina" "Ohio"         "Pennsylvania"
## [9] "Texas"
```

- Subset by name

```
## populations of California and New York
state_populations[c("California", "New York")]
## California    New York
##    39512223    19453561
```

1.5.2 Weekend activities (25 minutes; Shawn)

Writing *R* scripts

R scripts are convenient text files that we can use to save one or more lines of *R* syntax. Over the weekend you will get some experience working with *R* scripts. The example below will help you be a bit more prepared.

- In RStudio, click **File --> New File --> R Script** to create a new script file and open it in the editor.

If you've followed the daily coding activities throughout the week, you should have some *R* code that keeps track of your daily activities.

- If so, enter that code into your *R* script now.
- Otherwise, feel free to use the code below. Look for a **copy to clipboard** icon in the top-right of the code block. To copy the code block to your *R* script:
 - Click on the **copy to clipboard** icon
 - Place your cursor in your *R* script
 - Click **Edit --> Paste**:

```
## =====
## day 1 information
## =====
day1_activity = c("breakfast",
                  "check e-mail",
                  "projects",
                  "conference call",
                  "teams meeting",
```

```

        "lunch",
        "conference call",
        "webinar")
day1_is_work = c(FALSE,TRUE,TRUE,TRUE,TRUE,FALSE,TRUE,TRUE)
day1_minutes = c(30, 75, 120, 30, 60, 30, 60, 120)

n = length(day1_activity)
day1_total_hours = sum(day1_minutes) / 60
day1_work_hours = sum(day1_minutes[day1_is_work == TRUE]) / 60

cat("Total time recorded for day 1 : ", day1_total_hours,
    "hours, over", n, "activities\n")
cat("Total time working for day 1 : ", day1_work_hours, "hours \n\n")

```

Recall the discussion of factors and levels in Day 3; the code below leverages this but adds another level named `independent work`.

- If you've already got code to assign factors and levels to your daily activity, enter that code into your *R* script now.
- Otherwise, feel free to use the code below via the `copy to clipboard` procedure outlined above:

```

## =====
## Kelly, Morgan, and Matott's classification strategy
## =====
kmm_levels = c("connect",
               "exercise",
               "consult",
               "hobby",
               "essential",
               "independent work")
## manually map day 1 activity to appropriate kmm_levels
day1_classes = factor(
  c("essential", "connect", "independent work",
    "connect", "connect", "essential",
    "connect", "consult"),
  levels = kmm_levels
)

```

On day 3 you also got some experience working with dates. The code below stamps our day 1 activity data with an appropriately formatted date.

- If you've already got code to assign dates your daily activity, enter that code into your *R* script now.

- Otherwise, feel free to use the code below via the copy to clipboard procedure outlined above:

```
## =====
## Assign dates
## =====
day1_dates = rep("04-13-2020",length(day1_activity))
day1_dates = as.Date(day1_dates,format = "%m-%d-%Y")
```

[OPTIONAL ADVANCED MATERIAL]

Earlier today Dr. Morgan touched on named vectors. We can leverage named vectors to create a more general mapping between activities and levels. The code for this is given below. Try it and compare the result to your manual mapping!

```
## kmm_map is a named vector that maps activities to categories
kmm_map = c("breakfast"      = "essential",
            "check e-mail"   = "connect",
            "projects"       = "independent work",
            "requests"       = "independent work",
            "conference call" = "connect",
            "teams meeting"  = "connect",
            "lunch"          = "essential",
            "webinar"        = "consult",
            "walk"           = "exercise")
day1_classes = factor(kmm_map[day1_activity], levels = kmm_levels)
```

Saving *R* scripts

If you've been following along you should now have an *R* script that contains a bunch of code for keeping track of your daily activity log. Let's save this file:

- In RStudio, place your cursor anywhere in the script file
- click File --> Save (or press CTRL+S)
 - Name your file something like `daily_activity.R`.

Running *R* scripts

Now that we've created an *R* script you may be wondering "How do I run the code in the script?" There's actually a few ways to do this:

Option #1 (Run)

- Highlight the first block of the code (e.g the part where you recorded day 1 activity and maybe calculated amount of time worked).
- Click the --> **Run** icon in the top-right portion of the script editor window.
 - This will run the highlighted block of code. The output will appear in the RStudio console window along with an echo of the code itself.

Option #2 (Source)

- Click on the --> **Source** icon just to the right of the --> **Run** icon.
- This will run the entire script.
- Equivalent to entering into the console

```
source("daily_activity.R")
```

- Only the output generated by `print()` and `cat()` will appear in the RStudio console (i.e. the code in the script is not echoed to the console).

Option #3 (Source with Echo)

- Click on the downward pointing arrowhead next to the source button to open a dropdown menu
- In the dropdown menu, select **Source with Echo**
- This will run the entire script and the code in the script will be echoed to the RStudio console along with any output generated by `print()` and `cat()`.
- The echoed source and the normal output are not color-coded like they are when using the --> **Run** button.
- Equivalent to running

```
source("daily_activity.R", echo = TRUE, max = Inf)
```

Saving data

It can be useful to save objects created in an *R* script as a data file. These data files can be loaded or re-loaded into a new or existing *R* session.

For example, let's suppose you had an *R* script that mined a trove of Twitter feeds for sentiment data related to government responses to COVID-19. Suppose you ran the script for several weeks and collected lots of valuable data into a

bunch of vectors. Even though the *R* code is saved as a script file, the data that the script is collecting would be lost once script stops running. Furthermore, due to the temporal nature of Twitter feeds, you wouldn't be able to collect the same data by simply re-running the script. Luckily, *R* provides several routines for saving and loading objects. Placing the appropriate code in your *R* script will ensure that your data is preserved even after the script stops running.

Saving individual *R* objects

R supports storing a single *R* object as an *.rds* file. For example, the code below saves the `day1_activity` vector to an *.rds* file. The `saveRDS()` function is the workhorse in this case and the `setwd()`, `getwd()`, and `file.path()` commands allow us to conveniently specify a name and location for the data file:

```
## =====
## creating .rds data files (for saving individual objects)
## =====
setwd("C:/Matott/MyQuarantine")
my_rds_file = file.path(getwd(), "day1_activity.rds")
my_rds_file # print value -- sanity check
saveRDS(day1_activity, my_rds_file)
```

Loading individual *R* objects

The complement to the `saveRDS()` function is the `readRDS()` function. It loads the *R* object stored in the specified file. In the example below a data file is loaded and stored as an object named `day1_activity_loaded`. Compare this object to the existing `day1_activity` object - they should be the same!

```
## =====
## Reading .rds data files (for loading individual objects)
## =====
setwd("C:/Matott/MyQuarantine")
my_rds_file = file.path(getwd(), "day1_activity.rds")
my_rds_file
day1_activity_loaded = readRDS(my_rds_file) # now load from disk
```

Saving multiple *R* objects

The `save()` function will save one or more objects into a *.Rdata* file (these are also known as *session* files). The example below saves various `day1` and related factor-level objects to an *.Rdata* file.

```
## =====
## creating .RData files (for saving multiple objects)
## =====
setwd("C:/Matott/MyQuarantine")
my_rdata_file = file.path(getwd(), "day1.rdata")
save(kmm_levels, kmm_map,
     day1_activity, day1_classes, day1_dates, day1_is_work,
     day1_minutes, day1_total_hours, day1_work_hours,
     file = my_rdata_file)
```

If you have many objects that you want to save, listing them all can be tedious. Fortunately, the `ls()` command provides a list of all objects in the current *R* session. The results of `ls()` can be passed along to the `save()` command and this will result in all objects being saved. An example of the required syntax is given below.

```
setwd("C:/Matott/MyQuarantine")
my_rdata_file = file.path(getwd(), "day1.rdata")
save(list = ls(), file = my_rdata_file)
```

Loading multiple *R* objects

The complement to the `save()` function is the `load()` function. This will load all objects stored in an *.Rdata* file into the current *R* session. Example syntax is given below:

```
## =====
## Reading .RData files (for loading multiple objects)
## =====
setwd("C:/Matott/MyQuarantine")
my_rdata_file = file.path(getwd(), "daily_activity.rdata")
load(my_rdata_file) # reload
```

It is also possible to load an *.Rdata* file using the RStudio interface.

- Click Session --> Load Workspace ...
- A file browser dialog will open
- Navigate to the *.rdata* file and select

Wrapping up day 5

Today we reviewed the concepts that you worked with throughout the week during your independent activity. We also troubleshooted any problems or

- Alternatively, use “Run → Run All” to run an entire script file.

For today’s exercise, create a script file that summarizes your quarantine activities over several days. Use comments, white space (blank lines and spaces), and variable names to summarize each day. Here’s what I’ve got...

```
## 'classification' factor levels
levels <- c("connect", "exercise", "consult", "hobby", "essential")

## Quarantine log, day 1

activity_day_1 <-
  c("check e-mail", "breakfast", "conference call", "webinar", "walk")
minutes_day_1 <- c(20, 30, 60, 60, 60)
is_work_day_1 <- c(TRUE, FALSE, TRUE, TRUE, FALSE)
classification_day_1 <- factor(
  c("connect", "essential", "connect", "consult", "exercise"),
  levels = levels
)
date_day_1 <- as.Date(rep("04-14-2020", length(activity_day_1)), "%m-%d-%Y")

## Quarantine log, day 2

activity_day_2 <-
  c("check e-mail", "breakfast", "conference call", "webinar", "read a book")
minutes_day_2 <- c(20, 30, 60, 60, 60)
is_work_day_2 <- c(TRUE, FALSE, TRUE, TRUE, FALSE)
classification_day_2 <- factor(
  c("connect", "essential", "connect", "consult", "hobby"),
  levels = levels
)
date_day_2 <- as.Date(rep("04-15-2020", length(activity_day_2)), "%m-%d-%Y")

## Quarantine log, day 3

activity_day_3 <-
  c("check e-mail", "breakfast", "webinar", "read a book")
minutes_day_3 <- c(20, 30, 60, 60)
is_work_day_3 <- c(TRUE, FALSE, TRUE, FALSE)
classification_day_3 <- factor(
  c("connect", "essential", "connect", "consult", "hobby"),
  levels = levels
)
date_day_3 <- as.Date(rep("04-16-2020", length(activity_day_3)), "%m-%d-%Y")
```

Try concatenating these values, e.g.,


```
activity <- c(activity_day_1, activity_day_2, activity_day_3)
activity
## [1] "check e-mail"      "breakfast"         "conference call"   "webinar"
## [5] "walk"              "check e-mail"      "breakfast"         "conference call"
## [9] "webinar"           "read a book"       "check e-mail"      "breakfast"
## [13] "webinar"           "read a book"
```

Save your script, quit *R* and *RStudio*, and restart *R*. Re-open and run the script to re-do your original work.

Think about how this makes your work *reproducible* from one day to the next, and how making your scientific work reproducible would be advantageous.

1.7 Day 7: Saving data

We've defined these variables

```
activity <- c("check e-mail", "breakfast", "conference call", "webinar", "walk")
minutes <- c(20, 30, 60, 60, 60)
is_work <- c(TRUE, FALSE, TRUE, TRUE, FALSE)

levels <- c("connect", "exercise", "consult", "hobby", "essential")
classification <- factor(
  c("connect", "essential", "connect", "consult", "exercise"),
  levels = levels
)

dates <- rep("04-14-2020", length(activity))
date <- as.Date(dates, format = "%m-%d-%Y")
```

Individual variables can be saved to a file.

- Define the *path* to the file. The file extension is, by convention, ‘.rds’. We'll use a temporary location

```
temporary_file_path <- tempfile(fileext = ".rds")
```

...but we could have chosen the destination interactively

```
interactive_file_path <- file.choose(new = TRUE)
```

...or provided path relative to the ‘current working directory’, or an absolute file path (use ‘/’ to specify paths on all operating systems, including Windows)

```
getcwd()
relative_file_path <- "my_activity.rds"
absolute_file_path_on_macOS <- "/Users/ma38727/my_activity.rda"
```

- use `saveRDS()` to save a single object to a file

```
saveRDS(activity, temporary_file_path)
```

- use `readRDS()` to read the object back in

```
activity_from_disk <- readRDS(temporary_file_path)
activity_from_disk
## [1] "check e-mail"      "breakfast"          "conference call" "webinar"
## [5] "walk"
```

Use `save()` and `load()` to save and load several objects.

- Use `.RData` as the file extension. Usually we would NOT save to a temporary location, because the temporary location would be deleted when we ended our *R* session.

```
temporary_file_path <- tempfile(fileext = ".RData")
save(activity, minutes, file = temporary_file_path)
```

- Remove the objects from the *R* session, and verify that they are absent

```
rm(activity, minutes)
try(activity) # fails -- object not present
## Error in try(activity) : object 'activity' not found
```

- Load the saved objects

```
load(temporary_file_path)
activity
## [1] "check e-mail"      "breakfast"          "conference call" "webinar"
## [5] "walk"
```

As an exercise...

- Chose a location to save your data, e.g., in the current working directory

```
getwd()    # Where the heck are we?
## [1] "C:/Matott/QuaRantine"
my_file_path <- "my_quaRantine.RData"
```

- Save the data

```
save(activity, minutes, is_work, classification, date, file = my_file_path)
```

- Now the moment of truth. Quit *R* without saving your workspace

```
quit(save = FALSE)
```

- Start a new session of *R*, and verify that your objects are not present

```
ls() # list objects available in the '.GlobalEnv' -- there should be none
## character(0)
try(activity) # nope, not there...
## Error in try(activity) : object 'activity' not found
```

- Create a path to the saved data file

```
my_file_path <- "my_quaRantine.RData"
```

- Load the data and verify that it is correct

```
load(my_file_path)
activity
## [1] "check e-mail"      "breakfast"          "conference call"    "webinar"
## [5] "walk"
minutes
## [1] 20 30 60 60 60
is_work
## [1] TRUE FALSE TRUE TRUE FALSE
date
## [1] "2020-04-14" "2020-04-14" "2020-04-14" "2020-04-14" "2020-04-14"
classification
## [1] connect essential connect consult exercise
## Levels: connect exercise consult hobby essential
```

See you in zoom on Monday!

Chapter 2

The data frame

2.1 Day 8 (Monday) Zoom check-in

Review and troubleshoot (15 minutes)

The data frame (40 minutes)

Concept

Recall from Day 1:

- Data frames are handy containers for experimental data.
- Like a spreadsheet, a data frame has rows and columns
- The columns of a data frame contain data fields.
 - Each field could refer to a different type of object (numeric, string, etc.)
 - `height`, `weight`, `age`, etc.
 - `activity`, `duration`, `is work?`, `level`, `date`, etc.
- The rows of a data frame contain tuples of data
 - Note: you must ensure units are consistent across tuples!
- Rows and columns can be assigned names.

Create a simple data frame

```
heights <- c(72, 65, 68)
weights <- c(190, 130, 150)
ages <- c(44, 35, 37)
df <- data.frame(heights, weights, ages)
df
```

	heights	weights	ages
## 1	72	190	44
## 2	65	130	35
## 3	68	150	37

Create a data frame with row and column names

```
named_df <- data.frame(heights, weights, ages)
colnames(named_df) <- c("hgt_inches", "wgt_lbs", "age_years")
rownames(named_df) <- c("John Doe", "Pat Jones", "Sara Grant")
named_df
```

	hgt_inches	wgt_lbs	age_years
## John Doe	72	190	44
## Pat Jones	65	130	35
## Sara Grant	68	150	37

2.1.0.1 Add a row/tuple

For now, use `rbind()`. Later you'll learn about the more intuitive `add_row()` functionality of the `tidyverse` package.

```
more_heights <- c(61, 68, 70)
more_weights <- c(101, 134, 175)
more_ages <- c(13, 16, 24)
df_more <- data.frame(more_heights, more_weights, more_ages)
colnames(df_more) <- c("hgt_inches", "wgt_lbs", "age_years")
rownames(df_more) <- c("Bob Kane", "Kari Patra", "Sam Groe")

named_df <- rbind(named_df, df_more)
named_df
```

	hgt_inches	wgt_lbs	age_years
## John Doe	72	190	44
## Pat Jones	65	130	35
## Sara Grant	68	150	37
## Bob Kane	61	101	13

```
## Kari Patra      68      134      16
## Sam Groe       70      175      24
```

2.1.0.2 Delete a row/tuple

Row deletion using row names is a little tricky

```
# suppose the study has some dropouts ....
dropouts = c("Bob Kane", "John Doe")

named_df <- named_df[! rownames(named_df) %in% dropouts, ]

named_df
##           hgt_inches wgt_lbs age_years
## Pat Jones         65     130        35
## Sara Grant        68     150        37
## Kari Patra        68     134        16
## Sam Groe         70     175        24
```

Row deletion using row indices is more straightforward. Just use negative sub-setting

```
# suppose the study has some dropouts ....
dropouts = c(2,3)

df # refresh my memory about df contents ....
## heights weights ages
## 1      72      190   44
## 2      65      130   35
## 3      68      150   37

df <- df[-dropouts, ]

df # items 2 and 3 are dropped!
## heights weights ages
## 1      72      190   44
```

2.1.0.3 Some useful data frame operations

Try these out on your simple data frames `df` and `named_df`:

- `str(df)` # structure (NOT string!)(sorry Python programmers ;)

- `dim(df)` # dimensions
- `View(df)` # open tabular view of data frame
- `head(df)` # first few rows
- `tail(df)` # last few rows
- `names(df)` # column names
- `colnames(df)` # column names
- `rownames(df)` # row names

Creation

- Data from the second day of quarantine

```
activity <- c("check e-mail", "breakfast", "conference call", "webinar", "walk")
minutes <- c(20, 30, 60, 60, 60)
is_work <- c(TRUE, FALSE, TRUE, TRUE, FALSE)

levels <- c("connect", "exercise", "consult", "hobby", "essential")
classification <- factor(
  c("connect", "essential", "connect", "consult", "exercise"),
  levels = levels
)

dates <- rep("04-14-2020", length(activity))
date <- as.Date(dates, format = "%m-%d-%Y")
```

- Represent as a `data.frame()`

```
activities <- data.frame(activity, minutes, is_work, classification, date)
activities
##           activity minutes is_work classification      date
## 1  check e-mail      20    TRUE      connect 2020-04-14
## 2   breakfast      30   FALSE    essential 2020-04-14
## 3 conference call      60    TRUE      connect 2020-04-14
## 4     webinar      60    TRUE      consult 2020-04-14
## 5         walk      60   FALSE     exercise 2020-04-14
```

- Interrogate for some basic properties, including `dim()`ensions (number of rows and columns)

```
class(activities)
## [1] "data.frame"
dim(activities)
## [1] 5 5
```

Column access

- `$`
- `[[`

Updating or adding columns

Subsetting with `[`

- Subsetting rows
- Subsetting columns
- Subsetting rows and columns

Subsetting based on column values

- example

```
row_idx <- activities$minutes >= 60
activities[row_idx,]
##           activity minutes is_work classification      date
## 3 conference call      60     TRUE      connect 2020-04-14
## 4         webinar      60     TRUE      consult 2020-04-14
## 5           walk      60    FALSE      exercise 2020-04-14

## same as, but more readable than, ...
activities[activities$minutes >= 60,]
##           activity minutes is_work classification      date
## 3 conference call      60     TRUE      connect 2020-04-14
## 4         webinar      60     TRUE      consult 2020-04-14
## 5           walk      60    FALSE      exercise 2020-04-14
```

Binding rows (and columns)

- Activities, day 1

```
## 'classification' factor levels
levels <- c("connect", "exercise", "consult", "hobby", "essential")

## Quarantine log, day 1

activity_day_1 <-
  c("check e-mail", "breakfast", "conference call", "webinar", "walk")
minutes_day_1 <- c(20, 30, 60, 60, 60)
is_work_day_1 <- c(TRUE, FALSE, TRUE, TRUE, FALSE)
classification_day_1 <- factor(
  c("connect", "essential", "connect", "consult", "exercise"),
```

```

    levels = levels
  )
  date_day_1 <- as.Date(rep("04-14-2020", length(activity_day_1)), "%m-%d-%Y")

  day1 <- data.frame(
    activity = activity_day_1,
    minutes = minutes_day_1,
    is_work = is_work_day_1,
    classification = classification_day_1,
    date = date_day_1
  )

```

- Activities, day 2

```

activity_day_2 <-
  c("check e-mail", "breakfast", "conference call", "webinar", "read a book")
minutes_day_2 <- c(20, 30, 60, 60, 60)
is_work_day_2 <- c(TRUE, FALSE, TRUE, TRUE, FALSE)
classification_day_2 <- factor(
  c("connect", "essential", "connect", "consult", "hobby"),
  levels = levels
)
date_day_2 <- as.Date(rep("04-15-2020", length(activity_day_2)), "%m-%d-%Y")

day2 <- data.frame(
  activity = activity_day_2,
  minutes = minutes_day_2,
  is_work = is_work_day_2,
  classification = classification_day_2,
  date = date_day_2
)

```

- Activities, both days

```

quarantine_log <- rbind(day1, day2)
quarantine_log
##           activity minutes is_work classification      date
## 1    check e-mail     20    TRUE      connect 2020-04-14
## 2    breakfast      30   FALSE    essential 2020-04-14
## 3 conference call     60    TRUE      connect 2020-04-14
## 4      webinar      60    TRUE      consult 2020-04-14
## 5         walk      60   FALSE    exercise 2020-04-14
## 6    check e-mail     20    TRUE      connect 2020-04-15
## 7    breakfast      30   FALSE    essential 2020-04-15
## 8 conference call     60    TRUE      connect 2020-04-15

```

```
## 9      webinar      60    TRUE      consult 2020-04-15
## 10     read a book   60   FALSE      hobby 2020-04-15
```

Writing and reading

- Exmaple: round-trip

```
file <- tempfile() # temporary file
## file <- file.choose()
## file <- "activities.csv"
## file <- "/Users/ma38737/MyQuarantine/activities.csv"
write.csv(quarantine_log, file, row.names = FALSE)
read.csv(file)
##      activity minutes is_work classification      date
## 1    check e-mail     20    TRUE      connect 2020-04-14
## 2    breakfast       30   FALSE    essential 2020-04-14
## 3 conference call     60    TRUE      connect 2020-04-14
## 4      webinar       60    TRUE      consult 2020-04-14
## 5        walk        60   FALSE    exercise 2020-04-14
## 6    check e-mail     20    TRUE      connect 2020-04-15
## 7    breakfast       30   FALSE    essential 2020-04-15
## 8 conference call     60    TRUE      connect 2020-04-15
## 9      webinar       60    TRUE      consult 2020-04-15
## 10   read a book      60   FALSE      hobby 2020-04-15
```

R and spreadsheets

An alternative way of working with `data.frame()`

- `with()`: column selection and computation
- `within()`: update or add columns
- `subset()`: row and column subset

Summarization

- Use `with()` to simplify variable reference
- Create a new `data.frame()` containing the summary

```
with(quarantine_log, {
  data.frame(
    days_in_quarantine = length(unique(date)),
    total_minutes = sum(minutes),
```

```

        work_activities = sum(is_work),
        other_activities = sum(!is_work)
    )
})
##   days_in_quarantine total_minutes work_activities other_activities
## 1                   2             460                6              4

```

Summarization by group

- `aggregate()`

```

## minutes per day spent on each activity, from the quarantine_log
aggregate(minutes ~ activity, quarantine_log, sum)
##           activity minutes
## 1      breakfast      60
## 2    check e-mail      40
## 3 conference call     120
## 4           walk      60
## 5         webinar     120
## 6    read a book      60

## minutes per day spent on each clasasification
aggregate(minutes ~ classification, quarantine_log, sum)
##   classification minutes
## 1      connect      160
## 2     exercise      60
## 3      consult     120
## 4        hobby      60
## 5    essential      60

## non-work activities per day
aggregate(!is_work ~ date, quarantine_log, sum)
##           date !is_work
## 1 2020-04-14         2
## 2 2020-04-15         2

```

2.1.1 This week's activities (5 minutes)

Goal: retrieve and summarize COVID 19 cases in Erie county and nationally

2.2 Day 9: Creation and manipulation

Creation

Last week we created vectors summarizing our quarantine activities

```
activity <- c("check e-mail", "breakfast", "conference call", "webinar", "walk")
minutes <- c(20, 30, 60, 60, 60)
is_work <- c(TRUE, FALSE, TRUE, TRUE, FALSE)

levels <- c("connect", "exercise", "consult", "hobby", "essential")
classification <- factor(
  c("connect", "essential", "connect", "consult", "exercise"),
  levels = levels
)

dates <- rep("04-14-2020", length(activity))
date <- as.Date(dates, format = "%m-%d-%Y")
```

Each of these vectors is the same length, and are related to one another in a specific way – the first element of `activity`, ‘check e-mail’, is related to the first element of `minutes`, ‘20’, and to `is_work`, etc.

Use `data.frame()` to construct an object containing each of these vectors

- Each argument to `data.frame()` is a vector representing a column
- The `stringsAsFactors = FALSE` argument says that character vectors should NOT be automatically coerced to factors

```
activities <- data.frame(
  activity, minutes, is_work, classification, date,
  stringsAsFactors = FALSE
)
activities
```

##	activity	minutes	is_work	classification	date
## 1	check e-mail	20	TRUE	connect	2020-04-14
## 2	breakfast	30	FALSE	essential	2020-04-14
## 3	conference call	60	TRUE	connect	2020-04-14
## 4	webinar	60	TRUE	consult	2020-04-14
## 5	walk	60	FALSE	exercise	2020-04-14

- We can query the object we’ve created for its `class()`, `dim()`ensions, take a look at the `head()` or `tail()` of the object, etc. `names()` returns the column names.

```

class(activities)
## [1] "data.frame"
dim(activities) # number of rows and columns
## [1] 5 5
head(activities, 3) # first three rows
##           activity minutes is_work classification      date
## 1    check e-mail      20    TRUE      connect 2020-04-14
## 2      breakfast      30   FALSE    essential 2020-04-14
## 3 conference call      60    TRUE      connect 2020-04-14
names(activities)
## [1] "activity"      "minutes"        "is_work"        "classification"
## [5] "date"

```

Column selection

Use `[` to select rows and columns

- `activities` is a two-dimensional object
- Subset the data to contain the first and third rows and the first and fourth columns

```

activities[c(1, 3), c(1, 4)]
##           activity classification
## 1    check e-mail      connect
## 3 conference call      connect

```

- Subset columns by name

```

activities[c(1, 3), c("activity", "is_work")]
##           activity is_work
## 1    check e-mail    TRUE
## 3 conference call    TRUE

```

- Subset only by row or only by column by omitting the subscript index for that dimension

```

activities[c(1, 3), ] # all columns for rows 1 and 3
##           activity minutes is_work classification      date
## 1    check e-mail      20    TRUE      connect 2020-04-14
## 3 conference call      60    TRUE      connect 2020-04-14
activities[, c("activity", "minutes")] # all rows for columns 1 and 2
##           activity minutes

```

```
## 1    check e-mail    20
## 2      breakfast    30
## 3 conference call    60
## 4        webinar    60
## 5          walk     60
```

- Be careful when selecting a single column!

- By default, *R* returns a *vector*

```
activities[, "classification"]
## [1] connect    essential connect    consult    exercise
## Levels: connect exercise consult hobby essential
```

- Use `drop = FALSE` to return a `data.frame`

```
activities[, "classification", drop = FALSE]
##   classification
## 1      connect
## 2    essential
## 3      connect
## 4      consult
## 5      exercise
```

Use `$` or `[[` to select a column

- Selection of individual columns as vectors is easy

```
activities$classification
## [1] connect    essential connect    consult    exercise
## Levels: connect exercise consult hobby essential
```

- An alternative, often used in scripts, is to use `[[`, which requires the name of a variable provided as a character vector

```
activities[["classification"]]
## [1] connect    essential connect    consult    exercise
## Levels: connect exercise consult hobby essential

colname <- "classification"
activities[[colname]]
## [1] connect    essential connect    consult    exercise
## Levels: connect exercise consult hobby essential
```

Column selection and subsetting are often combined, e.g., to create a `data.frame` of work-related activities, or work-related activities lasting 60 minutes or longer

```
work_related_activities <- activities[ activities$is_work == TRUE, ]
work_related_activities
##           activity minutes is_work classification      date
## 1    check e-mail     20    TRUE      connect 2020-04-14
## 3 conference call     60    TRUE      connect 2020-04-14
## 4      webinar       60    TRUE      consult 2020-04-14

row_idx <- activities$is_work & (activities$minutes >= 60)
activities[row_idx,]
##           activity minutes is_work classification      date
## 3 conference call     60    TRUE      connect 2020-04-14
## 4      webinar       60    TRUE      consult 2020-04-14
```

Adding or updating columns

Use `$` or `[` or `[[` to add a new column,

```
activities$is_long_work <- activities$is_work & (activities$minutes >= 60)
activities
##           activity minutes is_work classification      date is_long_work
## 1    check e-mail     20    TRUE      connect 2020-04-14      FALSE
## 2      breakfast     30   FALSE    essential 2020-04-14      FALSE
## 3 conference call     60    TRUE      connect 2020-04-14       TRUE
## 4      webinar       60    TRUE      consult 2020-04-14       TRUE
## 5          walk       60   FALSE    exercise 2020-04-14      FALSE

## ...another way of doing the same thing
activities[["is_long_work"]] <- activities$is_work & (activities$minutes >= 60)

## ...and another way
activities[, "is_long_work"] <- activities$is_work & (activities$minutes >= 60)
```

Columns can be updated in the same way

```
activities$activity <- toupper(activities$activity)
activities
##           activity minutes is_work classification      date is_long_work
## 1    CHECK E-MAIL     20    TRUE      connect 2020-04-14      FALSE
## 2      BREAKFAST     30   FALSE    essential 2020-04-14      FALSE
## 3 CONFERENCE CALL     60    TRUE      connect 2020-04-14       TRUE
```


## 4	WEBINAR	60	TRUE	consult 2020-04-14	TRUE
## 5	WALK	60	FALSE	exercise 2020-04-14	FALSE

Reading and writing

Create a file path to store a 'csv' file. From day 7, the path could be temporary, chosen interactively, a relative path, or an absolute path

```
## could be any of these...
##
## interactive_file_path <- file.choose(new = TRUE)
## getcwd()
## relative_file_path <- "my_activity.rds"
## absolute_file_path_on_macOS <- "/Users/ma38727/my_activity.rda"
##
## ... but we'll use
temporary_file_path <- tempfile(fileext = ".csv")
```

Use `write.csv()` to save the `data.frame` to disk as a plain text file in 'csv' (comma-separated value) format. The `row.names = FALSE` argument means that the row indexes are not saved to the file (row names are created when data is read in using `read.csv()`).

```
write.csv(activities, temporary_file_path, row.names = FALSE)
```

If you wish, use RStudio File -> Open File to navigate to the location where you saved the file, and open it. You could also open the file in Excel or other spreadsheet. Conversely, you can take an Excel sheet and export it as a csv file for reading into *R*.

Use `read.csv()` to import a plain text file formatted as csv

```
imported_activities <- read.csv(temporary_file_path, stringsAsFactors = FALSE)
imported_activities
##      activity minutes is_work classification      date is_long_work
## 1  CHECK E-MAIL    20    TRUE      connect 2020-04-14      FALSE
## 2  BREAKFAST      30   FALSE    essential 2020-04-14      FALSE
## 3 CONFERENCE CALL    60    TRUE      connect 2020-04-14      TRUE
## 4  WEBINAR        60    TRUE      consult 2020-04-14      TRUE
## 5  WALK           60   FALSE    exercise 2020-04-14      FALSE
```

Note that some information has not survived the round-trip – the `classification` and `date` columns are plain character vectors.

```
class(imported_activities$classification)
## [1] "character"
class(imported_activities$date)
## [1] "character"
```

Update these to be a `factor()` with specific levels, and a `Date`.

```
levels <- c("connect", "exercise", "consult", "hobby", "essential")
imported_activities$classification <- factor(
  imported_activities$classification,
  levels = levels
)

imported_activities$date <- as.Date(imported_activities$date, format = "%Y-%m-%d")

imported_activities
##      activity minutes is_work classification      date is_long_work
## 1  CHECK E-MAIL     20    TRUE      connect 2020-04-14      FALSE
## 2   BREAKFAST     30   FALSE    essential 2020-04-14      FALSE
## 3 CONFERENCE CALL     60    TRUE      connect 2020-04-14       TRUE
## 4     WEBINAR     60    TRUE      consult 2020-04-14       TRUE
## 5        WALK     60   FALSE    exercise 2020-04-14      FALSE
```

Reading from a remote file (!)

- Visit the New York Times csv file daily tally of COVID-19 cases in all US counties.
- Read the data into an *R* `data.frame`

```
url <-
  "https://raw.githubusercontent.com/nytimes/covid-19-data/master/us-counties.csv"
us <- read.csv(url, stringsAsFactors = FALSE)
```

- Explore the data

```
class(us)
## [1] "data.frame"
dim(us)
## [1] 64707      6
head(us)
##      date      county      state fips cases deaths
## 1 2020-01-21 Snohomish Washington 53061      1      0
## 2 2020-01-22 Snohomish Washington 53061      1      0
```

```
## 3 2020-01-23 Snohomish Washington 53061 1 0
## 4 2020-01-24 Cook Illinois 17031 1 0
## 5 2020-01-24 Snohomish Washington 53061 1 0
## 6 2020-01-25 Orange California 6059 1 0
```

- Subset the data to only New York state or Erie county

```
ny_state <- us[us$state == "New York",]
dim(ny_state)
## [1] 1780 6

erie <- us[(us$state == "New York") & (us$county == "Erie"), ]
erie
##           date county      state fips cases deaths
## 2569 2020-03-15 Erie New York 36029 3 0
## 3028 2020-03-16 Erie New York 36029 6 0
## 3544 2020-03-17 Erie New York 36029 7 0
## 4141 2020-03-18 Erie New York 36029 7 0
## 4870 2020-03-19 Erie New York 36029 28 0
## 5717 2020-03-20 Erie New York 36029 31 0
## 6711 2020-03-21 Erie New York 36029 38 0
## 7805 2020-03-22 Erie New York 36029 54 0
## 9003 2020-03-23 Erie New York 36029 87 0
## 10314 2020-03-24 Erie New York 36029 107 0
## 11754 2020-03-25 Erie New York 36029 122 0
## 13367 2020-03-26 Erie New York 36029 134 2
## 15111 2020-03-27 Erie New York 36029 219 6
## 16951 2020-03-28 Erie New York 36029 354 6
## 18888 2020-03-29 Erie New York 36029 380 6
## 20938 2020-03-30 Erie New York 36029 443 8
## 23079 2020-03-31 Erie New York 36029 438 8
## 25283 2020-04-01 Erie New York 36029 553 12
## 27544 2020-04-02 Erie New York 36029 734 19
## 29866 2020-04-03 Erie New York 36029 802 22
## 32254 2020-04-04 Erie New York 36029 945 26
## 34687 2020-04-05 Erie New York 36029 1059 27
## 37160 2020-04-06 Erie New York 36029 1163 30
## 39674 2020-04-07 Erie New York 36029 1163 36
## 42227 2020-04-08 Erie New York 36029 1205 38
## 44803 2020-04-09 Erie New York 36029 1362 46
## 47417 2020-04-10 Erie New York 36029 1409 58
## 50071 2020-04-11 Erie New York 36029 1472 62
## 52744 2020-04-12 Erie New York 36029 1571 75
## 55428 2020-04-13 Erie New York 36029 1624 86
## 58128 2020-04-14 Erie New York 36029 1668 99
```

```
## 60844 2020-04-15 Erie New York 36029 1751 110
## 63572 2020-04-16 Erie New York 36029 1850 115
```

2.3 Day 10: subset(), with(), and within()

subset()

subset()ing a data.frame

- Read the New York Times csv file summarizing COVID cases in the US.

```
url <-
  "https://raw.githubusercontent.com/nytimes/covid-19-data/master/us-counties.csv"
us <- read.csv(url, stringsAsFactors = FALSE)
```

- Create subsets, e.g., to include only New York state, or only Erie county

```
ny_state <- subset(us, state == "New York")
dim(ny_state)
## [1] 1780 6
tail(ny_state)
##           date      county      state fips cases deaths
## 63611 2020-04-16 Warren New York 36113 81 5
## 63612 2020-04-16 Washington New York 36115 46 0
## 63613 2020-04-16 Wayne New York 36117 49 0
## 63614 2020-04-16 Westchester New York 36119 21828 738
## 63615 2020-04-16 Wyoming New York 36121 34 3
## 63616 2020-04-16 Yates New York 36123 7 0

erie <- subset(us, (state == "New York") & county == "Erie")
dim(erie)
## [1] 33 6
tail(erie)
##           date county      state fips cases deaths
## 50071 2020-04-11 Erie New York 36029 1472 62
## 52744 2020-04-12 Erie New York 36029 1571 75
## 55428 2020-04-13 Erie New York 36029 1624 86
## 58128 2020-04-14 Erie New York 36029 1668 99
## 60844 2020-04-15 Erie New York 36029 1751 110
## 63572 2020-04-16 Erie New York 36029 1850 115
```

with()

Use `with()` to simplify column references

- Goal: calculate maximum number of cases in the Erie county data subset
- First argument: a `data.frame` containing data to be manipulated – `erie`
- Second argument: an *expression* to be evaluated, usually referencing columns in the data set – `max(cases)`

– E.g., Calculate the maximum number of cases in the `erie` subset

```
with(erie, max(cases))
## [1] 1850
```

Second argument can be more complicated, using `{}` to enclose several lines.

- E.g., Calculate the number of new cases, and then reports the average number of new cases per day. We will use `diff()`

– `diff()` calculates the difference between successive values of a vector

```
x <- c(1, 1, 2, 3, 5, 8)
diff(x)
## [1] 0 1 1 2 3
```

– The length of `diff(x)` is one less than the length of `x`

```
length(x)
## [1] 6
length(diff(x))
## [1] 5
```

- `new_cases` is the `diff()` of successive values of `cases`, with an implicit initial value equal to 0.

```
with(erie, {
  new_cases <- diff(c(0, cases))
  mean(new_cases)
})
## [1] 56.06061
```

within()

Adding and updating columns `within()` a `data.frame`

- First argument: a `data.frame` containing data to be updated – `erie`
- Second argument: an expression of one or more variable assignments, the assignments create new columns in the `data.frame`.
- Example: add a `new_cases` column

```
erie_new_cases <- within(erie, {
  new_cases <- diff(c(0, cases))
})
head(erie_new_cases)
##           date county    state fips cases deaths new_cases
## 2569 2020-03-15  Erie New York 36029     3      0         3
## 3028 2020-03-16  Erie New York 36029     6      0         3
## 3544 2020-03-17  Erie New York 36029     7      0         1
## 4141 2020-03-18  Erie New York 36029     7      0         0
## 4870 2020-03-19  Erie New York 36029    28      0        21
## 5717 2020-03-20  Erie New York 36029    31      0         3
```

2.4 Day 11: aggregate() and an initial work flow**aggregate() for summarizing columns by group**

Goal: summarize maximum number of cases by county in New York state

Setup

- Read and subset the New York Times data to contain only New York state data

```
url <- "https://raw.githubusercontent.com/nytimes/covid-19-data/master/us-counties"
us <- read.csv(url, stringsAsFactors = FALSE)
```

```
ny_state <- subset(us, state == "New York")
```

aggregate()

- First argument: a *formula* – `cases ~ county`

- Right-hand side: the variable to be used to subset (group) the data – `county`
- Left-hand side: the variable to be used in the aggregation function – `cases`
- Second argument: source of data – `ny_state`
- Third argument: the function to be applied to each subset of data – `max`
- Maximum number of cases by county:

```
max_cases_by_county <- aggregate( cases ~ county, ny_state, max )
```

Exploring the data summary

- Subset to some interesting ‘counties’

```
head(max_cases_by_county)
##      county cases
## 1    Albany  581
## 2 Allegany   28
## 3   Broome  167
## 4 Cattaraugus 32
## 5   Cayuga   36
## 6 Chautauqua 24
subset(
  max_cases_by_county,
  county %in% c("New York City", "Westchester", "Erie")
)
##      county cases
## 14      Erie  1850
## 29 New York City 123146
## 57 Westchester 21828
```

Help: `?aggregate.formula`

An initial work flow

Data input

```
url <- "https://raw.githubusercontent.com/nytimes/covid-19-data/master/us-counties.csv"
us <- read.csv(url, stringsAsFactors = FALSE)
```

```

class(us)
## [1] "data.frame"
dim(us)
## [1] 64707    6
head(us)
##           date      county      state  fips cases deaths
## 1 2020-01-21 Snohomish Washington 53061     1      0
## 2 2020-01-22 Snohomish Washington 53061     1      0
## 3 2020-01-23 Snohomish Washington 53061     1      0
## 4 2020-01-24      Cook   Illinois 17031     1      0
## 5 2020-01-24 Snohomish Washington 53061     1      0
## 6 2020-01-25   Orange California 6059     1      0

```

Cleaning

- `date` is a plain-old character vector, but should be a `Date`.

```

class(us$date) # oops, should be 'Date'
## [1] "character"

```

- Update, method 1

```

us$date <- as.Date(us$date, format = "%Y-%m-%d")
head(us)
##           date      county      state  fips cases deaths
## 1 2020-01-21 Snohomish Washington 53061     1      0
## 2 2020-01-22 Snohomish Washington 53061     1      0
## 3 2020-01-23 Snohomish Washington 53061     1      0
## 4 2020-01-24      Cook   Illinois 17031     1      0
## 5 2020-01-24 Snohomish Washington 53061     1      0
## 6 2020-01-25   Orange California 6059     1      0

```

- Update, method 2

```

us <- within(us, {
  date = as.Date(date, format = "%Y-%m-%d")
})
head(us)
##           date      county      state  fips cases deaths
## 1 2020-01-21 Snohomish Washington 53061     1      0
## 2 2020-01-22 Snohomish Washington 53061     1      0
## 3 2020-01-23 Snohomish Washington 53061     1      0
## 4 2020-01-24      Cook   Illinois 17031     1      0
## 5 2020-01-24 Snohomish Washington 53061     1      0
## 6 2020-01-25   Orange California 6059     1      0

```


Interested only in Erie county, New York state

- Subset, method 1

```
row_idx <- (us$county == "Erie") & (us$state == "New York")
erie <- us[row_idx,]
dim(erie)
## [1] 33 6
```

- Subset, method 2

```
erie <- subset(us, (county == "Erie") & (state == "New York"))
dim(erie)
## [1] 33 6
```

Manipulation

- Goal: calculate `new_cases` as the difference between successive days, using `diff()`
- Remember use of `diff()`

```
## example: `diff()` between successive numbers in a vector
x <- c(1, 1, 2, 3, 5, 8, 13)
diff(x)
## [1] 0 1 1 2 3 5

## note 'diff()' what about an implicit '0' at the start of a sequence?
diff( c(0, x) )
## [1] 1 0 1 1 2 3 5
```

- Update, methods 1 & 2


```
## one way...
erie$new_cases <- diff( c(0, erie$cases) )

## ...or another
erie <- within(erie, {
  new_cases <- diff( c(0, cases) )
})
```

Simple visualization


- Use a formula to describe the dependent (y-axis) variable as a function of the independent (x-axis) variable – `cases ~ date`

```
plot( cases ~ date, erie)
```



maybe more informative: log-transformed new cases

```
plot( new_cases ~ date, erie, log = "y", main = "New Cases, Erie County" )  
## Warning in xy.coords(x, y, xlabel, ylabel, log): 3 y values <= 0 omitted from  
## logarithmic plot
```



- Help: `?plot.formula`

Summary: calculate maximum (total) number of cases per county in New York state

- For Erie county, let's see how to calculate the maximum (total) number of cases

```
max(erie$cases)          # one way...
## [1] 1850
with(erie, max(cases)) # ... another
## [1] 1850
```

- Subset US data to New York state

```
ny_state <- subset(us, state == "New York")
```

- Summarize each county in the state using `aggregate()`.
 - First argument: summarize `cases` grouped by `county` – `cases ~ county`
 - Second argument: data source – `ny_state`
 - Third argument: function to apply to each subset – `max`

```
max_cases_by_county <- aggregate( cases ~ county, ny_state, max)
head(max_cases_by_county)
##           county cases
## 1      Albany    581
## 2   Allegany     28
## 3    Broome    167
## 4 Cattaraugus    32
## 5     Cayuga     36
## 6 Chautauqua     24
```

- `subset()` to select counties

```
subset(
  max_cases_by_county,
  county %in% c("New York City", "Westchester", "Erie")
)
##           county cases
## 14          Erie    1850
## 29 New York City 123146
## 57 Westchester  21828
```

Summary: calculate maximum (total) number of cases per state

- Use entire data set, `us`
- `aggregate()` cases by county *and* state – `cases ~ county + state`

```
max_cases_by_county_state <-
  aggregate( cases ~ county + state, us, max )
dim(max_cases_by_county_state)
## [1] 2767    3
head(max_cases_by_county_state)
##      county  state cases
## 1 Autauga Alabama    25
## 2 Baldwin Alabama   102
## 3 Barbour Alabama    14
## 4  Bibb Alabama     24
## 5 Blount Alabama    18
## 6 Bullock Alabama     8
```

- `aggregate()` a second time, using `max_cases_by_county_state` and aggregating by state

```
max_cases_by_state <-
  aggregate( cases ~ state, max_cases_by_county_state, max )
```

- Explore the data

```
head(max_cases_by_state)
##      state cases
## 1  Alabama   634
## 2  Alaska   143
## 3  Arizona  2264
## 4  Arkansas  355
## 5 California 10854
## 6  Colorado  1549
subset(
  max_cases_by_state,
  state %in% c("California", "Illinois", "New York", "Washington")
)
##      state cases
## 5 California 10854
## 15 Illinois  18087
## 34 New York 123146
## 52 Washington  4811
```

2.5 Day 12 (Friday) Zoom check-in

2.6 Day 13:

2.7 Day 14

Self-directed activities.

Chapter 3

Packages and the ‘tidyverse’

3.1 Day 15 (Monday) Zoom check-in

3.2 CRAN

3.3 The ‘tidyverse’ of packages

3.4 Day 16

3.5 Day 17

3.6 Day 18

3.7 Day 19 (Friday) Zoom check-in

3.7.1 Review and trouble shoot (25 minutes)

3.7.2 Next week (25 minutes)

3.8 Day 20

3.9 Day 21

Self-directed activities.

Chapter 4

Maps and spatial statistics

4.1 Day 22 (Monday) Zoom check-in

4.2 Day 23

4.3 Day 24

4.4 Day 25

4.5 Day 26 (Friday) Zoom check-in

4.5.1 Review and trouble shoot (25 minutes)

4.5.2 Next week (25 minutes)

4.6 Day 27

4.7 Day 28

Self-directed activities.

Chapter 5

Bioinformatics with Bioconductor

5.1 Day 29 (Monday) Zoom check-in

5.2 Day 30

5.3 Day 31

5.4 Day 32

5.5 Day 33 (Friday) Zoom check-in

5.5.1 Review and trouble shoot (25 minutes)

5.5.2 Next week (25 minutes)

5.6 Day 34

5.7 Day 35

Self-directed activities.

Chapter 6

Collaboration

6.1 5 Days (Monday) Zoom check-in

6.2 4 Days

6.3 3 Days

6.4 2 Days

6.5 Today! (Friday) Zoom check-in


Course review and next steps

Frequently asked questions


1. Is the course material available in PDF?

Yes, click the ‘Download’ icon and PDF format in the title bar of the main document, as illustrated in the figure.

Remember that the course material is a ‘work in progress’, so the PDF will need to be updated frequently throughout the course. Also, the book is not pretty; that’s a task for a separate quarantine!



2. Whenever I press the ‘enter’ key, the RStudio console keeps saying + and doesn’t evaluate my expression! See the figure below.



Notice that you’ve started a character string with a double ", and tried to terminate it with a single quote '. Because the quotes do not match, *R* thinks you’re still trying to complete the entry of the variable, and

it's letting you know that it is expecting more with the `+` prompt at the beginning of the line.

A common variant of this is to open more parentheses than you close, as shown in

A screenshot of an R console window. The window has a title bar with tabs for 'Console', 'Terminal', 'R Markdown', and 'Jobs'. The 'Console' tab is active. The address bar shows the path '~ /a/github/QuaRantine/'. The console content shows the R prompt '>' followed by the command 'x <- c(c("foo", "bar")'. Below the command, there are three '+' signs on separate lines, indicating that the command is not yet complete and the console is waiting for more input.

```
> x <- c(c("foo", "bar")
+
+
+
```

The solution is either to complete your entry (by entering a `"` or balancing the parentheses with `)`) or abandon your attempt by pressing **control-C** or the escape key (usually in the top left corner of the keyboard)