Physical & electrical characteristics

Copper 6.35/11kV – Three core heavy duty screened armoured										
Product code: 3CCUX11HDA										
Nominal conductor area mm²		25	35	50	70	95	120	150	185	240
Nominal conductor diameter mm		6.1	7.0	8.2	9.8	11.5	12.9	14.3	16.1	18.2
Nominal insulation thickness mm		3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4
Approx cable diameter mm		51.3	53.7	56.3	60.4	64.4	67.9	71.3	76.7	82.1
Approx mass kg/100m		430	495	560	675	795	890	995	1220	1440
Max pulling tension on conductors kN		5.3	7.4	11	15	20	25	25	25	25
Max pulling tension on stocking grip kN		5.3	7.4	11	13	15	16	18	21	24
Max pulling tension on amour wires kN		11	12	13	15	17	19	21	24	25
Min bending radius* during installation mm		920	970	1010	1090	1160	1220	1280	1380	1480
Min bending radius* set in position mm		620	640	680	720	770	810	860	920	980
Max conductor resistance, dc @ 20°C Ohm/km		0.727	0.524	0.387	0.268	0.193	0.153	0.124	0.0991	0.0754
Conductor resistance, ac @ 90°C & 50 Hz Ohm/km		0.927	0.668	0.494	0.342	0.247	0.196	0.159	0.128	0.0984
Inductance mH/km		0.415	0.397	0.379	0.350	0.333	0.319	0.310	0.300	0.290
Inductive reactance, @ 50Hz Ohm/km		0.130	0.125	0.119	0.110	0.105	0.100	0.0973	0.0942	0.0910
Zero seq. impedance @ 20°C & 50 Hz Ohm/km		3.07+ j0.0836	2.16+ j0.0781	1.56+ j0.0726	1.11+ j0.0635	1.03+ j0.0585	0.995+ j0.0543	0.966+ j0.0515	0.941+ j0.0485	0.917+ j0.0454
Capacitance, phase to earth µF/km		0.212	0.231	0.255	0.290	0.325	0.354	0.383	0.419	0.465
Min insulation resistance @ 20°C MOhm.km		12,000	11,000	10,000	8,900	7,900	7,200	6,600	6,000	5,400
Electric stress at conductor screen kV/mm		2.64	2.56	2.49	2.40	2.33	2.29	2.25	2.22	2.18
Charging current @ rated voltage & 50 Hz A/phase/km		0.422	0.461	0.509	0.578	0.648	0.706	0.764	0.837	0.927
Short circuit rating	Phase conductor kA, 1 sec	3.6	5.0	7.2	10.0	13.6	17.2	21.5	26.5	34.3
	Metallic screen kA, 1 sec	3.5	5.1	7.1	10	10	10	10	10	10
Continuous current rating	In ground, direct buried A	135	165	195	245	290	330	370	410	475
	In ground, in singleway ducts A	120	145	170	205	245	280	310	350	410
	In free air, unenclosed & spaced from wall A	135	165	195	245	295	345	385	440	520

The cables described in this technical manual are designed to be used for the supply of electrical energy in fixed applications up to the rated voltages at a nominal power frequency between 49Hz and 61Hz. All values in this catalogue are for XLPE cables only. *Increased radius required for HDPE and nylon incorporating designs.