Objective

Analyze the provided pcap file to determine whether sensitive data (credentials or files) can be extracted from captured FTP traffic.

Access pcap file through this https://github.com/geo-hotzz/Pcap-Files-for-Practices/blob/main/ftp_full.pcap

Step 1: Open the PCAP File
The provided ftp_full.pcap file was opened in Wireshark for traffic inspection.

```bash
wireshark ftp_full.pcap
```

Step 2: Filter FTP Traffic

Applied the following display filter:

```
ftp || ftp-data
```

The FTP filter in Wireshark is used to:

- Isolate FTP traffic from all other network traffic
- View login credentials (USER / PASS)
- Identify file transfer commands (RETR, STOR, LIST)
- Analyze file uploads and downloads
- Investigate potential data leakage
  Instead of manually searching through thousands of packets, the filter shows only FTP-related packets.

Step 3: Extract Transferred File

1. Located `RETR` (download) command.
2. Followed the associated TCP stream:
   - Right-click → Follow → TCP Stream
3. Switched to **Raw** mode.
4. Saved the output to reconstruct the transferred file.
   Or else use the export object on wire shark.



But in this we could choose the FTP-DATA.So then we could able to see the files trasfered through transaction by Ftp.
After we can able to get the flag as a file .
After getting the text file,we could extract or find is there any credential data's,pass,uids is there

Verify File Integrity

- Check file size
- Open the file to confirm it is readable
- Ensure no corruption occurred during extraction
  If it’s a text file → open in a text editor
  If it’s binary → identify type first
  After extraction → Validate → Identify → Analyze → Hash → Report → Assess Impact
  #bash
  file filename
  This tells you whether it is:
- Text
- Image
- Executable
- Archive
- etc.
  To using cat command we can able to read the flag,
  #bash
  cat flag

The Flag is,
{Y0U_D1D_1T)