



EUROGRAPHICS 2016



THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

Structure aware mesh decimation

David Salinas, Florent Lagarde, Pierre Alliez (Inria)

Size of acquired data

The size of acquired data has grown exponentially over the last decades



Resolution increase



Size of object increase

Currently, recent automatic acquisition workflows (MVS, lidar) are able to capture dense meshes with billion of vertices

Around 6 millions vertices for 1 km² of a city with reasonable accuracy

With same density, around 10^{15} points to represent the whole land world area

Dire need for **simplification algorithms** to use this data
(online visualization, numeric simulation, ...).



EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS



A (very) brief history of geometrical simplification

Geometrical simplification can be seen as lossy compression

Goal : preserve geometry of simplified shape while reducing its complexity

- Quadric error metric [Garland Heckbert 98]
- Memoryless simplification [Lindstrom Turk 99]
- Variational approach VSA [Cohen-Steiner Alliez Desbrun 04]









Common problem : structure alteration at **coarse** complexities



EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

Structure alteration



Novembre 2014




EUROGRAPHICS 2016


THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

Our method – overview


Our method



Initial mesh
6,500 vertices




Detection of proxies




Graph of proxies

65 vertices




Decimation


8 vertices
(end of decimation)




Structure unaware




65 vertices




8 vertices




end



65 vertices



8 vertices



end




EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

General decimation algorithm

Edge collapse: merge two vertices of an edge e into a vertex v



Decimation algorithm:

- Edges \leftarrow All edges of the mesh to be simplified
- While Edges not empty
 - Extract e in Edges where $cost(e)$ is minimum
 - If $valid(e)$ is true then
 - Collapse(e) (place the new point where the cost is minimized)
 - Update cost of edges in the neighborhood of e

Parameterized by a **cost function $cost(e)$** and a **validity function $valid(e)$**



EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

Decimation algorithm – Cost function

Cost function :

Given an edge e and a new position v specify a (geometric) cost for this alteration.


Placement function :

Given an edge e specify where the new vertex must be placed after the edge collapse.
Usually placed at the point minimizing the cost.

Our cost function :

Takes into account squared distances to :

- planes of neighbors triangles
- orthogonal planes of neighbors border triangles
- planes of neighbors proxies
- orthogonal planes of neighbors border proxies triangles



EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

Decimation algorithm – Cost function

Placement function :

Given an edge e specify where the new vertex must be placed after the edge collapse.
Usually placed at the point minimizing the cost.


Cost function :

Given an edge e and a new position v specify a (geometric) cost for this alteration.

Our cost function :

Takes into account squared distances to :

- planes of neighbors triangles
- orthogonal planes of neighbors border triangles
- planes of neighbors proxies
- orthogonal planes of neighbors border proxies triangles



orthogonal planes
of border triangles

border proxies triangles



EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

Decimation algorithm – Cost function

Placement function :

Given an edge e specify where the new vertex must be placed after the edge collapse.
Usually placed at the point minimizing the cost.


Cost function :

Given an edge e and a new position v specify a (geometric) cost for this alteration.


Our cost function :

Takes into account squared distances to :


- planes of neighbors triangles
- orthogonal planes of neighbors border triangles
- planes of neighbors proxies
- orthogonal planes of neighbors border proxies triangles



orthogonal planes
of border triangles



orthogonal planes
of border triangles



border proxies triangles



Decimation algorithm

Placement function :

Given an edge e specify where the new vertex must be placed after the edge collapse.
Usually placed at the point minimizing the cost.


Cost function :

Given an edge e and a new position v specify a (geometric) cost for this alteration.


Our cost function :

Takes into account squared distances to :


- planes of neighbors triangles
- orthogonal planes of neighbors border triangles
- planes of neighbors proxies
- orthogonal planes of neighbors border proxies triangles



orthogonal planes
of border triangles



orthogonal planes
of border triangles



planes of neighbors
proxies

c



Decimation algorithm – Cost function

Placement function :

Given an edge e specify where the new vertex must be placed after the edge collapse.
Usually placed at the point minimizing the cost.


Cost function :

Given an edge e and a new position v specify a (geometric) cost for this alteration.


Our cost function :

Takes into account squared distances to :


- planes of neighbors triangles
- orthogonal planes of neighbors border triangles
- planes of neighbors proxies
- orthogonal planes of neighbors border proxies triangles




orthogonal planes
of border triangles



orthogonal planes
of border triangles



planes of neighbors
proxies



orthogonal planes of neighbors
border proxies triangles



Decimation algorithm – Cost function

Placement function :

Given an edge e specify where the new vertex must be placed after the edge collapse.
Usually placed at the point minimizing the cost.

Cost function :

Given an edge e and a new position v specify a (geometric) cost for this alteration.

Our cost function :

Takes into account squared distances to :

- planes of neighbors triangles
- orthogonal planes of neighbors triangles (if edge on the border)
- planes of neighbors proxies
- orthogonal planes of neighbors proxies (if edge on the border of a proxy)

Two parameters in $(0,1)$:

- ***Border*** parameter : trade border preservation for inner surface preservation
- ***Abstraction*** parameter : trade planar proxy proximity to initial surface proximity




EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS





Decimation algorithm – abstraction parameter

Abstraction parameter : trade planar proxy proximity to initial surface proximity

Simplification when changing abstraction parameter λ
 $\lambda=0$ $\lambda=0.5$



Initial mesh with detected planar proxies




EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

Decimation algorithm – validity function

Validity criterion :

Reject an edge collapse if it violates one the three structure preserving rules :



Forbidden proxy join:

Two proxies can't be join if they are not linked in the initial proxy graph.

Proxy degeneration :

A proxy had less than 4 vertices after an edge collapse.

Corner alteration :




A corner is destroyed after an edge collapse.



EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS



Some results



EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS



Some results



EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

Some results






EUROGRAPHICS 2016




THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS

Some results


Input : 400,000 vertices




Our output when
simplification **stops**
(350 vertices)




Structure unaware
methods
(350 or more vertices)



Garland Heckbert



VSA









Lindstrom-Turk









EUROGRAPHICS 2016



THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS











Generic data-structure

Skeleton-blocker data-structure



Based on 'Efficient data-structure for representing and simplifying simplicial complexes in high dimensions' [Attali Lieutier Salinas SoCG11, IJCGA12]

Able to represent simplicial complexes (meshes) of *any dimension*, not necessarily *manifold* (contrarily to CGAL Polyhedron_3)

Around **65 % times faster** than CGAL to contract a random sphere in 3D with n points to a tetrahedron

Public released by the end of 2014 in Gudhi's open source library

<https://project.inria.fr/gudhi/software/>



Conclusion and future works

Structure-aware mesh decimation :

- Decimation : automated, efficient, robust (geometrical and topological noise)
- Structure : robustness to imperfect structure detection, hybrid

Possible extensions :

- Non planar primitives
- Simplification of primitives set and graph in tandem
- Semantic rules



EUROGRAPHICS 2016

THE 37th ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS



A complex, abstract geometric background featuring a dense wireframe mesh on the left transitioning into a series of large, light-colored, faceted polyhedra on the right. The polyhedra are rendered with soft shadows and highlights, giving them a three-dimensional appearance against a lighter background.

Thank you!



EUROGRAPHICS 2016

THE 37TH ANNUAL CONFERENCE OF THE
EUROPEAN ASSOCIATION FOR COMPUTER GRAPHICS