



Using Subqueries to Solve Queries

Objectives

After completing this lesson, you should be able to do the following:

- Define subqueries
- Describe the types of problems that the subqueries can solve
- List the types of subqueries
- Write single-row and multiple-row subqueries

Lesson Agenda

- Subquery: Types, syntax, and guidelines
- Single-row subqueries:
 - Group functions in a subquery
 - `HAVING` clause with subqueries
- Multiple-row subqueries
 - Use `ALL` or `ANY` operator
- Null values in a subquery

Using a Subquery to Solve a Problem

Who has a salary greater than Abel's?

Main query:



Which employees have salaries greater than Abel's salary?

Subquery:



What is Abel's salary?




Subquery Syntax

```
SELECT    select_list
FROM      table
WHERE     expr operator
          (SELECT      select_list
           FROM        table);
```

- The subquery (inner query) executes *before* the main query (outer query).
- The result of the subquery is used by the main query.

Using a Subquery

```
SELECT last_name, salary
FROM employees
WHERE salary >
    (SELECT salary
     FROM employees
     WHERE last_name = 'Abel');
```

A red box highlights the subquery: (SELECT salary FROM employees WHERE last_name = 'Abel');. A red arrow points from the value 11000 to the > operator in the main query's WHERE clause.


	LAST_NAME	SALARY
1	King	24000
2	Kochhar	17000
3	De Haan	17000
4	Hartstein	13000
5	Higgins	12000

Guidelines for Using Subqueries


- Enclose subqueries in parentheses.
- Place subqueries on the right side of the comparison condition for readability (However, the subquery can appear on either side of the comparison operator.).
- Use single-row operators with single-row subqueries and multiple-row operators with multiple-row subqueries.

Types of Subqueries

- Single-row subquery



- Multiple-row subquery



Lesson Agenda



- Subquery: Types, syntax, and guidelines
- Single-row subqueries:
 - Group functions in a subquery
 - `HAVING` clause with subqueries
- Multiple-row subqueries
 - Use `ALL` or `ANY` operator
- Null values in a subquery

Single-Row Subqueries

- Return only one row
- Use single-row comparison operators

Operator	Meaning
=	Equal to
>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
<>	Not equal to

Executing Single-Row Subqueries


```
SELECT last_name, job_id, salary
FROM employees
WHERE job_id =  (SELECT job_id
                                FROM employees
                                WHERE last_name = 'Taylor')
AND salary >  (SELECT salary
                                FROM employees
                                WHERE last_name = 'Taylor');
```

The diagram illustrates the execution of a single-row subquery. The main query filters employees by job_id and salary. The subquery for job_id returns 'SA_REP', and the subquery for salary returns '8600'.

	LAST_NAME	JOB_ID	SALARY
1	Abel	SA_REP	11000

Using Group Functions in a Subquery

```
SELECT last_name, job_id, salary
FROM   employees
WHERE  salary =
      (SELECT MIN(salary)
       FROM   employees);
```



	LAST_NAME	JOB_ID	SALARY
1	Vargas	ST_CLERK	2500

The HAVING Clause with Subqueries

- The Oracle server executes the subqueries first.
- The Oracle server returns results into the HAVING clause of the main query.

```
SELECT  department_id, MIN(salary)
FROM    employees
GROUP BY department_id
HAVING  MIN(salary) > (SELECT MIN(salary)
                       FROM    employees
                       WHERE    department_id = 50);
```

2500

	DEPARTMENT_ID	MIN(SALARY)
1	(null)	7000
2	90	17000
3	20	6000
...		
7	10	4400

What Is Wrong with This Statement?

```
SELECT employee_id, last_name
FROM employees
WHERE salary =
      (SELECT MIN(salary)
       FROM employees
       GROUP BY department_id);
```

ORA-01427: single-row subquery returns more than one ...



An error was encountered performing the requested operation:

ORA-01427: single-row subquery returns more than one row
01427. 00000 - "single-row subquery returns more than one row"

*Cause:

*Action:

Error at Line:1

**Single-row operator
with multiple-row
subquery**

No Rows Returned by the Inner Query

```
SELECT last_name, job_id
FROM   employees
WHERE  job_id =
      (SELECT job_id
       FROM   employees
       WHERE  last_name = 'Haas');
```

0 rows selected

Subquery returns no rows because there is no employee named "Haas."

Lesson Agenda

- Subquery: Types, syntax, and guidelines
- Single-row subqueries:
 - Group functions in a subquery
 - `HAVING` clause with subqueries
- Multiple-row subqueries
 - Use `ALL` or `ANY` operator
- Null values in a subquery

Multiple-Row Subqueries

- Return more than one row
- Use multiple-row comparison operators

Operator	Meaning
IN	Equal to any member in the list
ANY	Must be preceded by =, !=, >, <, <=, >=. Compares a value to each value in a list or returned by a query. Evaluates to <code>FALSE</code> if the query returns no rows.
ALL	Must be preceded by =, !=, >, <, <=, >=. Compares a value to every value in a list or returned by a query. Evaluates to <code>TRUE</code> if the query returns no rows.

Using the ANY Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary
FROM   employees
WHERE  salary < ANY
      (SELECT salary
       FROM   employees
       WHERE  job_id = 'IT_PROG')
AND    job_id <> 'IT_PROG';
```

9000, 6000, 4200

	EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
1	144	Vargas	ST_CLERK	2500
2	143	Matos	ST_CLERK	2600
3	142	Davies	ST_CLERK	3100
4	141	Rajs	ST_CLERK	3500
5	200	Whalen	AD_ASST	4400

...

9	206	Gietz	AC_ACCOUNT	8300
10	176	Taylor	SA_REP	8600

Using the ALL Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary
FROM   employees          9000, 6000, 4200
WHERE  salary < ALL
      (SELECT salary
       FROM   employees
       WHERE  job_id = 'IT_PROG')
AND    job_id <> 'IT_PROG';
```

	EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
1	141	Rajs	ST_CLERK	3500
2	142	Davies	ST_CLERK	3100
3	143	Matos	ST_CLERK	2600
4	144	Vargas	ST_CLERK	2500

Lesson Agenda

- Subquery: Types, syntax, and guidelines
- Single-row subqueries:
 - Group functions in a subquery
 - `HAVING` clause with subqueries
- Multiple-row subqueries
 - Use `ALL` or `ANY` operator
- Null values in a subquery

Null Values in a Subquery

```
SELECT emp.last_name  
FROM   employees emp  
WHERE  emp.employee_id NOT IN  
                                (SELECT mgr.manager_id  
                                FROM   employees mgr);
```

0 rows selected

Summary

In this lesson, you should have learned how to:

- Identify when a subquery can help solve a problem
- Write subqueries when a query is based on unknown values

```
SELECT    select_list
FROM      table
WHERE     expr operator
          (SELECT select_list
           FROM    table);
```