


Mid-Power PLCC-6 3535 LEDs 0.5W - RF-A series

Selector Guide



Product	Power	Color				XY/Wd	Max current (mA)	viewing angle (°)	ESD withstand voltage(HBM)	automotive standard
			IF(mA)	vf(V)	Flux/iv					
RF-A1T35-W5SE-A9	0.5W	White	150	3.0-3.4	55.3-61.2-67.8-75.3	ZG1/ZG2 (0.326,0.345)	180	120°	8000	AEC-Q101
RF-A1T35-WYSE-A9	0.5W	PC Amber	150	3.0-3.4	40.9-45.3-50-55.3	5E (0.572,0.417)	180	120°	8000	AEC-Q101
RF-OMRA35TS-AB-J	0.5W	Red	150	2.0-2.6	19.6-21.8-24.2-26.9	617.5-620-622.5-625	160	120°	8000	AEC-Q101
RF-A2T35-R15E-R4	0.5W	Red	150	2.0-2.6	24.2-26.9-30-33.4	612.5-615-617.5-620	160	120°	8000	AEC-Q101
RF-A2T35-R30E-R4	0.5W	Red	150	2.0-2.6	24.2-26.9-30-33.4	627.5-630-632.5-635	160	120°	8000	AEC-Q101
RF-A2T35-Y93E-Y6	0.5W	Yellow	150	2.0-2.6	19.6-21.8-24.2-26.9	587-589.5-592-594.5	160	120°	8000	AEC-Q101
RF-A4T35-R15E-R4	0.5W	Red	150	2.0-2.6	24.2-26.9-30-33.4	612.5-615-617.5-620	160	120°	8000	AEC-Q102
RF-A4T35-R20E-R4	0.5W	Red	150	2.0-2.6	17.7-19.6-21.8-24.2	617.5-620-622.5-625	160	120°	8000	AEC-Q102
RF-A4T35-R30E-R4	0.5W	Red	150	2.0-2.6	13-14.4-16.0-17.7	627.5-630-632.5-635	160	120°	8000	AEC-Q102

Important: This selector guide for guidance only. Contact Plus Opto for the latest detailed specifications and availability. Specifications are subject to change without notice.

Plus Opto Limited | Tel: +44 (0)1942 671122 | Email: sales@plusopto.co.uk | Web: www.plusopto.com