

Through Hole Oval LEDs

Selector Guide



Part Number	Emitting Colour	Resin colour	Size (mm)	Luminous Intensity Typ. (mcd)	Wavelength λ_d (nm)	Viewing Angle $2\theta_{1/2}$
SL-434YD2Q-4C-T	● Super Bright Yellow	Yellow Diffused	3.9 × 3.2	1300	590	110° 40°
SL-434VD2Q-4C-T	● Super Bright Red	Red Diffused	3.9 × 3.2	1300	624	110° 40°
SL-434PGD2Q-G5-2B-T	● Pure Green	Green Diffused	3.9 × 3.2	3800	525	110° 40°
SL-434BD2Q-B4-2B-T	● Blue	Blue Diffused	3.9 × 3.2	600	470	110° 40°
SL-544BD2I-B4-2B-T	● Blue	Blue Diffused	5.2 × 3.8	780	470	110° 40°
SL-544PGD2I-G5-2B-T	● Pure Green	Green Diffused	5.2 × 3.8	2900	525	110° 40°
SL-544VD2I-4C-T	● Super Bright Red	Red Diffused	5.2 × 3.8	1300	624	110° 40°
SL-544VD2I-4C-T	● Super Bright Yellow	Yellow Diffused	5.2 × 3.8	1000	590	110° 40°
SL-544VD2I-5C	● Super Bright Red	Red Diffused	None	2900	624	40°
SL-544PGD2I-G5-3B	● Pure Green	Green Diffused	None	3800	525	40°

Important: This selector guide for guidance only. Contact Plus Opto for the latest detailed specifications and availability. Specifications are subject to change without notice.

Plus Opto Limited | Tel: +44 (0)1942 671122 | Email: sales@plusopto.co.uk | Web: www.plusopto.co.uk | Web: www.plusopto.com