

2835 0.2W Mid-power Surface Mount LEDs

Selector Guide

Size (mm) L × W × H	Emitted Colour	Wavelength λD (nm)	Intensity I _v typ. (mcd) @ 60 mA	Viewing Angle 2θ½	Part Number
 32.8 × 3.5 × 1.9 (L × W × H mm)	Super Red	625	7	120°	LG-2835URFS-1-T60
			11	120°	67-21S/R2C-D2030B8L31926Z6/2T
			8	60°	RT2835VC-S5
	Deep Red	660	70	120°	67-21S/NDR2C-P5080B2C12029Z6/2T
	Amber	615	9	120°	LG-2835UEL-1-T60-A01
	Pure Green	525	12	120°	LG-2835DGM-1-T150
			15.5	120°	G67-12S/G2C-D1525L4L82934Z6/2T
			18	60°	RT2835PGC-G5-S15
	Yellow	590	8	120°	LG-2835UYR-1-T60
			11	120°	67-21S/Y2C-D8595B7L32128Z6/2T
			18	60°	RT2835YC-S5
	Blue	470	3	120°	LG-2835DBK-1-T150
		455	2.5	120°	67-21S/B3C-D4555D5D72936Z6/2T
		465	5	60°	RT2835BC-B4-S3

2835 0.2W Mid-power Surface Mount LEDs

Selector Guide

Size (mm) L × W × H	Emitted Colour	Wavelength λD (nm)	Intensity Iv typ. (lm) @ 60 mA	Viewing Angle 2θ½	Part Number
	Cool White	6500K	22	120°	LG-2835C-1-T60-D702
	Natural White	4000K	23	120°	LG-2835C-1-T150-D70
	Warm White	3000K	24	120°	SL-R2835W-W6M-Q20
	Pure White	6500K	28	120°	R2835W-W2M-Q20
	Warm White	3000K	22	120°	LG-2835W-1-T60-D701

Important: This selector guide for guidance only. Contact Plus Opto for the latest detailed specifications and availability. Specifications are subject to change without notice.
Plus Opto Limited | Tel: +44 (0)1942 671122 | Email: sales@plusopto.co.uk | Web: www.plusopto.co.uk | Web: www.plusopto.com

Document reference: PO-SG-3528-PLCC2 RevA | Issue date: March 2026 | © 2026 Plus Opto Limited. All rights reserved.