T +44 (0) 1942 671122 E sales@plusopto.co.uk
W plusopto.co.uk W plusopto.com
B13 Derwent Court William Way Moss Industrial Estate Leigh Lancashire WN7 3PT

Triac Mains CV Dimmable LED Drivers

PSU-SP Series Constant Voltage

Our range of Triac Mains constant voltage LED drivers feature high efficiency and 0-100% flicker free dimming. Compatible with most leading/trailing triac dimmer modules the drivers are easily integrated into LED lighting schemes. Connection via covered screw terminals.



Features

- **Constant Voltage mode power supply**
- **Triac Dimmable**
- **Covered Screw terminal connection**
- **Compact package IP20**
- **High efficiency**
- **Short circuit / Over current protection**

Specifications

PART NUMBER	AC INPUT	OUTPUT VOLTAGE	OUTPUT CURRENT	RATED POWER	PF	DIMENSIONS (mm)
SP10-12VFT	220 ~ 240V	12vdc	0.167A – 0.833A	2 ~ 10W	≥0.90	111.4*42.5*16
SP10-24VFT		24vdc	0.167A – 0.417A	4 ~ 10W		
SP30-12VFT-1	220 ~ 240V	12vdc	0.5A – 2.5A	6 ~ 30W	≥0.90	158*45.8*18.3
SP30-24VFT-1		24vdc	0.25A – 1.25A			
SP36-12VFT-1	220 ~ 240V	12vdc	1.0A - 3.0A	12 ~ 36W	≥0.90	158*45.8*18.3
SP36-24VFT-1		24vdc	0.5A – 1.5A			
SP50-12VFT-1	220 ~ 240V	12vdc	1.6A – 4.16A	19.2 ~ 50W	≥0.90	177*57.8*21.8
SP50-24VFT-1		24vdc	0.8A – 2.08A			
SP100-12VLT	220 ~ 240V	12vdc	0.83A - 8.33A	10 ~ 100W	≥0.90	195*67.1*31.2
SP100-24VLT		24vdc	0.42A - 4.17A			
SP150-12VLT	220 ~ 240V	12vdc	1.25A – 11.0A	15 ~ 132W	≥0.95	195*67.1*31.2
SP150-24VLT		24vdc	0.625A – 6.25A	15 ~ 150W		
SP200-24VLT	220 ~ 240V	24vdc	4.16A – 8.3A	100 ~ 200W	≥0.95	215*77.5*35
SP300-24VLT	220 ~ 240V	24vdc	6.0A – 12.5A	144~ 300W	≥0.95	215*77.5*35

Input Voltage Range: AC220-240V 50/60Hz {power factor measured at AC230V and full load}

Notes:
This data is for selection reference only. Please check the full data sheet for the latest specifications
Specifications may be subject to change without notice