M6 LED Panel Mount Indicators

Prominent Chrome Bezel with Resistor | 24 V DC | Built-in Resistor



Optical features	
Indicator type	standard

Electrical features	
Voltage tolerance	10 %
Pin assignment	Brass terminal = anode, tinned terminal = cathode

Mechanical features	
Lens typ	round
Lens size	3 mm
Bezel typ	Prominent bezel
Screw thread size	M6
Bezel material	Metal
Connector type	Tab terminals

Thermal features	
Operating temperature	-20...+60 °C
Storage temperature	-25...+80 °C

The Plus Opto M6 series LED panel mount indicators feature a prominent satin chrome metal bezel with M6 screw thread for secure panel mounting. Each unit incorporates a built-in current-limiting resistor for direct connection to 24 V DC supplies. Available in five colours with a round 3 mm lens, these compact indicators suit industrial control panels, machinery, and equipment status displays.

Ordering Information

Part No.	Colour	Voltage	Current	Intensity	Finish
19020351	Green	24 V DC	15 mA	6 mcd	Satin Chrome
19020352	Yellow	24 V DC	15 mA	6 mcd	Satin Chrome
19020353	Red	24 V DC	15 mA	8 mcd	Satin Chrome
19020357	Blue	24 V DC	15 mA	26 mcd	Satin Chrome
1902035W	White	24 V DC	7 mA	1050 mcd	Satin Chrome

Technical Specifications

Optical

Indicator type
Standard

Lens type
Round

Lens size
3 mm

Bezel type
Prominent bezel

Electrical

Supply voltage
24 V DC

Voltage tolerance
±10%

Pin assignment
Brass = anode, tinned = cathode

Mechanical

Screw thread
M6 × 0.5

Bezel material
Metal – satin chrome

Connector type
Tab terminals

Overall length
33 mm

Panel cutout
ø 7 mm

Thermal

Operating temp.
-20 … +60 °C

Storage temp.
-25 … +80 °C

Plus Opto Limited
Leigh, Lancashire, UK

T: +44 (0)1942 671122
E: sales@plusopto.co.uk

W: www.plusopto.co.uk

Data subject to change without notice.

DS-M6-LED-001 | © Plus Opto Limited 2026