



T +44 (0) 1942 671122 E sales@plusopto.co.uk

W plusopto.co.uk W plusopto.com

B13 Derwent Court William Way Moss Industrial Estate Leigh Lancashire WN7 3PT

Lifud CV Non-dimmable LED drivers- Selector Guide

LF-GHY series 24V 45W-240W

To support our extensive range of LED products we offer a comprehensive range of LED drivers designed specifically for lighting applications. The LF-GHY Constant Voltage non-dimmable drivers offer a high performance cost effective solution



Model	Output Power	Input Voltage	Output Voltage	Output Current	Efficiency (full load)	PF (full load)	Dimension (L*W*H)
LF-GHY045H24	45 W	220-240 Vac	24 Vdc	0-1.875 A	88% (230Vac)	0.97 (230Vac)	251*30.7*19 mm
LF-GHY075H24	75 W	220-240 Vac	24 Vdc	0-3.125 A	91% (230Vac)	0.96 (230Vac)	316*30.7*22.8 mm
LF-GHY100H24	100 W	220-240 Vac	24 Vdc	0-4.2 A	94% (230Vac)	0.98 (230Vac)	316*30.7*22.8 mm
LF-GHY150H24	150 W	220-240 Vac	24 Vdc	0-6.25 A	94% (230Vac)	0.99 (230Vac)	336*30.7*22.8 mm
LF-GHY180H24	180 W	220-240 Vac	24 Vdc	0-7.5 A	94% (230Vac)	0.99 (230Vac)	361*33.1*22.8 mm
LF-GHY240H24	240 W	220-240 Vac	24 Vdc	0-10 A	93% (230Vac)	0.99 (230Vac)	361*33.1*22.8 mm

Full data sheets are available on request from our office

Specifications may be subject to change without notice