

SL3535P415-Q8-1WY

3.5x3.5mm, UV LED

Ceramic Package Top View LED



Technical Data Sheet

Features

- Small SMT ceramic package with high efficiency.
- Low thermal resistance as low as 6°C/W.
- Soldering method: SMT.
- Binning Parameters: Brightness, Forward.
- Voltage, Wavelength and Chromaticity.
- Moisture Sensitivity Level
- Matches ANSI binning.
- Reflow soldering with JEDEC JSTD-020C compatible.
- The product itself will remain within RoHS compliant Version.

Descriptions

- The SL3535 series is a surface-mount high-power device featuring high brightness combined with a compact size that is suitable for all kinds of lighting applications such as general illumination, flash, spot, signal, industrial and commercial lighting. The thermal pad of this device is electrically isolated providing convenience in thermal and electrical design.
- The SL3535 series is one of the most promising devices in Seam high power product offering and is ready to face the challenges of today's Solid-State Lighting requirements.

Applications

- The uv curing (ink, glue, manicure)
- Industrial application (exposure, bonding)
- Disinfection sterilization
- Anti-counterfeiting recognition (barcode, yanchao, Criminal identification)



T +44 (0) 1942 671122 E sales@plusopto.co.uk W www.plusopto.co.uk
B13 Derwent Court William Way Moss Industrial Estate Leigh Lancashire WN7 3PT

SL3535P415-Q8-1WY


3.5x3.5mm, UV LED

Ceramic Package Top View LED

Technical Data Sheet

Part No.	Emitting Color	Lens Color
SL3535P415-Q8-1WY	UV	Water Clear

Package Dimension



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ± 0.25 mm (.010") unless otherwise noted.

SL3535P415-Q8-1WY

3.5x3.5mm, UV LED

Ceramic Package Top View LED



Technical Data Sheet

Absolute Maximum Ratings at Ta=25°C

Parameters	Symbol	Max	Unit
Power Dissipation	Pd	1	W
Peak Forward Current ^(a)	IFP	500	mA
DC Forward Current ^(b)	IF	350	mA
Reverse Voltage	VR	5	V
Electrostatic Discharge (HBM)	ESD	2000	V
LED Junction Temperature	Tj	120	°C
Operating Temperature Range	Topr	-40°C to +85°C	
Storage Temperature Range	Tstg	-40°C to +100°C	
Soldering Temperature	Tsld	260°C for 5 Seconds	

Notes:







- a. Duty Factor = 10%, Frequency = 1 kHz
- b. Derate linearly as shown in derating curve.

Electrical Optical Characteristics at Ta=25°C

Parameters	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Radiant Flux ^(a)	Φ_v	585		715	mW	IF=350mA
Viewing Angle	2 θ 1/2	---	30	---	Deg	IF=350mA
Peak Emission Wavelength ^(b)	λ_p	413	415	417	nm	IF=350mA
Spectral Line Half-Width	$\Delta\lambda$	---	20	---	nm	IF=350mA
Forward Voltage ^(c)	VF	3.0	3.20	3.40	V	IF=350mA
Thermal Resistance	Rth j-s	---	6.5	---	°C/W	IF=350mA
Reverse Current	IR	---	---	50	μA	VR=5V

Notes:

- a. Radiant Flux measurement tolerance: ±10%.
- b. Wavelength measurement tolerance: ±1nm
- c. Forward voltage measurement tolerance: ±0.1V

Technical Data Sheet**Typical Electrical / Optical Characteristics Curves**
(25°C Ambient Temperature Unless Otherwise Noted)


SL3535P415-Q8-1WY

3.5x3.5mm, UV LED

Ceramic Package Top View LED


Technical Data Sheet

Reel Dimensions



Carrier Tape Dimensions

Loaded quantity 500 pcs per reel.



SL3535P415-Q8-1WY

3.5x3.5mm, UV LED


Ceramic Package Top View LED



Technical Data Sheet

Packing & Label Specifications


Moisture Resistant Packaging:



Technical Data Sheet

CAUTIONS**1. Handling Precautions:**

- 1.1. Handle the component along the side surfaces by using forceps or appropriate tools.
- 1.2. Do not directly touch or handle the silicone lens surface. It may damage the internal circuitry.
- 1.3. Do not stack together assembled PCBs containing exposed LEDs. Impact may scratch the silicone lens or damage the internal circuitry.



Compare to epoxy encapsulant that is hard and brittle, silicone is softer and flexible. Although its characteristic significantly reduces thermal stress, it is more susceptible to damage by external mechanical force. As a result, special handling precautions need to be observed during assembly using silicone encapsulated LED products. Failure to comply might lead to damage and premature failure of the LED.


2. Storage

- 2.1. Do not open moisture proof bag before the products are ready to use.
- 2.2. Before opening the package, the LEDs should be kept at 30°C or less and 60%RH or less.
- 2.3. The LEDs should be used within a year.
- 2.4. After opening the package, the LEDs should be kept at 30°C or less and 60%RH or less.
- 2.5. The LEDs should be used within 168 hours after opening the package.
- 2.6. If the moisture adsorbent material has fabled away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions. Baking treatment: 65±5°C for 24 hours

Technical Data Sheet

3. Soldering Condition

3.1. Pb-free solder temperature profile



3.2. Reflow soldering should not be done more than two times.

3.3. When soldering, do not put stress on the LEDs during heating.

3.4. After soldering, do not warp the circuit board.

3.5. Recommended soldering conditions:

Reflow soldering		Soldering iron	
Pre-heat	150~200°C	Temperature	300°C Max.
Pre-heat time	120 sec. Max.	Soldering time	3 sec. Max.
Peak temperature	260°C Max.		(one time only)
Soldering time	10 sec. Max.(Max. two times)		


3.6. Because different board designs use different number and types of devices, solder pastes, reflow ovens, and circuit boards, no single temperature profile works for all possible combinations.

Technical Data Sheet

However, you can successfully mount your packages to the PCB by following the proper guidelines and PCB-specific characterization.

4. Drive Method

4.1. An LED is a current-operated device. In order to ensure intensity uniformity on multiple LEDs connected in parallel in an application, it is recommended that a current limiting resistor be incorporated in the drive circuit, in series with each LED as shown in Circuit A below.



a. Recommended circuit.

b. The brightness of each LED might appear different due to the differences in the I-V characteristics of those LEDs.

Terms and conditions for the usage of this document

1. The information included in this document reflects representative usage scenarios and is intended for technical reference only.
2. The part number, type, and specifications mentioned in this document are subject to future change and improvement without notice. Before production usage customer should refer to the latest datasheet for the updated specifications.
3. When using the products referenced in this document, please make sure the product is being operated within the environmental and electrical limits specified in the datasheet. If customer usage exceeds the specified limits, Seam will not be responsible for any subsequent issues.
4. The information in this document applies to typical usage in consumer electronics applications. If customer's application has special reliability requirements or have life-threatening liabilities, such as automotive or medical usage, please consult with Seam representative for further assistance.
5. The contents and information of this document may not be reproduced or re-transmitted without permission by Seam.