

2835 0.2W Mid-power White Surface Mount LEDs

Selector Guide

Size (mm) L × W × H	Emitted Colour	Colour temperature (CCT) °K	Intensity lumens max @ 60 mA	Viewing Angle 2θ½	Part Number
 32.8 × 3.5 × 1.9 (L × W × H mm)	Warm White	2700K	33	120°	67-21S/KK4C-H2727M4N42833Z6/2T
		3000K	39	120°	67-21S/KK4C-H3030M42P32833Z6/2T
		3500K	39	120°	67-21S/KK4C-H4040N3P32833Z6/2T
	Natural White	4000K	39	120°	67-21S/KK4C-H5050N31P32833Z6/2T
	Daylight White	5000K	39	120°	67-21S/KK4C-H5757N31P32833Z6/2T
		5300K	39	120°	67-21S/KK4C-H6565N3P32833Z6/2T
		5700K	39	120°	67-21S/KK4C-H5757N31P32833Z6/2T/EU
	Pure White	6000K	39	120°	67-21S/KK4C-H6060N3P32833Z6/2T/EU
		6500K	39	120°	67-21S/KK4C-H6565N3P32833Z6/2T/EU
	Warm White	2700K	26	120°	SL-R2835W-W6M-Q20
	Pure White	6500K	26	120°	SL-R2835W-W2M-Q20
	Warm White	3000K	22	120°	LG-2835W-1-T60-D701
	Natural White	4000K	23	120°	LG-2835C-1-T150-D70
	Cool White	6500K	22	120°	LG-2835C-1-T60-D702

Forward Voltage: Vf 2.8-3.3V

CRI: Ra 80min

Important: This selector guide for guidance only. Contact Plus Opto for the latest detailed specifications and availability. Specifications are subject to change without notice.

Plus Opto Limited | Tel: +44 (0)1942 671122 | Email: sales@plusopto.co.uk | Web: www.plusopto.co.uk | Web: www.plusopto.com