


2835 0.2W – 1W Mid-power White Surface Mount LEDs

Selector Guide



Part Number		Power	IF(mA)	VF(V)	CCT	Φ(lm)	Efficacy (lm/w)	CRI-min	Viewing angle
AS-2835D90W-2-S1-08L-PCT-HR3	Natural White	0.2W	60	2.7	4000K	36	223	80	120°
AS-2835F40W-2-S1-08L-PCT-HR3		0.2W	60	2.7	4000K	37	228	80	120°
AS-2835F39W-2-S1-08L-PCT-HR2-K6-QG-SPHO-P5		0.2W	60	2.7	4000K	39.5	246	79	120°
AS-2835D46W-2C-S1-08L-PCT-HR3-K3		1W	150	6	4000K	153	170	80	120°
AS-2835D90W-2C-S1-08L-PCT-HR3-K3		1W	150	6	4000K	160	180	80	120°
AS-2835D46W-3C-S1-08L-PCT-HR3-K3		1W	100	9	4000K	160	188	80	120°
AS-2835D90W-3C-S1-08L-PCT-HR3-K3		1W	100	9	4000K	168	195	80	120°
AS-2835F40W-3C-S1-08L-PCT-HR3-K3		1W	100	9	4000K	172	202	80	120°
AS-2835F40W-3C-S1-08L-PCT-HR3-K3-SPHO-P5		1W	100	9	4000K	177	207	80	120°

Important: This selector guide for guidance only. Contact Plus Opto for the latest detailed specifications and availability. Specifications are subject to change without notice.
Plus Opto Limited | Tel: +44 (0)1942 671122 | Email: sales@plusopto.co.uk | Web: www.plusopto.co.uk | Web: www.plusopto.com