



T +44 (0) 1942 671122 E sales@plusopto.co.uk

W plusopto.co.uk W plusopto.com

B13 Derwent Court William Way Moss Industrial Estate Leigh Lancashire WN7 3PT

Lifud CC 0/10V dimmable LED drivers- Selector Guide

LF-AAA series 24V 8W-40W

To support our extensive range of LED products we offer a comprehensive range of LED drivers designed specifically for lighting applications. The LF-AAA series 0-10V dimmable drivers offer selectable output current and flicker free dimming control.



Part Number	Output Power	Input Voltage	Output Voltage	Output Current	Efficiency (full load) 230VAC	PFC (full load) 230VAC	Dimensions mm
LF-AAA008-0350-42	8W	220-240 VAC	9-42 Vdc	100-350mA	76%	0.90	142.1x29.8x20.5
LF-AAA008-0700-12	8W		2-12Vdc	350-700mA	76%	0.90	142.1x29.8x20.5
LF-AAA0012B-0400-42	12W		9-42 Vdc	150-400mA	83%	0.90	121.9x39.9x25
LF-AAA020B-0500-42	20W			250-500mA	85%	0.95	121.9x39.9x25
LF-AAA030-0750-42	30W			550-750mA	86%	0.95	141.5x46x27.5
LF-AAA040B-1050-42	40W			750-1050mA	87%	0.95	141.5x46x27.5

High compatibility with single and multiple dimmer modules

Full data sheets are available on request from our office

Specifications may be subject to change without notice