

PF5000x10-300DL5050RGB-24V

Full Colour RGB Flexible LED Strip

Features

- Full colour flexible LED light source
- Three in one 5050 RGB LED emitters
- Easy to cut at 100mm intervals (6 LEDs)
- Wide 120° angle of emission
- Low power, low heat, long life
- 3M Adhesive backing tape



Applications: POS Display equipment & lighting

Configuration


Parameter	Rating	Unit
LED emitters PLCC 5050	300 pcs 5.0x5.0mm	TOTAL / reel
LED pitch	16.66	mm
Dimensions	5000x12mm cuttable at 100mm intervals	
Termination	5x Flying wire leads 200mm long	
Connection	4 wire: Red, Green, Blue, with Common +ve (Black wire)	

Electro-optical characteristics Ta=25°C

Part Numbers	Colour (nm)	QTY/M	Luminous Flux (LM/M)	Current/M (24VDC)	Rated Power (max W/M)
PF5000x10-300RGB-24v/IP20 PF5000x10-300RGB-24v IP62 PF5000x10-300RGB-24v IP68	620-630	(60pcs)	146	0.22A	4.8W
	520-535		338	0.2A	4.8W
	460-475		97	0.2A	4.8W
	RGB		546	0.60A	14.4W

Operating Voltage	24v	Vdc
Operating Temp	-20 to +45°C	°C
Storage Temp	-0 to +55°C	°C

Dimensions



Handling notes:

Ensure that the correct low voltage dc power supply is matched to the flexible strip specification

Avoid repeated bending of the strip as this will damage the circuit and components and please observe the maximum bend radius of 30mm

Avoid handling of the surface components in particular the LED emitters as any pressure may result in damage and latent failures.

When cutting IP65 the ingress protection will be compromised please ensure that the assembly is re-sealed accordingly in order to maintain the IP rating

Installation notes:

To achieve a consistent luminous effect, each 5 metre should be connected to the power source.

To ensure long life we recommend that the strip is kept as cool as possible and environments where the temperature exceeds 40°C should be avoided

Drive & Control:

For control solutions please refer to our range of controllers and drive options which include DMX, RF Wireless, WiFi. More information may be found at <https://plusopto.com/category-led-drivers> and <https://plusopto.com/category-led-controllers>

Specifications may be subject to change without notice