

3528 PLCC-2 Surface Mount LEDs

Selector Guide

Size (mm) L × W × H	Emitted Colour	Wavelength λD (nm)	Intensity Iv typ. (mcd) @ 20 mA	Viewing Angle 2θ½	Part Number
 3.5 × 2.8 × 1.9 (L × W × H mm)	Super Red	625	440	120°	LHRF9553S/TR1
			715		SC21RN12JS-T2U-1
			850		SLM-1311-HRKC-X2
	Super Red	630	500	120°	LHRF9553L-B01
	Amber	615	200	120°	LUES9553
			900		SC21AA09JS-RS2-1
	Yellow/Green	573	70	120°	SL-R3528GC-2B-TR10
	Pure Green	520	1200	120°	SLM-1311-UGKC-X2-D
		525	1200	120°	SL-R3528PGC-G5-1B
			1250	120°	LDGM9553/A
	Yellow	590	500	120°	LHY9553R
			600		SL-R3528YC-3C
			900		LUYS9553-B01
	Yellow	587	600	120°	SC21YN12JS-UV1-1-R
	Blue	470	320	120°	LDBK9553
			400		R3528BC-B4-1B
			350		SLM-1311-BXKC-X2

3528 PLCC-2 Surface Mount LEDs

Selector Guide

Size (mm) L × W × H	Emitted Colour	Wavelength λD (nm)	Intensity I _v typ. (mcd) @ 20 mA	Viewing Angle 2θ _½	Part Number
	Cool White	6500K	2200	120°	LWK9553CW
	Natural White	4000K	2300	120°	LWK9553NW
	Warm White	3000K	2300	120°	LWK9553WW
	Pure White	6500K	2500 (8lm)	120°	SL-R3528W-W2-1F
	Warm White	3000K	2300 (7lm)	120°	SL-R3528W-W6-1F

Important: This selector guide for guidance only. Contact Plus Opto for the latest detailed specifications and availability. Specifications are subject to change without notice.

Plus Opto Limited | Tel: +44 (0)1942 671122 | Email: sales@plusopto.co.uk | Web: www.plusopto.co.uk | Web: www.plusopto.com

Document reference: PO-SG-3528-PLCC2 RevA | Issue date: March 2026 | © 2026 Plus Opto Limited. All rights reserved.