

Multimodal Data Processing

Geoffrey Iyer

University of California

gsiyer@math.ucla.edu

June 13th, 2017

Overview

- 1 Introduction
 - Multimodality
- 2 Multimodal Segmentation
 - Problem setup
 - Multimodal weights
 - Feature extraction with graph Laplacian
- 3 Results
 - DFC2015 data
 - Umbrella data
- 4 Current Work: Graph Matching
 - Graph matching
- 5 References

Multimodal datasets

With the increasing availability of data, many applications involve data drawn from more than one source (called *modalities*).




(a) Exposure bracketed sequence



(b) Fused result

Exposure Fusion:
[Mertens et al, CGF, 2008]



↓
Speech Recognition

Speech Recognition:
[Datcu et al, IEEE CVPR 2007]

Challenges in multimodality

Most multimodal methods are developed specifically for one problem, BUT:

[Lahat et al, IEEE 2015]: “... a solution that is based on a sufficiently data-driven, model-free approach may turn out to be useful in very different domains.”

Our Previous Work

First attempt: Multimodal segmentation via graph methods.

Assumes datasets are coregistered (share a common indexing).

Focus on RGB/Lidar image segmentation.


Accepted to ICIP, Sept 2017.

Example Data

From IEEE Data Fusion Contest, 2015
[Bampos-Taberner et al, IEEE J-STARS 2016].



RGB Modality



Lidar Modality

Notation

From each modality, have a data set X^k . ℓ = number of modalities.

N = number of observations.

d_j = dimension of set X^k . (Can view $X^k \in \mathbb{R}^{N \times d_k}$).

From co-registration assumption:

i -th point in X^{k_1} corresponds to i -th point in X^{k_2} .

Create concatenated set $X = (X^1, X^2, \dots, X^\ell) \subseteq \mathbb{R}^{N \times (d_1 + \dots + d_\ell)}$.

x_i = element i from X . x_i^k = element i from X^k .

Graph Representation: Background

When using a single modality:

For each pair $x_i, x_j \in X$, define a *weight* w_{ij} that measures the similarity between the points.

\implies represent data as $N \times N$ weight matrix W .

Common similarity measure from the literature: RBF kernel

$$w_{ij} = \exp \left(- \|x_i - x_j\|^2 / \sigma \right).$$

Need to adapt this to multimodal data.

Multimodal Weight Matrix

For each modality X^k , calculate the distance matrix E^k via

$$E_{ij}^k = \left\| x_i^k - x_j^k \right\|.$$

$\|\cdot\|$ chosen based on the details of the modality.

(in our examples $\|\cdot\|$ is the 2-norm)

Scale each matrix by standard deviation (nondimensionalization)

$$\bar{E}^k = \frac{E^k}{\text{std}(E^k)}.$$

Multimodal Weight Matrix

Define

$$w_{ij} = \exp \left(- \max \left(\bar{E}_{ij}^1, \dots, \bar{E}_{ij}^k \right) / \sigma \right).$$

Heuristics:

- Standard deviation scaling allows us to directly compare $\bar{E}^{k_1}, \bar{E}^{k_2}$ with reasonable results.
- Because of the max, elements are similar under this measure only if they are similar in each modality.

Graph min-cut

Use weights W to segment X into A_1, \dots, A_k . We want to

- group nodes with high similarity (weight) together
- ensure each set is a reasonable size

Use the *Normalized graph-cut*

$$\text{Ncut}(A_1, \dots, A_k) = \frac{1}{2} \sum_{j=1}^k \frac{W(A_j, A_j^c)}{\text{vol}(A_j)}.$$

$$W(A, B) = \sum_{i \in A, j \in B} w_{ij}.$$

$$\text{vol}(A) = \sum_{i \in A, j \in X} w_{ij}.$$

Exact min-cut solution is computationally infeasible.

Graph Laplacian

A well-known relaxation for graph min-cut problem:
eigenvectors of the (normalized) graph Laplacian L .

$$L = I - D^{-1/2}WD^{-1/2},$$

where $D = N \times N$ diagonal matrix (degree matrix), with

$$d_{ii} = \sum_{j=1}^n w_{ij}.$$

Feature extraction

Result of [vonLuxburg, Stat Comput 2007]

eigenvectors of $L \iff$ features extracted from data

Can use eigenvectors for a variety of applications.

Our results: Use the eigenvectors to segment the data.


- K-means (unsupervised)
- Graph MBO (semisupervised) [Z. Meng et al, IPOL 2017]

Data

Our algorithm applied to DFC 2015
[Bampos-Taberner et al, IEEE J-STARs 2016].




RGB Modality



Lidar Modality

DFC2015 data


Results




Example eigenvectors of graph Laplacian

Results

K-means result (unsupervised). $m = 6$ classes.




Classes




Regions on original image

Results

MBO (7% supervised). $m = 6$ classes.



Classes




Regions on original image

Data

Our algorithm applied to [Scharstein et al., GCPR 2014] dataset.




RGB Modality



Lidar Modality

Results



Example eigenvectors of graph Laplacian

Results

Spectral Clustering result (unsupervised). $m = 6$ classes.




Classes



Regions on original image

Results

MBO result (5% supervised). $m = 6$ classes.



Classes



Regions on original image

Graph Matching

Goal: Remove or weaken the coregistration assumption.

Current idea: Graph matching.

View each dataset as a (weighted) graph.

Try to match nodes with similar structure.

Problem Setup

Two weighted graphs, G_1, G_2 , with weight matrices W_1, W_2 .

For now, $|G_1| = |G_2| = N$.

Search for a graph isomorphism $G_1 \rightarrow G_2$ preserving edge weights.



Best isomorphism is $1 \rightarrow 2, 2 \rightarrow 3, 3 \rightarrow 1$.

Problem Setup

Isomorphism $G_1 \rightarrow G_2$ corresponds to a permutation on nodes.
Have P the corresponding permutation matrix. Want to minimize

$$\left\| W_1 - PW_2P^T \right\|_F^2.$$

Exact solution is too expensive. Can solve using graph Laplacian trick from

[Umeyama, IEEE TPAMI 1988, Knossow et al., GbRPR 2009].

Relaxation

Relax problem to

$$Q^* = \operatorname{argmin}_{Q Q^T = I} \left\| W_1 - Q W_2 Q^T \right\|_F^2.$$

Let L_1, L_2 the graph Laplacians corresponding to W_1, W_2

U_1, U_2 the corresponding matrices of eigenvectors.

Then $Q^* = U_1 S U_2^T$.

S is a diagonal matrix with entries of ± 1 to account for sign ambiguity in eigenvectors.

Heuristics

Recall from graph Laplacian

column of $U_i \iff$ feature extracted from data

row of $U_i \iff$ image of data point in new feature space.

Match rows of U_1 to rows of U_2 by considering $U_1 U_2^T$.

Matching Algorithm

Q_{ij}^* gives the similarity between node i of G_1 and node j of G_2 .

Choose a permutation $p : \{1, 2, \dots, N\} \rightarrow \{1, 2, \dots, N\}$ via

$$\operatorname{argmax}_{\text{permutations } p} \sum_{i=1}^N Q_{i,p(i)}^*.$$



Hungarian algorithm finds this in $O(N^3)$ [Munkres, SIAM 1957].

Benefits of Graph Matching

Benefits of Graph Matching

- 1 Invariant under conformal maps.
 - scaling, shifts, rotations, etc.
 - robust to continuous deformation.
- 2 A precise number representing similarity between nodes gives us many options.
 - Thresholding
 - Hierarchical matching
- 3 Easy extension to the case $|G_1| \neq |G_2|$.

Example Matching



Graph Match on Synthetic Data

Change Detection

One possible application: Change detection.




Given images X and Y of the same scene, compare coregistration against results of graph matching. Use this to pick out large changes between X , Y .

From graph matching, get a permutation

$$\rho : \{1, \dots, n\} \rightarrow \{1, \dots, n\}.$$

Compare x_i to $x_{\rho(i)}$, and y_i to $y_{\rho(i)}$.

Change Detection Example

Image X Image Y Naive difference $\|X - Y\|$  $\|x_i - x_{\rho(i)}\|$

References I



Tom Mertens and J. Kautz and Frank Van Reeth

Exposure Fusion: A Simple and Practical Alternative to High Dynamic Range Photography

Computer Graphics Forum 28(1):161 - 171



D. Datcu and Z. Yang and L. Rothkrantz (2007)

Multimodal workbench for automatic surveillance applications

2007 IEEE Conference on Computer Vision and Pattern Recognition 1-2



Lahat, Dana and Adalı, Tülay and Jutten, Christian (2015)

Multimodal Data Fusion: An Overview of Methods, Challenges and Prospects

Proceedings of the IEEE 103(9), 1449-1477



Yi-Ren Yes and Chun-Hao Huang and Yu-Chiang Frank Wang

Heterogeneous Domain Adaptation and Classification by Exploiting the Correlation Subspace

IEEE Transactions on Image Processing 23(5), 2009-2018

References II



Wang, Chang and Mahadevan, Sridhar (2013)

Manifold Alignment Preserving Global Geometry

Proceedings of the Twenty-Third International Joint Conference on Artificial Intelligence IJCAI '13, 1743-1749



Tuia, Devis AND Camps-Valls, Gustau (2016)

Kernal Manifold Alignment for Domain Adaptation

PLOS ONE 11, 1-25



M. Campos-Taberner and A. Romero-Soriano and C. Gatta and G. Camps-Valls and A. Lagrange and B. Le Saux and A. Beaupre and A. Boulch and A. Chan-Hon-Tong and S. Herbin and H. Randrianarivo and M. Ferecatu and M. Shimon and G. Moser and D. Tuia (2015)

Processing of Extremely High-Resolution LiDAR and RGB Data: Outcome of the 2015 IEEE GRSS Data Fusion Contest #8211;Part A: 2-D Contest

IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing 9(12), 5547-5559

References III



Iyer, Geoffrey and Chanussot, Jocelyn and Bertozzi, Andrea (2017).

A Graph-Based Approach for Feature Extraction and Segmentation of Multimodal Images

Preprint



Daniel Scharstein and Heiko Hirschmüller and York Kitajima and Greg Krathwohl and Nera Nešić and Xi Wang and Porter Westling (2014)

High-resolution stereo datasets with subpixel-accurate ground truth

Proceedings of the 36th German Conference on Pattern Recognition 31-42



Umeyama, S. (1988)

An Eigendecomposition Approach to Weighted Graph Matching Problems

IEEE Trans. Pattern Anal. Mach. Intell., 10(5), 695-703

References IV



Knossow, David and Sharma, Avinash and Mateus, Diana and Horaud, Radu (2009)

Inexact Matching of Large and Sparse Graphs Using Laplacian Eigenvectors

Graph-Based Representations in Pattern Recognition: 7th IAPR-TC-15 International Workshop, 2009. Proceedings



vonLuxburg, Ulrike (2007)

A tutorial on spectral clustering

Statistics and Computing, 17(4), 395-416



Ekaterina Merkurjev and Tijana Kostic and Andrea L Bertozzi (2013)

An MBO scheme on graphs for classification and image processing

SIAM Journal on Imaging Sciences, 6(4), 1903-1930

References V



Charless Fowlkes and Serge Belongie and Fan Chung and Jitendra Malik
(2004)

Spectral Grouping Using the Nystrom Method

IEEE Transactions on Pattern Analysis and Machine Intelligence, 26(2)



J. Munkres (1957)

Algorithms for the Assignment and Transportation Problems

Journal of the Society for Industrial and Applied Mathematics, 5(1):3238



Z. Meng, E. Merkurjev, A. Koniges, and A. L. Bertozz (2017)

Hyperspectral Image Classification Using Graph Clustering Methods

IPOL 2017, preprint