

Uniclass L68117	EPIC F814
CI/SfB	Vu4 (K3)



**Promat**



# Cafco MANDOLITE® CP2

*Vermiculite Cement Based Wet Mix Spray*

construction applications



[www.promat-spray.com](http://www.promat-spray.com)

## Cafco MANDOLITE® CP2

---

### Vermiculite Cement Based Wet Mix Spray

#### INTRODUCTION

Cafco MANDOLITE® CP2 is a spray applied, single package factory controlled premix, based on vermiculite and Portland cement, for internal use.

Cafco MANDOLITE® CP2 produces a monolithic coating able to withstand the thermal shocks experienced in a high intensity cellulosic fire. Concrete structures in particular, will be protected from explosive spalling when coated with Cafco MANDOLITE® CP2.

Although low in density, thus significantly reducing dead load, Cafco MANDOLITE® CP2 is highly durable and will not crack or spall under mechanical impact.

Cafco MANDOLITE® CP2 may be applied within environments where limited exposure to the elements is likely throughout the building phase of the project, e.g. perimeter beams.

Cafco MANDOLITE® CP2 is used for application to steel and concrete frames, metal floor or roof decks, and return air plenums. It may be easily removed and reinstated locally when additional fixings are required. Building types that will benefit from the use of Cafco MANDOLITE® CP2, include a wide range of educational, leisure and entertainment centres, commercial or industrial projects.

#### ADVANTAGES

- Structures protected with Cafco MANDOLITE® CP2 can provide fire resistance for up to 240 minutes.
- Does not release toxic or hazardous fumes.
- Presents no known health hazards either before, during or after application.

#### QUALITY ASSURANCE

Promat operates a quality system in accordance with BS EN ISO 9001: 2000 and has received full accreditation to these standards.

Operating to these standards means that all activities, which have a bearing upon quality, are set out in written procedures.

Systematic and thorough checks are made on all materials and their usage. Test equipment is subjected to regular checks and is referred back to national standards.

The information given in this data sheet is based on actual tests and is believed to be typical of the product. No guarantee of results is implied however, since conditions of use are beyond our control.

# Cafco MANDOLITE® CP2

## Vermiculite Cement Based Wet Mix Spray

### PROPERTIES AND PERFORMANCE

Colour and finish	Off-white with a monolithic spray texture
Minimum practical thickness	8mm when unreinforced, 15mm when reinforced
Theoretical coverage	172m <sup>2</sup> /tonne at 15mm thickness
Number of coats	One or more as required
Cure	By hydraulic set
Initial set	2 to 6 hours at 20°C and 50% RH
Density	390kg/m <sup>3</sup> ± 15% (when dry and in place)
Bond impact	No cracks or delamination
Air erosion resistance	No erosion to ASTM E859
Deflection effect	No cracks or delaminations within normal code limits
Compressive strength	563kPa (81.6lb/in <sup>2</sup> ) to ASTM E761
Combustibility	Non-combustible to BS476: Part 4
Flame spread	Class 0 as defined by the Building Regulations
Smoke generation	Does not contribute to smoke generation
Thermal conductivity	0.095W/mK at 20°C
Corrosion resistance	Does not promote corrosion of steel. However, a primed substrate is recommended for long term corrosion resistance. See <b>Preparation</b>
pH value	12.0-12.5
Fire resistance	<p>Structures protected with Cafco MANDOLITE® CP2 have undergone fire resistance tests up to 240 minutes in approved independent laboratories to recognised standards throughout the world, including:</p> <ul style="list-style-type: none"> <li>• UK (BS 476: Parts 20-21: 1987)</li> <li>• Germany (DIN 4102)</li> <li>• USA (ASTM E119 UL263)</li> </ul> <p>The tests also comply with International Standard ISO 834</p> <p>Cafco MANDOLITE® CP2 protected structures have been successfully tested under BS 476: Part 21 to failure temperatures of up to 800°C. This allows the specifier the freedom to adopt a fire engineering approach to fire resistance in accordance with BS 5950: Parts 3 and 8, as well as the Fire Appendices of the forthcoming Eurocode</p> <p>The fire resistance test results relate solely to the constructions tested and test conditions imposed. Promat provides computer based thickness calculations to meet specific fire resistance requirement. See <b>FIRE PROTECTION THICKNESS</b></p>

### PREPARATION

Typical substrates	Unprimed and primed steel, concrete frames, metal floor/roof decks and return air plenums
Substrate preparation	<p>The substrate shall be clean, dry and free from dust, loose millscale, loose rust, oil and any other condition preventing good adhesion</p> <p>Cafco MANDOLITE® CP2 can be applied to unprimed or primed steelwork. Prior to the application, incompatible primers should be prepared by the application of CAFCO® SC 125 or CAFCO® SBR Bonding Latex used as a keycoat</p>
Mesh reinforcement	<p>Most fire tests conducted have been carried out without mesh reinforcement, to demonstrate the ability of Cafco MANDOLITE® CP2 to stay in place under the most severe fire conditions. However, for maximum long term in service durability, the use of lightweight mesh reinforcement is recommended where vibration or mechanical damage and the possibility of subsequent de-bonding exist</p>



# Cafco MANDOLITE® CP2

## Vermiculite Cement Based Wet Mix Spray

### FIRE PROTECTION THICKNESS

The thickness of the fire protection for a given period of fire resistance in a cellulosic type fire, relates to the A/V ratio of the section.

All column and beam sections have their own specific A/V ratio. Please consult Promat to establish the A/V ratio for a particular beam or column section. TABLES 1 and 2 ascertain the thickness of Cafco MANDOLITE® CP2 that meets the required period of fire resistance for I-section beams and H-section columns.

For advice on thickness calculations for hollow sections, cellular beams, castellated sections, composite floors, upgrading of concrete slabs and more complex situations, please contact Promat.

**TABLE 1 Cafco MANDOLITE® CP2 thicknesses for I-section beams (3-sided exposure). Critical temperature 620°C, continuous concrete topping.**

A/V	Thickness for the required fire resistance					
	30 min	60 min	90 min	120 min	180 min	240 min
30	8mm	8mm	9mm	11mm	16mm	21mm
50	8mm	8mm	12mm	15mm	22mm	28mm
70	8mm	10mm	14mm	18mm	26mm	34mm
90	8mm	11mm	16mm	20mm	29mm	38mm
110	8mm	12mm	17mm	22mm	31mm	41mm
130	8mm	13mm	18mm	23mm	33mm	43mm
150	8mm	13mm	19mm	24mm	35mm	45mm
170	8mm	14mm	19mm	25mm	36mm	47mm
190	8mm	14mm	20mm	26mm	37mm	48mm
210	9mm	15mm	20mm	26mm	38mm	49mm
230	9mm	15mm	21mm	27mm	39mm	51mm
250	9mm	15mm	21mm	27mm	39mm	51mm
270	9mm	15mm	21mm	28mm	40mm	52mm
290	9mm	16mm	22mm	28mm	40mm	53mm
310	9mm	16mm	22mm	28mm	41mm	54mm

**TABLE 2 Cafco MANDOLITE® CP2 thicknesses for I-section beams and H-section columns (4-sided exposure). Critical temperature 550°C.**

A/V	Thickness for the required fire resistance					
	30 min	60 min	90 min	120 min	180 min	240 min
30	8mm	8mm	10mm	13mm	19mm	24mm
50	8mm	10mm	14mm	18mm	25mm	33mm
70	8mm	12mm	16mm	21mm	30mm	38mm
90	8mm	13mm	18mm	23mm	33mm	43mm
110	9mm	14mm	19mm	25mm	35mm	46mm
130	9mm	15mm	20mm	26mm	37mm	48mm
150	10mm	15mm	21mm	27mm	38mm	50mm
170	10mm	16mm	22mm	28mm	40mm	52mm
190	10mm	16mm	22mm	28mm	41mm	53mm
210	10mm	17mm	23mm	29mm	42mm	54mm
230	10mm	17mm	23mm	30mm	42mm	55mm
250	11mm	17mm	24mm	30mm	43mm	56mm
270	11mm	17mm	24mm	30mm	44mm	57mm
290	11mm	18mm	24mm	31mm	44mm	57mm
310	11mm	18mm	24mm	31mm	45mm	58mm

## HEALTH AND SAFETY

Adequate ventilation must be provided during use.

Avoid contact with the skin and eyes by using eye protection, gloves, barrier cream and a face mask.

If the product comes into contact with the skin, wash immediately with soap and water. If the eyes are affected, flush with plenty of water and seek medical attention immediately.

A safety data sheet is available from Promat upon request.

Promat activities are conducted with due regard to all statutory requirements with appropriate safeguards against exposing employees and the public to health and safety risks.



## Cafco MANDOLITE® CP2

### Vermiculite Cement Based Wet Mix Spray

#### APPLICATION

<b>Initial steps</b>	Application of Cafco MANDOLITE® CP2 must be carried out by an applicator recognised by Promat
<b>Methods</b>	Mix Cafco MANDOLITE® CP2 with potable water in a suitable mixer and apply by a spraying machine approved by Promat Cafco MANDOLITE® CP2 may be centrally pumped vertically or horizontally, enabling all spray plant and material storage to be contained in one area
<b>Limitations</b>	Cafco MANDOLITE® CP2 may be applied when the substrate and air temperatures are at least 2°C and rising, but should not be applied if the substrate or air temperatures are less than 4°C and falling. Maximum substrate and air temperature is 45°C Substrate temperature should be at least 2°C above dew point temperature

#### TOP COATING

Cafco TOPCOAT® 200 may be used as protection from frequent wash down, long term chemical spills, or for improved resistance to fungal, algal and bacterial growth.

#### PACKAGING

12.5kg bags.

#### STORAGE

Off the ground and kept dry until ready for use.

#### SHELF LIFE

Maximum 12 months.

#### ENVIRONMENTAL

- Do not discharge into drains, watercourses or soil.
- Not readily biodegradable.
- Not expected to bioaccumulate.
- Not expected to be toxic to aquatic life except at high concentrations.

## HEAD OFFICE, BELGIUM

**Promat International N.V.**  
Bormstraat 24  
2830 Tiselt  
Tel: +32 15 718 100  
Fax: +32 15 718 109  
Email: info@promat  
international.com  
www.promat-international.com  
www.promat-tunnel.com  
www.promat-marine.com  
www.promat-spray.com

## ASIA PACIFIC HEADQUARTERS, MALAYSIA

**Promat International (Asia Pacific) Limited**  
Unit 19-02-01  
Level 2 PNB Damansara  
No.19 Lorong Dungun  
Damansara Heights  
50490 Kuala Lumpur  
Tel: +60 3 2095 5111  
Fax: +60 3 2095 6111  
Email: spraysinfo@promat-ap.com  
www.promat-ap.com

## AUSTRALIA

**Promat Australia Pty. Limited**  
1 Scotland Road, Mile End South  
SA 5031 Adelaide  
Tel: 1800 PROMAT  
Fax: +61 8 8352 1014  
Email: spraysinfo@promat.com.au  
www.promat-ap.com

**Promat Australia Pty. Limited**  
Unit 1, 175 Briens Road  
NSW 2152 Northmead  
Tel: 1800 PROMAT  
Fax: +61 2 9630 0258  
Email: spraysinfo@promat.com.au  
www.promat-ap.com

**Promat Australia Pty. Limited**  
3/273 Williamstown Road  
VIC 3207 Port Melbourne  
Tel: 1800 PROMAT  
Fax: +61 3 9645 3844  
Email: spraysinfo@promat.com.au  
www.promat-ap.com

## AUSTRIA

**Promat Ges.m.b.H.**  
Seybelgasse 13  
1230 Wien  
Tel: +43 1 865 4501  
Fax: +43 1 865 3600  
Email: office@promat.at  
www.promat.at

## BELGIUM

**Promat N.V.**  
Kuijersstraat 1  
1880 Kapelle-op-den-Bos  
Tel: +32 15 713 351  
Fax: +32 15 718 229  
Email: info@promat.be  
www.promat.be

## CHINA

**Promat China Limited**  
Room 503, Block B, Qi Lin Plaza  
13-35 Pan Fu Road  
510180 Guangzhou  
Tel: +86 20 8136 1167  
Fax: +86 20 8136 1372  
Email: spraysinfo@promat-ap.com  
www.promat.com.cn

**Promat North China (Division of Promat China Limited)**  
Room 1507 Building 5  
SOHO Xiandaicheng  
No.88 Jianguo Road  
Chaoyang District  
100022 Beijing  
Tel: +86 10 8589 1254  
Fax: +86 10 8589 2904  
Email: spraysinfo@promat-ap.com  
www.promat.com.cn

## CZECH REPUBLIC

**Promat s.r.o.**  
Čkalova 22/784  
16000 Praha 6 - Bubeneč  
Tel: +420 2 2439 0811  
Fax: +420 2 3333 3576  
Email: promat@promatpraha.cz  
www.promatpraha.cz

## DENMARK

**Promat ApS**  
Tåstrup Stationscenter  
Selsmosevej 2, 1. floor  
2630 Tåstrup  
Tel: +45 7020 0482  
Fax: +45 7020 0483  
Email: info@promat-nordic.com  
www.promat-nordic.com

## FRANCE

**Promat S.A.S.**  
BP 66 Rue de L'Ammandier  
78540 Vernouillet  
Tel: +33 1 3979 6160  
Fax: +33 1 3971 1660  
Email: info@promat.fr  
www.promat.fr

## GERMANY

**Promat GmbH**  
Scheifenkamp 16  
40878 Ratingen  
Tel: +49 2102 493 0  
Fax: +49 2102 493 111  
Email: mail@promat.de  
www.promat.de

## HONG KONG

**Promat International (Asia Pacific) Limited**  
Room 1010, C.C. Wu Building  
302-308 Hennessy Road  
Wanchai  
Tel: +852 2836 3692  
Fax: +852 2834 4313  
Email: spraysinfo@promat-ap.com  
www.promat.com.hk

## INDIA

**Promat International (Asia Pacific) Limited (India Representative Office)**  
610-611, Ansal Imperial Tower  
C-Block, Community Centre  
Naraina Vihar, Naraina  
110028 New Delhi  
Tel: +91 11 2577 8413  
Fax: +91 11 2577 8414  
Email: spraysinfo@promat-ap.com  
www.promat-ap.com

## ITALY

**Promat S.p.A.**  
Corso Paganini 39/3  
16125 Genova  
Tel: +39 010 248 8411  
Fax: +39 010 213 768  
Email: info@promat.it  
www.promat.it

## MALAYSIA

**Promat (Malaysia) Sdn. Bhd.**  
Unit 19-02-01  
Level 2 PNB Damansara  
No.19 Lorong Dungun  
Damansara Heights  
50490 Kuala Lumpur  
Tel: +60 3 2095 8555  
Fax: +60 3 2095 2111  
Email: spraysinfo@promat-ap.com  
www.promat-ap.com

## NETHERLANDS

**Promat B.V.**  
Zonnebaan 36  
3542 EE Utrecht  
Tel: +31 30 241 0770  
Fax: +31 30 241 0771  
Email: info@promat.nl  
www.promat.nl

## POLAND

**Promat TOP Sp. z o.o.**  
ul. Przecławska 8  
03 879 Warszawa  
Tel: +48 22 212 2280  
Fax: +48 22 212 2290  
Email: top@promattop.pl  
www.promattop.pl

## RUSSIA

**Promat GmbH**  
Repräsentanz  
ul. Kantemirovskaya 58  
115477 Moscow  
Tel: +7 495 325 4268  
Fax: +7 495 231 7977  
Email: gd@promat.ru  
www.promat.ru

## SINGAPORE

**Promat Building System Pte. Limited**  
10 Science Park Road  
#03-14 The Alpha  
Singapore Science Park II  
117684 Singapore  
Tel: +65 6776 7635  
Fax: +65 6776 7624  
Email: spraysinfo@promat-ap.com  
www.promat-ap.com

## SPAIN

**Promat Ibérica S.A.**  
C/ Velazquez, 41 - 2 Planta  
28001 Madrid  
Tel: +34 91 781 1550  
Fax: +34 91 575 1597  
Email: info@promat.es  
www.promat.es

## SWITZERLAND

**Promat AG**  
Stationsstrasse 1  
8545 Rickenbach-Sulz  
Tel: +41 52 320 9400  
Fax: +41 52 320 9402  
Email: office@promat.ch  
www.promat.ch

## UNITED ARAB EMIRATES

**Promat Middle East**  
Suite 1805, Floor 18  
Festival City Tower  
P O. Box 123945, Dubai  
Tel: +971 4 232 9780  
Fax: +971 4 232 9781  
Email: promatmiddleeast@promat.co.uk  
www.promat-spray.com

## UNITED KINGDOM

**Promat UK Limited**  
The Sterling Centre  
Eastern Road, Bracknell  
RG12 2TD Berkshire, Great Britain  
Tel: +44 1344 381 300  
+44 1344 381 400 (technical)  
Fax: +44 1344 381 301  
Email: marketinguk@promat.co.uk  
www.promat-spray.com

## Promat Ireland

43 Fitzwilliam Square  
Dublin 2, Ireland  
Tel: +353 1 419 0437  
Fax: +353 1 460 8802  
www.promat.ie

## VIETNAM

**Promat International (Asia Pacific) Limited (Vietnam Representative Office)**  
Room 606 Giay Viet Plaza  
180-182 Ly Chinh Thang Street  
Ward 9, District 3  
Ho Chi Minh City  
Tel: +84 904 055 055  
Fax: +84 8 931 5964  
Email: spraysinfo@promat-ap.com  
www.promat-ap.com