



MolView manual

This is the manual for MolView version 2.2

MolView can be found at molview.org

Table of Contents

1. Drawing structural formulas.....	3
Top toolbar.....	3
Left toolbar.....	3
Right toolbar.....	3
2. Finding structures.....	3
3. 3D model.....	4
Reset.....	4
Representation.....	4
Background.....	4
Engines.....	4
Model transformation.....	4
Crystallography.....	4
4. Advanced tools.....	5
Link.....	5
Export.....	5
Properties.....	6
Spectroscopy.....	6
Advanced search.....	6
5. Spectroscopy.....	7
Export data.....	7
6. Custom GLmol display.....	8
Biological assembly.....	8
Chain representation.....	8
Chain coloring.....	8
Fog and clipping.....	8
7. Advanced Jmol functions.....	9
Clear.....	9
Calculations.....	9
Measurement.....	9
Render mode.....	10

1. Drawing structural formulas

You can draw structural formulas using the sketching component.

Top toolbar

The top toolbar contains all general editing tools. The *2D to 3D* tool converts the structural formula into a 3D molecule displayed in the model window.

Left toolbar

In the left toolbar, you can select a tool you want to use in order to modify or extend the structural formula. In order to draw a carbon chain using the chain tool, you have to click a start point or atom and drag a chain.

Right toolbar

The right toolbar contains some common elements and a periodic table tool in case you want to use another element. Note that you can only replace existing atoms. So in order to add an atom, you first have to add a new bond using the tools from the left toolbar.

2. Finding structures

You can load structures from large databases like PubChem via the search field located on the right side of the menubar. Just type what you are looking for and enter or click one of the search categories listed below.

- **Compounds:** small molecules from the PubChem database
- **Biomolecules:** biological macromolecules from the RCSB database
- **Crystals:** crystal structures from the Open Crystallography Database

When you type something longer than one character, a list of suggestions will appear. You can click one or use the up/down arrow keys to select one and enter it.

In addition, you can load a PubChem CID via *Compounds*, a PDB ID via *Biomolecules* or a COD ID via *Crystals*. You can also directly enter a SMILES, InChi or InChiKey string in the search field (don't use the *Compounds* button)

You can show or hide search results using the leftmost button. Note that *Biomolecules* search is absent on mobile browsers which do not support WebGL since they can't display biomolecules anyway.

3. 3D model

You can find the general 3D *Model* menu in the menubar.

Reset

This function sets the model position, zoom and rotation back to default.

Representation

You can choose from a list of different molecule representations including; ball and stick, stick, van der Waals spheres, wireframe and lines. Biomolecules are automatically drawn using ribbons.

Background

You can switch between a black and a white model background. The default background is black (exported images from GLmol or ChemDoodle have a transparent background)

Engines

You can choose from three different render engines: **GLmol**, **Jmol** and **ChemDoodle**. GLmol is used as default render engine. MolView automatically switches to:

1. **Jmol** if you execute functions from the Jmol menu
2. **ChemDoodle** if you load a crystal structure (*Glmol cannot render crystal structures*)

You might want to switch back to GLmol when you do no longer need Jmol or ChemDoole since GLmol has a better performance.

Note that biomolecules are drawn slightly different in each engine. ChemDoodle provides the finest biomolecule display. You should, however, avoid using ChemDoodle for large biomolecules.

Model transformation

You can rotate, translate and zoom the 3D model using a mouse. Use the right button for rotation, the middle button for translation (except for ChemDoodle) and the scrollwheel for zooming. On touch devices, you can rotate the model using one pointer and scale the model using multi-touch.

Crystallography

You can load an array of crystal cells (2x2x2 or 1x3x3) or a single unit cell when viewing crystal structures.

4. Advanced tools

You can find the *Tools* menu in the menubar. This menu contains several utility functions.

Link

You can link to a specific compound, biomolecule or crystal using URL parameters. This menu gives you two options:

- **Share:** use this option if you want to share the current MolView content including chemical structure, layout and molecule representation.
- **Embed:** use this option if you want to embed the current model into your website. To add the 3D view with the current structure to your website, you have to copy the given HTML code into your website.

If you only want to link to the current chemical structure, you can also copy the URL from the adress bar. (make sure the URL links to the right structure by reloading the page)

Export

Export options in the Export menu:

- **Structural formula image:** PNG snapshot from sketcher (*transparent background*)
- **3D model image:** PNG snapshot from model window
(*transparent background in GLmol and ChemDoodle*)
- **SDF file:** exports a MDL Molfile from the 3D model
(*displayed if the 3D model is a common molecule*)
- **PDB file:** exports a Protein Data Bank file from the 3D model
(*displayed if the 3D model is a biomolecule*)
- **CIF file:** exports a Crystallographic Information File from the 3D model
(*displayed if the 3D model is a crystal structure*)

Properties

Depending on the situation, this function gives you more information about the current molecule.

- **If the model is a biomolecule:** hotlink to RCSB Protein Data Bank page
- **If the model is a crystal structure:** hotlink to Crystallography Open Database page
- **Else:** shows a dialog with a number of properties for the structural formula from the sketcher

Spectroscopy

This method shows a dialog where you can view spectra related to the structural formula from the sketcher. More details are covered in chapter 5.

Advanced search

You can perform three types of advanced search based on the structural formula from the sketcher.

1. **Similarity search:** search for compounds with a similar structural formula
2. **Substructure search:** search for compounds with the current structure as subset
3. **Superstructure search:** search for compounds with the current structure as superset

5. Spectroscopy

The Spectroscopy menu item is located under *Model > Chemical data* in the menubar. This menuitem shows the spectroscopy dialog where you can choose from a number of spectra (if available)

1. H1-NMR prediction
2. Mass spectrum
3. IR spectrum

Export data

The spectroscopy dialog allows you to export two kind of files from the current spectrum:

- **PNG image:** snapshot from interactive spectrum
- **JCAMP file:** JCAMP-DX file of the current spectrum

6. Custom GLmol display

The GLmol render engine contains some custom display functions for biomolecules. These functions are located under the *GLmol* menu in the menubar.

Biological assembly

Some biomolecules are only a small unit (asymmetric unit) of a much larger structure (biological unit). This function allows you to view the full biological unit.

Chain representation

GLmol offers five different chain representations.

1. **Ribbon:** draws ribbon diagram (*default representation*)
2. **Cylinder and plate:** solid cylinders for α -helices and solid plates for β -sheets
3. **C-alpha trace:** lines between central carbon atom in amino-acids (*very fast rendering*)
4. **B-factor tube:** tube where thickness is calculated from the B-factor (*thermal motion*)
5. **Bonds:** all bonds are displayed as lines

Chain coloring

You can choose from five chain coloring methods.

1. **Secondary structures:** different colors for α -helices, β -sheets, etc.
2. **Spectrum:** chain colored with full color spectrum (*blue-green-red*)
3. **Chain:** each chain gets a different color
4. **B-factor:** blue for low B-factor and red for high B-factor (*if provided*)
5. **Polarity:** colors polar amino-acids red and non polar amino-acids white

Fog and clipping

When you are viewing large structures, like biomolecules, it can be useful to hide a certain part using fog or clipping. GLmol offers a few options to do this.

1. **Fog:** you can move the fog forward by dragging the mouse **up** while holding the **right** mousebutton and vice versa.
2. **Clipping plane:** you can move a frontal clipping plane into the structure by dragging the mouse to the **left** while holding the **right** mousebutton and vice versa.

7. Advanced Jmol functions

Jmol offers some advanced functions. You can find them in the *Jmol* menu in the menubar. Note that all functions (except for render modes) are disabled when viewing proteins.

Clear

Clears all executed calculations and measurements.

Calculations

You can perform the following Jmol calculations in Jmol:

- **MEP surface lucent/opaque:** calculates and projects molecular electrostatic potential on a translucent or opaque van der Waals surface
- **Charge:** calculates and draws the atomic charge as labels
- **Bond dipoles:** calculates and draws the individual bond dipoles
- **Overall dipole:** calculates and draws the netto bond dipole
- **Energy minimization:** executes an MMFF94 energy minimization
(note that this function only executes a maximum of 100 minimization steps at a time)

Measurement

You can do distance, angle and torsion measurements using Jmol. You can select one of these measurement modes via the *Jmol* menu (*click selected mode again to deselect*)

- **Distance:** distance between two atoms in **nm** (*select two atoms*)
- **Angle:** angle between two bonds in **deg** (*select three atoms*)
- **Torsion:** torsion between four atoms in **deg** (*select four atoms*)

Note that the resolved 3D model is only an approach of the real molecule, this means you have to execute an **Energy minimization** in order to do reliable measurements.

Render mode

In Jmol, you can switch between different render modes in order to speed up performance or to increase quality.

There are three render modes:

1. **Everything:** slowest but best quality
2. **Normal:** average speed and quality
3. **Minimal:** fastest but least quality