

Git - Single Repository

Kurt Schmidt

Dept. of Computer Science, Drexel University

August 25, 2016

(Stolen largely from Geoff Mainland)

Intro

What is version control

Git - Single Repository

Kurt Schmidt

Intro

First

Repository

`git init`
`git add`
`git commit`

Committing Changes

`help`,
Summary
`git help`

First Look at Internals

SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

- Track the history of a collection of files (source code)
- Allows us to:
 - See what files changed, and when
 - Compare (diff) two or more versions
 - Recover (check out) older versions of files
 - Experiment with new ideas, features, without the risk of losing existing work (branching) – (not this set)
- Greatly facilitates collaboration (subsequent set)

Version Control with Git

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

`git init`
`git add`
`git commit`

Committing
Changes

`help`,
Summary
`git help`

First Look at
Internals
SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

- Many version control systems: Bazaar (BZR), CVS, Subversion (SVN), Darcs, Mercurial, Perforce, Visual SourceSafe, etc.
- But **git** has (largely) won
 - Developed to manage Linux kernel source code
 - Popularised by **GitHub**
 - **Widely used**

Git - Single Repository

Kurt Schmidt

Intro

First Repository

`git init`
`git add`
`git commit`

Committing Changes

help,
Summary
`git help`

First Look at Internals
SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

First Repository

Setting up your First Repository

Git - Single Repository

Kurt Schmidt

Intro

First Repository

git init
git add
git commit

Committing Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

- You can have multiple repositories, in various locations
- The entire subtree is included
- Repositories can contain repositories (let's not do that now)
- Let's set some global settings (~/.gitconfig)

```
$ git config --global user.name "Your name"  
$ git config --global user.email "Your email"
```

The Actual Repository

Git - Single Repository

Kurt Schmidt

Intro

First Repository

`git init`
`git add`
`git commit`

Committing Changes

help, Summary

`git help`

First Look at Internals

SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

Create a new directory, with no files in it, and create an empty repository:

```
$ mkdir lab-git  
$ cd lab-git  
$ git init
```

Initialized empty Git repository in `../lab-git/.git`

Adding a New File

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

Let's create a new file

```
$ echo 'Hello, Wrld!' > hello.txt  
$ git status
```

```
# On branch master  
#  
# Initial commit  
#  
# Untracked files:  
#   (use "git add <file>..." to include in what will be committed)  
#  
# hello.txt  
nothing added to commit but untracked files present (use "git add" to track)
```


git add

Git - Single Repository

Kurt Schmidt

Intro

First Repository

git init
git add
git commit

Committing Changes

help,
Summary
git help

First Look at Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

- Any changes need to be staged, or added to the *index*
- **commit** will add staged changes to the repository, clear the index

```
$ git add hello.txt  
$ git status
```

```
# On branch master  
#  
# Initial commit  
#  
# Changes to be committed:  
#       (use "git rm --cached <file>..." to unstage)  
#  
# new file:   hello.txt  
#
```

git commit

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

- We can now commit

```
git commit [-m msg ]
```

- Note, the -m. It'll ask you for a message anyway, so might as well do it now
 - Just a quick msg, help you distinguish between commits

```
$ git commit -m "Initial commit"
```

```
[master (root-commit) 59b8633] Initial commit
1 files changed, 1 insertions(+), 0 deletions(-)
create mode 100644 hello.txt
```

Committing Changes

Oops...

Git - Single Repository

Kurt Schmidt

Intro

First Repository

git init
git add
git commit

Committing Changes

help,
Summary
git help

First Look at Internals

SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

Let's fix that error:

```
$ sed -i s/Wrld/World/ hello.txt  
$ git status
```

```
# On branch master  
# Changed but not updated:  
#   (use "git add <file>..." to update what will be committed)  
#   (use "git checkout -- <file>..." to discard changes in working directory)  
#  
# modified:   hello.txt  
#  
no changes added to commit (use "git add" and/or "git commit -a")
```

Commit New Changes

Git - Single Repository

Kurt Schmidt

Intro

First Repository

git init
git add
git commit

Committing Changes

help,
Summary
git help

First Look at Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

- We can add individual files, as before

```
$ git add hello.txt
```

- Or, the `-u` flag will have git search all the files it's previously seen (been added) for updates

```
$ git add -u
```

- Note, update won't pull in new files
- Now, we can commit

```
$ git commit -m"Fixed typo"
```

Examining the Repository – log

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

```
$ git log
```

```
commit a8cd966467c62aa93efe1069f6a7e0a301eb468b
Author: Kurt Schmidt <kschmidt@cs.drexel.edu>
Date:   Wed Jul 29 19:25:38 2015 -0400
```

Fixed typo

```
commit 59b86338e073bef31e8026761f4c809fcfe29001
Author: Kurt Schmidt <kschmidt@cs.drexel.edu>
Date:   Tue Jul 28 21:58:01 2015 -0400
```

Initial commit

Examining the Repository – diff

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals

SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

- To see the differences between 2 different commits:

```
$ git diff 59b863..a8cd96
```

```
diff --git a/hello.txt b/hello.txt
index 26899e5..8ab686e 100644
--- a/hello.txt
+++ b/hello.txt
@@ -1,1 @@
-Hello, wrld!
+Hello, World!
```

- Can, optionally, indicate an individual file:

```
$ git diff 59b863..a8cd96 -- hello.txt
```

- To compare working file(s) against last commit:

```
$ git diff HEAD -- hello.txt
```

Git - Single Repository

Kurt Schmidt

Intro

First
Repository

`git init`
`git add`
`git commit`

Committing
Changes

help,
Summary

`git help`

First Look at
Internals

SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

help, Summary

Quick Summary, So Far

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

`git init`
`git add`
`git commit`

Committing
Changes

help,
Summary
`git help`

First Look at
Internals
SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

<code>git init</code>	Initialise a new repo
<code>git status</code>	Check status of working tree
<code>git add <i>files...</i></code>	Add files (changes) to index
<code>git commit -mmsg</code>	Commit changes in index to repo
<code>git log</code>	See commit history
<code>git diff</code>	Compare versions

git help

Git - Single Repository

Kurt Schmidt

Intro

First Repository

`git init`
`git add`
`git commit`

Committing Changes

`help`,
Summary
`git help`

First Look at Internals
SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

- Get a list of `git` commands, and a brief description:
`git help`
- Get more detailed help on a topic:
`git help topic`

First Look at Internals

Index vs. Working Tree

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

`git init`
`git add`
`git commit`

Committing
Changes

`help`,
Summary
`git help`

First Look at
Internals

SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

- A *working tree* is just a copy of the files checked out of the repository. It's where you work on your files
- The *index* is the set of changes to be committed.
- The *index* may be different from the working directory
- Changes to the working directory must be added to the *index*

Branches, master, HEAD

Git - Single Repository

Kurt Schmidt

Intro

First Repository

`git init`
`git add`
`git commit`

Committing Changes

`help`,
Summary
`git help`

First Look at Internals

SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

- A brand-new repository has a single branch
 - You can branch to, e.g., add a feature
 - Merge back in when it's working happily
 - We'll discuss branching in another set
- This default branch is called `master`
- `HEAD` is a reference, points to the current (checked out) branch

SHA-1, commit identifiers

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals

SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

- Each revision (commit) gets a unique identifier

```
commit a8cd966467c62aa93efe1069f6a7e0a301eb468b
Author: Kurt Schmidt <kschmidt@cs.drexel.edu>
Date:   Wed Jul 29 19:25:38 2015 -0400
```

Fixed typo

```
commit 59b86338e073bef31e8026761f4c809fcfe29001
Author: Kurt Schmidt <kschmidt@cs.drexel.edu>
Date:   Tue Jul 28 21:58:01 2015 -0400
```

Initial commit

SHA-1, commit identifiers (cont.)

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

`git init`
`git add`
`git commit`

Committing
Changes

`help`,
Summary
`git help`

First Look at
Internals
SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

- A hash value, created from the committed content, plus a header
 - Note this serves as a padlock. The committed content can't be modified. Well, it's easy to see that it has been
- Each serves as a way to identify individual commits
- You can simply use the first 4 character (providing that they make a prefix unique to the repository)

Recovering

Removing Uncommitted Changes – git reset

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary

git help

First Look at
Internals

SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

- To remove all pending changes from the index
`git reset`
- **Note**, `--mixed` (the default) does **nothing** to the working tree, to the files in the directory

```
$ touch tmp_file  
$ git add *  
$ git status
```

```
# On branch master  
# Changes to be committed:  
#   (use "git reset HEAD <file>..." to unstage)  
#  
# modified:   hello.txt  
# new file:   tmp_file  
#
```

git reset (cont.)

- Didn't mean to include that temp file
- Let's back out all staged changes (clear the index):

```
$ git reset
```

```
Unstaged changes after reset:
M hello.txt
```

```
$ git add hello.txt
$ git status
```

```
# On branch master
# Changes to be committed:
#   (use "git reset HEAD <file>..." to unstage)
#
# modified:   hello.txt
#
# Untracked files:
#   (use "git add <file>..." to include in what will be committed)
#
# tmp_file
```

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

git reset (cont.)

Git - Single Repository

Kurt Schmidt

Intro

First Repository

git init
git add
git commit

Committing Changes

help,
Summary
git help

First Look at Internals
SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

- Add just the file we want, commit

```
$ git add hello.txt  
$ git commit -m"Added another line to hello"
```

```
[master 599c722] Added another line to hello  
1 files changed, 1 insertions(+), 0 deletions(-)
```

- Use

```
git reset HEAD file...
```

```
to unstage individual files
```

Hard reset

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

```
git reset --hard
```

You're cooking along, and you've gone down a bad path. You just want to go back to the last commit, start again. A hard reset:

- Clears the index
- Returns the working directory to the last committed state

```
$ echo "A bunch of changes that aren't working for me" >> hello.txt  
$ git reset --hard
```

```
HEAD is now at 599c722 Added another line to hello
```

```
$ cat hello.txt
```

```
Hello, World!  
How's things?
```

Check Out a File

Git - Single Repository

Kurt Schmidt

Intro

First Repository

git init
git add
git commit

Committing Changes

help,
Summary
git help

First Look at Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

Let's say you don't want to trash all of your changes, you're just unhappy with one file, want to start fresh on that. `git checkout files...`

- Recovers the **most recently committed version of the file**
- (Modifies the file(s) in your working tree)

```
$ echo "a dark path I can't find my way back from" >> trouble_file  
$ git checkout -- trouble_file  
$ cat trouble_file
```

```
Everything's fine on this line.  
$
```

(the `--` is Posix for "no more command options follow")

Removing a File from Future Commits

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

All right, you've been using a file, and you're done with it.
Maybe replacing some library w/a newer one. So, you delete it:

```
$ \rm trouble_file  
$ git commit -m "removed trouble_file"
```

```
# On branch master  
# Changed but not updated:  
#   (use "git add/rm <file>..." to update what will be committed)  
#   (use "git checkout -- <file>..." to discard changes in working directory)  
#  
# deleted:   trouble_file  
#  
no changes added to commit (use "git add" and/or "git commit -a")
```

Removing a File from Future Commits - (cont)

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

That didn't work so well. Not a problem:

```
$ git add -u  
$ git commit -m "removed trouble_file"
```

```
[master 99fd33e] removed trouble_file  
1 files changed, 0 insertions(+), 1 deletions(-)  
delete mode 100644 trouble_file
```

Removing a File – git rm

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

Do it all at once:

```
git rm files...
```

```
$ git rm old.lib
```

```
rm old.lib
```

```
$ git commit -m"removed the old lib"
```

```
[master 1fb317b] removed the old lib  
0 files changed, 0 insertions(+), 0 deletions(-)  
delete mode 100644 old.lib
```


Undoing Last Commit

Consider the recent history:

```
commit b26a94946c21248aad149557dd3d825848a06e76
Author: Kurt Schmidt <kschmidt@cs.drexel.edu>
Date:   Mon Aug 3 02:13:06 2015 -0400
```

```
    Adding curtains, bad path
```

```
commit 67fec740797b3b532d4a34100d4d7654ba3881e
Date:   Mon Aug 3 01:45:59 2015 -0400
```

```
    Building on a bad commit
```

```
commit ddfb7e2e9580d0303b9e8fa047717a4770e345ce
Date:   Sun Aug 2 23:19:26 2015 -0400
```

```
    This is a sad commit, gonna trash it
```

```
commit 501eb01dd938dd9a59f8037972007ee0f85dd15a
Date:   Sun Aug 2 23:15:18 2015 -0400
```

```
    Last good commit
```

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

Undoing Last Commit (cont.)

Let's roll back the most recent commit:

```
$ git revert b26a
```

Or, if you've not detached HEAD:

```
$ git revert HEAD
```

- Note, this **doesn't actually remove the last commit**
- Start this on a clean working directory (no changes)
- The **revert will take the working tree back to the previous commit state, then commit that**
- **Safe, no loss of history**
- Best way to go, if the repository has been published (shared)

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

Undoing Last Commit – (cont.)

This is what the commit history looks like now:

```
commit f515f31ada2b7337fac1b5ad4de8b87efb5881fc
Author: Kurt Schmidt <kschmidt@cs.drexel.edu>
Date: Tue Aug 4 15:20:38 2015 -0400
```

Revert "Adding curtains, bad path"

This reverts commit b26a94946c21248aad149557dd3d825848a06e76.

```
commit b26a94946c21248aad149557dd3d825848a06e76
Author: Kurt Schmidt <kschmidt@cs.drexel.edu>
Date: Mon Aug 3 02:13:06 2015 -0400
```

Adding curtains, bad path

```
commit 67fec740797b3b532d4a34100d4d7654ba3881e
Author: Kurt Schmidt <kschmidt@cs.drexel.edu>
Date: Mon Aug 3 01:45:59 2015 -0400
```

Building on a bad commit

...

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering
git reset
git checkout
git rm
git revert
Summary

Undoing Multiple Commits

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary
git help

First Look at
Internals
SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

You can roll back a sequence of commits. Consider the following history:

```
$ git log --oneline
```

```
c3317e7 Continuing bad path  
cf10f50 Started a bad path  
2e65010 2nd commit, good  
11ac734 Init
```

We'd like to get back to the 2nd commit.

Undoing Multiple Commits

Git - Single
Repository

Kurt Schmidt

Intro

First
Repository

git init
git add
git commit

Committing
Changes

help,
Summary

git help

First Look at
Internals

SHA-1 ID

Recovering

git reset
git checkout
git rm
git revert
Summary

```
$ git revert --no-commit 2e65..c3317
```

Or, if you've not detached HEAD:

```
$ git revert --no-commit 2e65..HEAD
```

- This apparently, rolls back *to* commit 2e65010
- The `--no-commit` saves us from committing each rollback
- So we must commit (just once)

```
$ git commit -m "Roll back to good state"
```

```
$ git log --oneline
```

```
92e61db Roll back to good state
c3317e7 Continuing bad path
cf10f50 Started a bad path
2e65010 2nd commit, good
11ac734 Init
```

Summary of Simple Commands, Recovery

Git - Single Repository

Kurt Schmidt

Intro

First Repository

`git init`
`git add`
`git commit`

Committing Changes

`help`,
Summary
`git help`

First Look at Internals
SHA-1 ID

Recovering

`git reset`
`git checkout`
`git rm`
`git revert`
Summary

```
git rm file
```

Remove a file

```
git add -u
```

Add changes to the index[†]

```
git reset
```

Reset index

```
git checkout file
```

Discard changes to *file*

```
git reset --hard
```

Discard *all* changes

```
git revert key
```

Revert repository to state of previous commit

[†]Doesn't see newly created files