

Notes on Linear Sorting

Geoffrey Matthews

May 2, 2018

Comparison sorts

- ▶ The only operation that may be used to gain information about a sequence is comparisons between pairs of elements.
- ▶ All sorts seen so far are comparison sorts:
 - ▶ insertion sort
 - ▶ merge sort
 - ▶ quicksort
 - ▶ heapsort


Lower bounds for comparison sorts

- ▶ $\Omega(n)$ to examine all the input
- ▶ All sorts seen so far are $\Omega(n \lg n)$
- ▶ We will show that all comparison sorts must be $\Omega(n \lg n)$

Decision tree


- ▶ Abstraction of any comparison sort
- ▶ Represents comparisons made by
 - ▶ a specific sorting algorithm
 - ▶ on inputs of a given size
- ▶ Abstracts away everything else: control and data movement.
- ▶ We're counting *only* comparisons.

Insertion sort on three elements



- ▶ Internal nodes labeled by comparisons (original positions).
- ▶ Leaf nodes labeled by permutation of order from original.
- ▶ Number of leaves $\geq n!$.

For any comparison sort



- ▶ 1 tree for each n
- ▶ View the tree as if the algorithm splits in two at each node.
- ▶ The tree models all possible execution traces.

What is the longest path from root to leaf?

- ▶ Depends on the algorithm.
- ▶ Insertion sort: $\Theta(n^2)$
- ▶ Merge sort: $\Theta(n \lg n)$

Lemma: any binary tree of height h has $\leq 2^h$ leaves.

- ▶ $\ell = \#$ of leaves
- ▶ $h = \text{height}$
- ▶ then $\ell \leq 2^h$

Proof by induction on h :

Base: $h = 0$. Tree is just one node, which is a leaf. $1 \leq 2^0$.

Inductive step: Assume true for $h - 1$. Extend tree with as many new leaves as possible. Each leaf becomes the parent of two new leaves.

$$\begin{aligned}\# \text{ of leaves for } h &= 2(\# \text{ of leaves for } h - 1) \\ &\leq 2(2^{h-1}) \\ &= 2^h\end{aligned}$$

Theorem: any decision tree that sorts n elements has height $\Omega(n \lg n)$

- ▶ $n! \leq \ell \leq 2^h$
- ▶ $h \geq \lg(n!)$
- ▶ Sterling's approximation: $n! > (n/e)^n$
- ▶ Therefore:

$$\begin{aligned} h &\geq \lg(n!) \\ &\geq \lg(n/e)^n \\ &= n \lg(n/e) \\ &= n \lg n - n \lg e \\ &= \Omega(n \lg n) \end{aligned}$$

Sorting in linear time

- ▶ Impossible with any comparison sort.
- ▶ **Counting sort**
- ▶ Key assumption: numbers to be sorted are integers in $\{0, \dots, k\}$.
- ▶ Key idea: count how many numbers are \leq each number.
- ▶ This tells you where it goes in the array.

Input: $A[1..n]$ where $A[j] \in \{0, \dots, k\}$

Output: $B[1..n]$, sorted.

Auxiliary storage: $C[0..k]$

Counting sort example

COUNTING-SORT(A, B, n, k)

```
1  let  $C[0..k]$  be a new array
2  for  $i = 0$  to  $k$ 
3       $C[i] = 0$ 
4  for  $j = 1$  to  $n$ 
5       $C[A[j]] = C[A[j]] + 1$ 
6  for  $i = 1$  to  $k$ 
7       $C[i] = C[i] + C[i - 1]$ 
8  for  $j = n$  downto 1
9       $B[C[A[j]]] = A[j]$ 
10      $C[A[j]] = C[A[j]] - 1$ 
```

A:

2 ₁	5 ₁	3 ₁	0 ₁	2 ₂	3 ₂	0 ₂	3 ₃
----------------	----------------	----------------	----------------	----------------	----------------	----------------	----------------

After **for** loop of lines 4-5:

C:

2	0	2	3	0	1
---	---	---	---	---	---

After **for** loop of lines 6-7:

C:

2	2	4	7	7	8
---	---	---	---	---	---

Counting sort example

COUNTING-SORT(A, B, n, k)

```
1  let  $C[0..k]$  be a new array
2  for  $i = 0$  to  $k$ 
3       $C[i] = 0$ 
4  for  $j = 1$  to  $n$ 
5       $C[A[j]] = C[A[j]] + 1$ 
6  for  $i = 1$  to  $k$ 
7       $C[i] = C[i] + C[i - 1]$ 
8  for  $j = n$  downto 1
9       $B[C[A[j]]] = A[j]$ 
10      $C[A[j]] = C[A[j]] - 1$ 
```

A:

2 ₁	5 ₁	3 ₁	0 ₁	2 ₂	3 ₂	0 ₂	3 ₃
----------------	----------------	----------------	----------------	----------------	----------------	----------------	----------------

C:

2	2	4	7	7	8
---	---	---	---	---	---

B:

						3 ₃	
	0 ₂					3 ₃	
	0 ₂				3 ₂	3 ₃	
	0 ₂		2 ₂		3 ₂	3 ₃	
0 ₁	0 ₂		2 ₂		3 ₂	3 ₃	
0 ₁	0 ₂		2 ₂	3 ₁	3 ₂	3 ₃	
0 ₁	0 ₂		2 ₂	3 ₁	3 ₂	3 ₃	5 ₁
0 ₁	0 ₂	2 ₁	2 ₂	3 ₁	3 ₂	3 ₃	5 ₁

Counting sort is **stable**:

- Keys with the same value appear in the same order in output as in input.

Counting sort analysis


COUNTING-SORT(A, B, n, k)

```
1  let  $C[0..k]$  be a new array
2  for  $i = 0$  to  $k$ 
3       $C[i] = 0$ 
4  for  $j = 1$  to  $n$ 
5       $C[A[j]] = C[A[j]] + 1$ 
6  for  $i = 1$  to  $k$ 
7       $C[i] = C[i] + C[i - 1]$ 
8  for  $j = n$  downto 1
9       $B[C[A[j]]] = A[j]$ 
10      $C[A[j]] = C[A[j]] - 1$ 
```

- ▶ $\Theta(n + k)$
 - ▶ which is $\Theta(n)$ if $k = O(n)$.
- ▶ How big a k is practical?
 - ▶ 64-bit values? Are you kidding?
 - ▶ 32-bit values? No.
 - ▶ 16-bit? Probably not.
 - ▶ 8-bit? Maybe, depending on n .
 - ▶ 4-bit? Unless n is really small.

- ▶ Counting sort will be used in radix sort.

Radix sort example




- ▶ Sort on each digit individually.
- ▶ Start with least significant digit.
- ▶ Must use a stable sort subroutine.
- ▶ Subroutine only works on a small range of numbers.

Radix sort

- ▶ IBM in early 20th century.
- ▶ Punch card sorting machines only sorted on one column.
- ▶ Humans would reload the cards and change the column.
- ▶ Human-machine cyborg algorithm!
- ▶ **Key idea:** Sort *least* significant digits first.

Example of a punch card



Radix sort

RADIX-SORT(A, d)

1 **for** $i = 1$ **to** d

2 use a stable sort to sort A on digit i

Radix sort correctness

- ▶ Induction on number of passes.
- ▶ Assume digits $1, \dots, i - 1$ are sorted.
- ▶ Show that a stable sort on i leaves $1, \dots, i - 1$ sorted:
 - ▶ If 2 digits in position i are different,
 - ▶ ordering by i is correct and positions $1, \dots, i - 1$ are irrelevant.
 - ▶ If 2 digits in position i are equal,
 - ▶ numbers are already sorted by inductive hypothesis. Stable sort leaves them that way.

Radix sort analysis

Assume we use counting sort on each digit.

- ▶ $\Theta(n + k)$ per digit
- ▶ d digits
- ▶ $\Theta(d(n + k))$ total
- ▶ If $k = O(n)$, time = $\Theta(dn)$.

Radix sort: How to break each key into digits?

- ▶ n words
- ▶ b bits/word
- ▶ Break into r -bit digits. $d = \lceil b/r \rceil$
- ▶ Use counting sort, $k = 2^r - 1$.
Example: 32-bit words, 8-bit digits.

$$b = 32$$

$$r = 8$$

$$d = \lceil 32/8 \rceil = 4$$

$$k = 2^8 - 1 = 255$$

- ▶ Time = $\Theta\left(\frac{b}{r}(n + 2^r)\right)$

How to choose r ?

- ▶ Time = $\Theta\left(\frac{b}{r}(n + 2^r)\right)$
- ▶ Balance b/r and $n + 2^r$.
- ▶ Choosing $r \approx \lg n$ gives

$$\Theta\left(\frac{b}{\lg n}(n + n)\right) = \Theta\left(\frac{bn}{\lg n}\right)$$

- ▶ If we choose $r < \lg n$ then $\frac{b}{r} > \frac{b}{\lg n}$ and $n + 2^r$ is still $\Theta(n)$.
- ▶ If we choose $r > \lg n$ then $n + 2^r$ term gets big.
- ▶ Sort 2^{16} 32-bit numbers:
Use $r = \lg 2^{16} = 16$ bits.
 $\lceil b/r \rceil = 2$ passes.

Compare radix to merge and quick

- ▶ 1 million (2^{20}) 32-bit integers.
- ▶ Radix sort: $\lceil 32/20 \rceil = 2$ passes.
 - ▶ Each radix “pass” is 2 passes:
 - one to take census
 - one to move data
- ▶ Merge/quick: $\lg n = 20$ passes.

How does radix sort violate the $\Omega(n \lg n)$ speed limit?

- ▶ Counting sort allows us to gain information about keys other than by directly comparing two keys.
- ▶ Directly comparing keys only gives one bit of information.
- ▶ Using keys as array indices gets far more information out of each key.
- ▶ Branching factor of the decision tree is k .
- ▶ Choosing one of k branches gets $\lceil \lg k \rceil$ bits of information.