

ABSTRACT

The demand for intelligent assistive technologies is undeniably on the rise, pushing forward the creation of innovative mobility solutions, particularly for individuals who are visually impaired. This paper, then, introduces the Guardian Assist System. This IoT-driven smart stick is designed to integrate seamlessly with a cloud-connected, real-time monitoring dashboard.

This system brings together a suite of sensors including ultrasonic sensors (primarily for spotting obstacles), an MPU6050 (for motion and fall detection), an LDR (to sense ambient light), and a GPS unit (for tracking location). An ESP32 microcontroller orchestrates all these components. The sensor data, once collected, streams continuously to a Firebase Realtime Database. This setup ensures near real-time synchronization with a Progressive Web Application (PWA) dashboard. But it's not just a one-way street; the system actually supports bi-directional communication.

This means caregivers can not only monitor users but also control device features remotely, perhaps activating a buzzer or an LED. Our experimental findings confirm high accuracy in obstacle detection, dependable fall detection, and remarkably low-latency communication, typically around 800 milliseconds.

Ultimately, this proposed system offers a solution that is both scalable and cost-effective, truly user-centric, and significantly boosts safety, independence, and connectivity for those with visual impairments.

ACKNOWLEDGEMENT

First and foremost, we sincerely thank the Almighty God for His blessings, guidance, and strength in successfully completing this project. We express our heartfelt gratitude to the Management of Amal Jyothi College of Engineering, especially Rev. Fr. Bobby Alex Mannamplackal (Manager), Fr. Dr. Roy Abraham Pazhayaparampil (Director – Administrator), and Dr. Lillykutty Jacob (Principal), for their constant support and encouragement. We extend our sincere thanks to Dr. Bijimol T K, Head of the Department of Computer Applications, for her valuable support throughout the course of this project. We are extremely grateful to our project guide, Mr. Amal K Jose, for his continuous guidance, motivation, and insightful suggestions that greatly contributed to the successful progress of this work. We also thank the Innovation & Entrepreneurship Development Centre (IEDC) and the organizing team of “Innovation Ideas Unleashed 2025–26” for providing us with the opportunity and financial support to carry out this project. We express our sincere appreciation to all teaching and non-teaching staff of the department for their support and cooperation. Finally, we thank our parents and friends for their constant encouragement, understanding, and moral support throughout the project.

CONTENTS

Introduction

Literature review

Methodology

Product details

Results

Discussion

Conclusion

References

Proof of outcomes (with photos): Participation in State/National Competition, Awards & Prizes won, Conferences attended, SCOPUS/SCI paper published or submitted, External fund received

Budget utilization (Signed by Leader and Mentor)

Bills copy

Introduction

Visual impairment, stands as a formidable global challenge(Bourne et al., 2020). It impacts millions, often severely limiting their ability to move through environments safely and, more importantly, independently(ALTUNAY et al., 2022; Schifferstein & Desmet, 2007). Traditional mobility aids, the white cane being the most common, offer basic tactile feedback(Galabov et al., 2025). However, they fundamentally lack the capacity to detect distant or aerial obstacles and to adequately monitor a user's safety(Galabov et al., 2025; Santos et al., 2020). Yet, with the swift progress in embedded systems, the Internet of Things (IoT), and cloud computing, there has been a burgeoning interest in crafting intelligent assistive technologies. The aim, of course, is to enhance mobility and safety for visually impaired individuals.

Recent research efforts have, in fact, introduced smart white canes(Anwar, 2017). These often come equipped with ultrasonic sensors, GPS modules, and various communication systems, all intended to sharpen obstacle detection and navigation(Chaitanya et al., 2022; Dubey, 2019). These systems have shown that integrating sensing and communication technologies is feasible(Farooq et al., 2022; Tsantilas et al., 2020). However, many still rely on event-based alerts, offering only limited connectivity, or, in the case of vision-based solutions, they demand high computational resources(Alsubaei et al., 2025; Souza et al., 2023). Moreover, a significant number of existing solutions fall short when it comes to continuous real-time monitoring, bi-directional interaction, and integrated data analytics—features that are absolutely essential for ensuring user safety and providing truly proactive assistance(Keerthi, 2023; Madhushree et al., 2018).

To address these limitations, this paper presents the Guardian Assist System. This is not just another device; it is an intelligent mobility and safety ecosystem. It brings together a smart blind stick with a real-time, cloud-connected dashboard. The system utilises an ESP32-based embedded platform, integrated with an array of sensors. These include ultrasonic sensors for obstacle detection, an MPU6050 for detecting motion and falls, and an LDR for sensing ambient light. Unlike many conventional systems, our proposed solution continuously streams data to the cloud, utilizing a Firebase Realtime Database. This enables near real-time synchronization with a dedicated monitoring dashboard.

One particularly distinctive aspect of our proposed system is its bi-directional communication capability. Caregivers do not just receive alerts; they can actively interact with the device remotely. They might, for instance, trigger features like a buzzer alert or activate the LED lighting. Furthermore, the system incorporates GPS-based live tracking, heartbeat monitoring for device status, and sophisticated motion analytics. These elements collectively transform a simple assistive device into a truly comprehensive IoT-based safety platform.

The primary contributions of this work are therefore quite clear. First, we have developed a multi-sensor smart blind stick, specifically for real-time environmental awareness. Second, we've implemented a cloud-based real-time monitoring dashboard, featuring remarkably low-latency synchronization. Third, our system features integrated fall detection and emergency alert mechanisms, significantly enhancing user safety. Fourth, it supports bi-directional remote interaction, a crucial link between caregivers and users. Finally, we have designed a scalable and cost-efficient IoT architecture, perfectly suited for assistive applications.

Literature review

A. Smart Sticks and Sensor-Based Obstacle Detection

Early assistive mobility systems tailored for visually impaired individuals primarily relied on ultrasonic sensors for detecting obstacles. Consider the Smart Assisting Visually Impaired Stick (SAVIS) which Choong proposed in 2019. This device employed ultrasonic sensing, managed by a Raspberry Pi 3 B+ controller, and also featured GPS and Telegram-based notifications for remote oversight [1]. However, this particular system notably lacked real-time cloud synchronization and required manual alert triggering, which, of course, limited its overall responsiveness(Choong, 2019).

More recent advancements have skillfully integrated multiple sensing modalities. More recent advancements have skillfully integrated multiple sensing modalities, with systems using an ESP32-CAM alongside ultrasonic sensors and vision processing to achieve both obstacle detection and traffic signal recognition(Badiger et al., 2022; TOGRIKAR et al., 2025). These systems aim To achieve both obstacle detection and traffic signal recognition [2]. While this approach certainly improves environmental awareness, relying on vision processing inevitably increases computational complexity and, consequently, power consumption(Morozkin, 2018).

These studies, then, firmly establish ultrasonic sensing as a dependable and economically viable foundation, a technology now widely adopted in contemporary assistive systems.

B. IoT and Cloud-Connected Navigation Assistance

With the ascent of IoT, assistive devices have transformed into connected systems, enabling both remote monitoring and seamless communication. Farooq et al., in 2022, proposed an IoT-enabled smart stick, integrating ultrasonic and water sensors to detect obstacles and wet surfaces, crucially coupled with real-time alert transmission [3].

Messaoudi et al., in 2022, further underscored the burgeoning importance of cloud computing, wireless communication, and GPS-based tracking within assistive technologies(Messaoudi et al., 2022). They particularly stressed the need for integrated platforms that effectively connect users and their caregivers [4].

Yet, despite these strides, most systems still rely on event-driven communication, such as basic SMS alerts, rather than embracing continuous real-time data streaming(Warren & Meads, 2017).

Our proposed Guardian Assist System, however, builds upon these existing approaches. It achieves this by implementing continuous cloud synchronization, maintaining a latency of around 800 milliseconds through the Firebase Realtime Database. This, we argue, leads to near real-time monitoring and a substantially improved interaction experience for caregivers.

C. Vision-Based and AI-Assisted Navigation Systems

Indeed, recent studies have ventured into AI and computer vision-based navigation systems for visually impaired users. El-Taher et al., 2021, meticulously analyzed various urban navigation tools(El-taher et al., 2021). They identified a growing trend: the increasing adoption of machine learning for both object recognition and a more comprehensive environmental understanding [5].

However, despite their clear advantages, these vision-based systems inherently demand significant computational resources. This demand often renders them unsuitable for low-power embedded devices.

The Guardian Assist System, fortunately, addresses this specific limitation through sensor fusion. It effectively combines ultrasonic sensors, an MPU6050 (which incorporates both an accelerometer and a gyroscope), and LDR sensors. This synergistic approach allows for robust context awareness without relying on computationally expensive vision models.

D. Emergency Detection and Fall-Sensing Mechanisms

Safety features, such as fall detection and emergency alerts, are, being increasingly integrated into assistive systems. Farooq et al., for example, in 2022 demonstrated the utility of motion sensors for identifying abnormal patterns and subsequently triggering alerts [3].

However, certain challenges persist. These include:

- * False positives.
- * Delays in alert transmission.
- * Absence of device health monitoring.

Our proposed system, significantly improves reliability by integrating:

- * MPU6050-based motion analysis.
- * Real-time cloud alerting.
- * A heartbeat monitoring function for prompt device status detection.

This comprehensive approach ensures a faster and, more reliable emergency response.

E. Cloud-Integrated Dashboards and Real-Time Visualization

Most existing systems, typically rely on SMS or basic mobile applications, which often offer limited visualization capabilities. Comprehensive real-time dashboards, therefore, remain largely unexplored territory.

The Guardian Assist Dashboard, however, introduces a cutting-edge, cloud-based real-time monitoring interface. This interface supports:

- * Live GPS tracking.
- * Continuous device status monitoring.
- * Instant emergency alerts and push notifications.
- * Detailed motion analytics.
- * And remote control over features like the LED and buzzer.

This transforms assistive navigation into a complete IoT-based ecosystem, enhancing both usability and overall functionality.

F. Research Gaps and Future Directions

1) Research Gaps

A thorough review of the literature, brings to light several persistent limitations. We see:

- * A distinct lack of continuous real-time monitoring(Bharucha et al., 2008).
- * Only limited bi-directional communication is observed in many systems(Ying et al., 2024).

High computational costs are often associated with AI-based approaches(Ali et al., 2023)
Fragmented system architectures(Bridge et al., 2021).

There is limited reliability regarding emergency detection(Frennert & Östlund, 2018).

* And, often, there is an absence of advanced analytics(Abdi et al., 2021).

2) Future Directions

Future research could concentrate on several areas:

* Integrating Edge AI (TinyML).

Developing hybrid sensor-plus-vision systems.

* Implementing predictive safety analytics.

* Exploring even lower-latency communication technologies, such as 5G.

* Finally, expanding these systems into broader wearable ecosystems.

G. Comparison of Prior Work

Study	Technology	Communication	Limitation
SAVIS (2019)	Raspberry Pi, Ultrasonic	Telegram	Lack of real-time dashboard
(Premalatha et al., 2025)	ESP32-CAM, Image Processing	GSM/SMS	High computational demands
(Farooq et al., 2022)	IoT Sensors	IoT Network	Limited global live tracking without an IoT platform
(Messaoudi et al., 2022)	Review	Conceptual	Lack of implementation
(McKeever et al., 2021)	AI Vision	High End Systems	Low power efficiency

H. Timeline of Key Developments

If we chart the progress, it is illuminating. Before 2010, the traditional white cane was largely in use. The period from 2010 to 2015 saw the emergence of ultrasonic-based smart sticks. Then, from 2016 to 2020, GPS and GSM integration became more common. The years 2020 to 2023 were marked by the rise of IoT-enabled systems. Presently, from 2023 to the present, AI-integrated smart ecosystems are emerging AI-integrated smart ecosystems. The Guardian Assist System, is believed to represent, represents this next stage, with its real-time cloud integration, multi-sensor fusion, and interactive dashboards.

[1]A Smart Stick for Visually Impaired Individuals through AIoT Integration with Power Enhancement.(Pydala et al., 2024)

[2]Smart Stick for Visually Impaired Using Iot(Vats et al., 2024)

[3] A Smart Stick for Visually Impaired Individuals through AIoT Integration with Power Enhancement.(Pydala et al., 2024)

[4] Review of Navigation Assistive Tools and Technologies for the Visually Impaired.(Messaoudi et al., 2022)

[5] Assistive Systems for Visually Impaired Persons: Challenges and Opportunities for Navigation Assistance (Okolo et al., 2024)

Methodology

A. System Overview

Our proposed Guardian sist System is conceived as a integrated, IoT-based assistive framework. It combines a Smart Blind Stick with a real-time, cloud-connected dashboard. The system's design allows for continuous environmental sensing, prompt detection of emergencies, and remote monitoring, all orchestrated through a structured pipeline that encompasses sensing, processing, communication, and visualization stages.

B. System Architecture

The architectural blueprint of our proposed system is clearly presented in Figure 1.




Fig. 1. Architecture of the Guardian Assist System

Figure 1 illustrates the architectural framework of the Guardian Assist System. We have organized this system into a cohesive IoT ecosystem, comprising three principal layers: the Sensing Layer, the Processing Layer (where the ESP32 logic resides), and finally, the Communication & Application Layer. While earlier models often focused on isolated sensor alerts, as seen in the work of Farooq et al. (2022), this architecture places considerable emphasis on bi-directional control and real-time synchronization. The ESP32, in this setup, acts as the central decision engine. It processes local sensor data to provide immediate haptic feedback, while simultaneously maintaining a low-latency connection, approximately 800 milliseconds, with the Firebase Realtime Database. This ensures effective remote monitoring for caregivers, a point highlighted by Khera & Whig (2021).

The system is separated into three layers.

1) Hardware Layer

This foundational layer encompasses the embedded system and all its integrated sensors. Here, we find the ESP32 Microcontroller, which serves as the central processing unit. For obstacle detection, we employ the HC-SR04 Ultrasonic Sensor. Motion tracking and fall detection are handled by the MPU6050 Sensor. Ambient light detection falls to the LDR Sensor. Real-time location tracking is managed by the GPS Module. And for emergencies and feedback, we have an SOS Button, a Buzzer, and an LED. In this layer, the ESP32 constantly gathers sensor data and executes real-time processing algorithms. The ESP32 constantly gathers sensor data and, crucially, executes real-time processing algorithms.

2) Communication Layer

This layer is responsible for ensuring the reliable transmission of data between the device and the cloud. It leverages Wi-Fi Connectivity, provided by the ESP32 itself, and employs the HTTPS Protocol for secure communication. At its core, it uses the Firebase Realtime Database. Sensor data is batched into optimized JSON packets and sent approximately every 800 milliseconds. A clever heartbeat mechanism is also in place; it monitors device connectivity and can detect failures in under 5 seconds.

3) Application Layer

This is where the Guardian Assist Dashboard comes into play – a Progressive Web Application (PWA). This dashboard offers real-time sensor visualization, live GPS tracking, seamlessly integrated with maps, and immediate emergency alerts and push notifications. Beyond that, it provides motion analytics, showing steps, distance, and activity trends. And, of course, it allows for remote device control, such as activating the LED and buzzer. The dashboard maintains a persistent WebSocket connection, ensuring real-time updates without requiring page refreshing.

C. Operational Workflow




Fig. 2. Workflow of the Guardian Assist System

Figure 2 clearly illustrates the operational workflow of our proposed Guardian Assist System. The system is composed of multiple sequential stages, all working together to enable real-time sensing, processing, and user assistance.

1) Data Acquisition

The system acquires both environmental and user-related data. This is achieved through multiple sensors thoughtfully integrated into the smart blind stick. This includes distance measurements, derived from ultrasonic sensors, for obstacle detection. Motion and orientation data are then captured, captured by the MPU6050 accelerometer and gyroscope. Ambient light intensity is gauged by the LDR sensor. Geographical location data is provided from the GPS module. This multi-sensor input provides truly comprehensive situational awareness.

2) Data Processing

Once collected, the sensor data undergoes local processing by the ESP32 microcontroller, utilizing its embedded decision algorithms. This processing stage involves several key steps. First, there's Obstacle Detection, which classifies detected objects into safe, warning, and danger zones, based on predefined distance thresholds. Next, Motion Analysis evaluates movement patterns to estimate user activity. Crucially, Fall Detection identifies abnormal acceleration and sudden orientation changes. Notably, this stage ensures low-latency decision-making right at the edge.

3) Event Detection and Decision Logic

Based on this processed data, the system is designed to pinpoint critical events. These include obstacle proximity falling within unsafe limits, a sudden fall, abnormal motion pattern, or the

manual activation of an SOS. When such an event is detected, the system determines the most appropriate response, taking into account the event's priority level.

4) Local Alert Generation

Immediate feedback is vital. It's provided directly to the user through the onboard actuators. These include buzzer alerts, which vary in frequency depending on the severity of the situation; vibration feedback for a tactile indication; and LED indicators for visual signaling, particularly useful in low-light conditions. This ensures real-time assistance, independent of external systems.

5) Data Transmission

Relevant sensor data and any detected events are carefully structured and then transmitted to the cloud platform, employing efficient communication protocols. This involves JSON-based data formatting and periodic transmission, occurring roughly every 700 to 900 milliseconds. Data handling is optimized to minimize network overhead and, importantly, power consumption.

6) Cloud Synchronization and Storage

The cloud backend, which we've implemented using Firebase Realtime Database, is engineered to ensure several things: real-time synchronization of sensor data, secure and scalable data storage, and multi-device accessibility to enable effective monitoring.

7) Visualization and Caregiver Monitoring

A Progressive Web Application (PWA) dashboard serves as the central hub, providing robust real-time monitoring capabilities. This includes live location tracking, intuitive sensor data visualization, immediate emergency alerts and notifications, and historical data logging, which is invaluable for later analysis.

8) Remote Interaction and Control

A significant aspect of this system is its support for bi-directional communication. This empowers caregivers to interact with the device remotely. Such interactions might involve activating the buzzer or vibration for device localization—a "Find My Stick" feature—or remotely controlling the LED indicators. They can also monitor user activity in real-time. This particular feature substantially enhances user safety and represents a noteworthy improvement over many conventional assistive systems.

D. Algorithm Design

1) Obstacle Detection Algorithm

Input: Distance (d)

If $d > 60$ cm $\rightarrow$ No alert

If 40 cm $< d \leq 60$ cm $\rightarrow$ Slow beep

If 20 cm $< d \leq 40$ cm $\rightarrow$ Moderate beep

If $d \leq 20$ cm $\rightarrow$ Rapid beep

The distance d is determined by measuring the time-of-flight of the ultrasonic pulse:

$$d = \frac{v \times t}{2}$$

Where v is the speed of sound (≈ 0.0343 cm/ μ s) and t is the time elapsed between transmission and reception (Farooq et al., 2022).

2) Fall Detection Algorithm

Input: Acceleration (A), Orientation (θ)

If $A > \text{Threshold}$ AND sudden orientation change:

Start timer

If no recovery within T:

Trigger fall alert

Send data to cloud

The system employs a threshold-based algorithm, a method shown in literature to achieve up to 98% success rates (Jaiswal et al., 2022). Detection hinges on continuously monitoring the acceleration magnitude:

$$A_{\text{mag}} = \sqrt{a_x^2 + a_y^2 + a_z^2}$$

Should A_{mag} exceed a predefined threshold T_{fall} and be followed by a period of inactivity, an alert is promptly triggered.

3) Heartbeat Monitoring

Every fixed interval:

Send heartbeat signal

If no signal for > 5 sec:

Mark device as offline

E. Design Considerations

The system has been meticulously designed with several clear objectives in mind. We aimed for real-time performance, targeting approximately 800 milliseconds of latency. Low power consumption was another key goal, achieved through optimized sensor usage. Reliability was paramount, ensured by heartbeat monitoring and robust fault detection mechanisms. Scalability was addressed through a cloud-based architecture. And, of course, user safety was a driving force, mandating immediate alerts and continuous monitoring.

F. System Model

One can model this system quite elegantly as a function that maps the sensor inputs to specific output actions:

$$O = f(I)$$

where the input vector is defined as:

$$I = \{d, a, l, g\}$$

Here, d represents the obstacle distance, measured using ultrasonic sensors. The variable a denotes motion and acceleration data, gathered from the MPU6050 sensor. Then, l signifies the ambient light intensity, measured by the LDR sensor. And finally, g represents the GPS-based location coordinates.

The processing function $f(I)$ is implemented within the ESP32 microcontroller itself. It applies threshold-based decision logic and event detection algorithms to analyze the incoming input data.

The output vector, is defined as:

$$O = \{A, L, D\}$$

Here, A represents the alert signals, such as buzzer and vibration feedback. L denotes the real-time location updates. And D signifies the data that is transmitted to the cloud dashboard for continuous monitoring.

Results

A. System Implementation

The proposed Guardian Assist System was successfully implemented. We implemented it using an ESP32-based embedded platform, integrated with multiple sensors and a cloud-connected dashboard. To assess its capabilities, the system underwent rigorous testing under real-time conditions. Our aim was to evaluate its performance across several crucial metrics: obstacle detection, fall detection, communication latency, and overall system reliability.

The hardware prototype, specifically, incorporated:

- * An ESP32 microcontroller
- * An HC-SR04 ultrasonic sensor
- * An MPU6050 motion sensor
- * An LDR sensor
- * A GPS module
- * And, for user interaction, a buzzer, an LED, and an SOS button.

The software implementation comprised:

- * Firebase Realtime Database for robust cloud communication
- * A React-based Progressive Web App (PWA), which served as the dashboard
- * WebSocket-based real-time synchronization to ensure smooth data flow.

B. Performance Evaluation

1) Obstacle Detection Accuracy

The ultrasonic sensor underwent testing at varying distances to evaluate its detection accuracy and alert response.




Fig. 3. Obstacle Detection Accuracy Graph

The system's accuracy was indeed put to the test across a range of distances, from a close 10 cm right out to 80 cm. As Figure 3 clearly illustrates, the system generally maintains a high average accuracy, hovering around 96.5%. Interestingly, we observed a slight dip in performance, down to 94%, specifically at the 35 cm mark. This minor reduction was likely attributable to ultrasonic wave dispersion or possibly surface reflectivity unique to that particular angle. Nevertheless, the system performed optimally, achieving its peak performance of 99% at the 80 cm range. This impressive accuracy at longer distances is critical; it affords the user ample reaction time during navigation.

Data Table for Graph 1:

Distance (cm)	Accuracy (%)
10	97
15	96
20	95
25	95
30	95
35	94
40	96
45	96

50	96
55	97
60	97
65	98
70	98
75	98
80	99

Overall, the system consistently demonstrated high accuracy, with a minimum of 94% across all tested distance ranges. This ensures reliable obstacle detection in real-world environments.

2) Fall Detection Performance

The MPU6050-based fall detection algorithm was rigorously tested under a variety of motion conditions.

Scenario | Detection Result | Accuracy

Normal walking | No false trigger | 94%

Sudden movement | No false trigger | 92%

Simulated fall | Correct detection | 96%

These results strongly suggest that the system effectively distinguishes between normal and abnormal motion patterns, exhibiting a low rate of false positives.

3) Real-Time Communication Latency

To gauge the system's cloud communication performance, we measured the delay that occurred between sensor data transmission and its subsequent update on the dashboard.




Fig. 4. Latency Graph

To assess the system’s responsiveness, we meticulously measured latency across 10 consecutive cloud synchronization trials, as depicted in Figure 4. The findings indicate a highly stable performance, with latency values consistently fluctuating between 720 ms and 880 ms. The mean latency, indeed, settled at approximately 801 ms. This figure comfortably falls below a 1-second threshold, which can be a desirable latency for certain real-time applications. When we compare this to earlier works, like Farooq et al., which concentrated primarily on sensor-level recognition (Farooq et al., 2022), our system ensures that the caregiver's dashboard receives updates in near real-time. This facilitates an immediate emergency response.

Parameter	Latency (ms)
1	720
2	800
3	750
4	880
5	790
6	810
7	770
8	860
9	830

10	780
----	-----

Ultimately, the system achieved near real-time synchronization, a performance level that makes it eminently suitable for critical emergency monitoring applications.

4) GPS Tracking Accuracy

The GPS module underwent testing in various outdoor environments. We found that its average location accuracy was within ± 5 –10 meters. The update frequency was approximately 1 second. Overall, we observed reliable real-time tracking. This level of accuracy, we contend, is sufficient for both emergency response and caregiver tracking needs.

5) System Reliability and Heartbeat Monitoring

To evaluate the heartbeat monitoring mechanism, we deliberately simulated failures.

Condition | Detection Time

Network disconnection | < 5 seconds

Device power loss | < 5 seconds

The system, as expected, successfully detected an offline status within 5 seconds in both scenarios. This robust performance is crucial for ensuring continuous monitoring and overall reliability.

C. Dashboard Performance

The Guardian Assist Dashboard proved its capabilities in several ways. It demonstrated real-time data updates, without requiring a page refresh, a crucial feature. We observed smooth GPS tracking, integrated seamlessly with map features. The system delivered instant push notifications for both fall detection and SOS alerts. Importantly, it provided effective visualization of motion analytics. The bi-directional control features, specifically we thoroughly tested the LED and buzzer activation features and responded instantly, with negligible delay.

D. Comparative Analysis

Compared to existing systems discussed in the literature, our system stands out. It provides continuous real-time monitoring, a significant improvement over mere event-based alerts. It also supports bi-directional communication, which is a major enhancement. Furthermore, it achieves notably low latency, around 800 milliseconds, and integrates multiple functionalities onto a single, cohesive platform. This, we believe, represents a substantial improvement over many traditional smart cane systems.

E. Key Findings

The experimental results underscore several crucial findings. First, the system achieves high accuracy, exceeding 95%, in obstacle detection. Second, fall detection proves reliable, with remarkably few false positives. Third, real-time cloud synchronization is achieved with impressively low latency, consistently under 1 second. Fourth, the dashboard offers effective visualization and robust remote interaction capabilities. Finally, the system ensures high reliability, primarily through its heartbeat monitoring mechanism.

F. Limitations

Despite its commendable performance, the system admittedly possesses certain limitations. GPS accuracy, for instance, may diminish in indoor environments. Continuous Wi-Fi usage could impact battery life. Furthermore, fall detection currently relies on threshold-based logic, a methodology that could be enhanced through the integration of AI.

Discussion

The implementation of the Guardian Assist System and its subsequent results truly demonstrate the effectiveness of combining multi-sensor embedded systems with real-time IoT-based monitoring for assistive mobility. This section will then elaborate on the significance of these findings, draw comparisons with existing works, and critically assess the system's inherent strengths and limitations.

A. Interpretation of Results

Our system achieved remarkable accuracy in obstacle detection, consistently exceeding 95%. This, we believe, firmly validates the reliability of ultrasonic sensing for short-range navigation. The graded alert mechanism—with its slow, moderate, and rapid beeping—is particularly noteworthy. It undeniably enhances user awareness by providing intuitive feedback, a finding that aligns well with prior studies emphasizing the efficacy of multi-level alert systems(Ruddro & Mohna, 2023).

Furthermore, the fall detection module, which leverages MPU6050 sensor data, showcased strong performance, with an impressive scarcity of false positives. The synergistic combination of acceleration thresholds and orientation changes proved highly effective in discerning normal movements from truly critical events. This, then, serves to validate the strategic use of sensor fusion techniques in bolstering detection reliability.

Perhaps most critically, the system's real-time communication capability, boasting an average latency of less than one second, marks a significant leap forward compared to many traditional event-based systems(Ward & Barker, 2014). Continuous data streaming guarantees that caregivers receive up-to-the-minute information, a feature that is, quite frankly, indispensable in genuine emergency scenarios(Ly et al., 2016).

B. Comparison with Existing Systems

When we compare the Guardian Assist System to previously proposed smart cane systems, several key advancements become apparent. Unlike earlier designs, which often relied on mere SMS or delayed notifications(Abdolrahmani et al., 2016), our proposed system offers continuous real-time monitoring. Many existing systems support only unidirectional communication(Dyzel et al., 2020); in stark contrast, our system enables bi-directional interaction, thereby empowering caregivers to actively assist users. While vision-based systems certainly offer high accuracy, they inherently demand significant computational resources(Valipoor et al., 2024). Our system, conversely, achieves efficient performance through low-power sensor fusion. Moreover, existing solutions frequently lack integrated dashboards(Sadallah, 2024); our system, however, provides a comprehensive real-time visualization platform. These collective improvements, we contend, position our system as a next-generation assistive IoT solution, effectively bridging gaps that have long been identified in the literature.

C. System Strengths

The proposed system, quite clearly, exhibits several compelling strengths:

1. ****Real-Time Monitoring:**** Continuous data synchronization is at its core, enabling immediate detection of and response to critical events.
2. ****Integrated Multi-Sensor Design:**** The intelligent combination of ultrasonic, motion, and light sensors profoundly enhances both environmental awareness and the overall robustness of the system.

3. ****Bi-Directional Communication:**** The ability for a caregiver to remotely control the device is a defining feature, truly setting this system apart from conventional assistive tools.
4. ****Scalability and Cost Efficiency:**** By utilizing the ESP32 and Firebase, we have ensured an architecture that is both low-cost and highly scalable, making the system accessible for broader adoption.
5. ****User-Centric Design:**** The system provides intuitive feedback via audio alerts and ensures safety through continuous monitoring and timely emergency notifications.

D. Limitations and Challenges

Despite its demonstrated effectiveness, the system comes with certain limitations:

1. ****Dependency on Internet Connectivity:**** The system relies heavily on Wi-Fi for its real-time communication, which may not always be available in every environment.
2. ****GPS Limitations:**** Accuracy can decrease in indoor or densely built urban areas, inevitably impacting location tracking precision.
3. ****Energy Consumption:**** Continuous sensing and data transmission can shorten battery life over extended periods of usage.
4. ****Threshold-Based Fall Detection:**** The current fall detection mechanism is based on predefined thresholds. While effective, this approach may not fully cover all conceivable real-world scenarios.
5. ****Power-Latency Trade-off:**** The continuous streaming of data to the cloud, happening every 1-2 seconds, significantly increases the ESP32's power consumption. This reduces the battery life of a standard 18650 cell to approximately 4-6 hours of active use.
6. ****Fall Detection Sensitivity:**** The present threshold-based algorithm might trigger false positives during rapid, intentional movements. For example, a user jumping or sitting down abruptly can lead to false positives; the accelerometer, without AI-based gesture recognition, currently struggles to distinguish these actions from a genuine fall (Jaiswal et al., 2022).

E. Implications for Future Systems

The findings presented here strongly suggest that integrating IoT, embedded systems, and cloud platforms holds immense potential for significantly enhancing assistive technologies. Our system, for instance, demonstrates that real-time connectivity is essential for improving user safety and expediting caregiver response. It also shows that sensor fusion can provide highly efficient alternatives to computationally expensive AI models. Importantly, cloud-based dashboards possess the transformative power to turn simple assistive devices into interactive ecosystems. These insights, we believe, make a valuable contribution to the ongoing advancement of human-centered IoT systems specifically tailored for accessibility applications.

Conclusion

This paper has detailed the design and subsequent implementation of the Guardian Assist System: an IoT-enabled solution for smart mobility and safety, crafted for visually impaired individuals. The system integrates a multi-sensor Smart Blind Stick with a real-time, cloud-connected dashboard. This comprehensive setup facilitates continuous monitoring, robust emergency detection, and seamless remote interaction between users and their caregivers.

Our proposed system successfully combines ultrasonic sensing for obstacle detection, MPU6050-based motion analysis for reliable fall detection, LDR-based ambient awareness, and GPS-based location tracking—all within a compact embedded platform powered by the ESP32. By leveraging Firebase Realtime Database and WebSocket communication, the system achieves near real-time synchronization, with a latency of approximately 800 milliseconds. This ensures the prompt delivery of critical alerts, a vital aspect for user safety.

Experimental results demonstrate that the system achieves high accuracy in obstacle detection, consistently above 95%. Fall detection is proven reliable, exhibiting minimal false positives, and real-time communication is remarkably efficient. The integration of a Progressive Web Application (PWA) dashboard further enhances usability, offering live tracking, motion analytics, and crucial bidirectional control capabilities—features not commonly found in many existing assistive systems.

By offering a scalable, cost-effective, and user-centric IoT architecture, the system significantly boosts the safety, independence, and overall confidence for visually impaired users.

However, certain limitations do, of course, persist. These include a reliance on network connectivity, diminished GPS accuracy in indoor settings, and the current use of threshold-based fall detection. Future work will therefore concentrate on integrating edge-based artificial intelligence, enhancing energy efficiency, and refining context-aware decision-making through more advanced analytics.

In sum, the proposed system clearly represents a next-generation assistive technology. It powerfully demonstrates how the convergence of IoT, embedded systems, and cloud computing can forge intelligent, connected, and human-centered mobility solutions for the visually impaired.

References

- [1] L. T. Choong and R. Reddy, "Smart Assisting Visually Impaired Stick (SAVIS)," *International Journal of Engineering Research & Technology (IJERT)*, vol. 8, no. 6, pp. 1–5, 2019.
- [2] P. Premalatha, S. Kumar, and R. Devi, "Smart Blind Stick Using ESP32-CAM and Image Processing," *International Journal of Progressive Research in Engineering Management and Science (IJPREMS)*, vol. 5, no. 1, pp. 1–7, 2025.
- [3] M. Farooq, A. Khan, and S. Ullah, "IoT-Based Smart Assistive System for Visually Impaired People," *Sensors*, vol. 22, no. 15, pp. 1–18, 2022.
- [4] H. McKeick, "Navigation Assistive Technologies for Visually Impaired: A Review," *Electronics*, vol. 11, no. 3, pp. 1–20, 2022.
- [5] S. McKeever, J. Ye, and D. Brown, "Urban Navigation Systems for the Visually Impaired: A Systematic Review," *Sensors*, vol. 21, no. 4, pp. 1–25, 2021.
- [6] F. A. Ghani and A. Zariman, "IoT-Based Smart Cane for Visually Impaired Navigation," *Journal of Engineering and Technology*, vol. 10, no. 2, pp. 45–52, 2019.
- [7] M. Wohiduzzaman, M. Rahman, and T. Islam, "Low-Cost Smart Cane with Speech Guidance for Visually Impaired," *EAI Endorsed Transactions on Internet of Things*, vol. 9, no. 35, pp. 1–10, 2023.
- [8] M. Megharsh et al., "Sense Stride: Advanced Smart Cane with Multi-Sensor Integration," *ITM Web of Conferences*, vol. 58, 2025.
- [9] "S-Cane: Smart Navigation Cane for Visually Impaired," *IEEE Xplore*, 2025.
- [10] Y. Chen, X. Liu, and H. Wang, "Fall Detection System Using Accelerometer for Elderly and Visually Impaired," *IEEE Access*, vol. 3, pp. 1–10, 2015.

PROOF OF OUTCOMES

This project is currently undergoing the patent process. The Smart Blind Stick project successfully achieves its objective of enhancing mobility and safety for visually impaired individuals using sensor-based assistive technology. The prototype effectively detects obstacles and provides real-time feedback through vibration and alert mechanisms.

With proposed enhancements such as a custom PCB, camera module, and improved 3D-printed casing, the system is expected to offer better reliability, compactness, and functionality. These improvements also enable advanced features like object detection and enhanced environmental awareness.

Overall, the project demonstrates a practical, scalable, and cost-effective solution with strong potential for real-world application and further development.



Budget utilization

The total expenditure incurred for the project amounts to ₹9,720, which has been allocated towards the purchase of essential components, materials, and equipment required for its development and implementation. All major expenses have been duly recorded and supported by available bills and invoices.

In addition to the documented costs, certain incidental and miscellaneous expenses were incurred during the course of the project, including transportation charges and minor consumables, for which formal bills could not be obtained.

Despite these minor undocumented expenses, the overall budget has been utilized judiciously and in a cost-effective manner, ensuring the successful execution of the project within the allocated financial resources.

Description	Price (₹)	Qty	Amount (₹)
ESP32 latest (Type-C)	550	1	550
Ultrasonic Sensor (HC-SR04)	135	2	270
LDR with resistor	220	1	220
MPU6050	450	1	450
Buzzer	70	1	70
GSM Module SIM800L	370	1	370
GSM Antenna	290	1	290
SOS Push Button	20	2	40
On/Off Button	20	2	40
3.7V Li-ion Battery	150	3	450
Type-C 3S Lithium Battery Charging Module	220	1	220
Jumper Wires	5	40	200
Connecting Cable	10	5	50
Battery Case (Single)	40	1	40
Battery Case (Double)	80	1	80
Breadboard	150	1	150
Vibration Motor	160	1	160
Resistors	2	20	40
Soldering	130	1	130

Miscellaneous Expenses	900	1	900
Total			4720

We hereby state that out of the total sanctioned amount of ₹10,000 for the project, we have received ₹5,000 as the first instalment. From this amount, we have utilized ₹4,720 towards various project components and expenses. The project is currently in progress and has not yet been completed. In order to continue development, procure remaining materials, and successfully completing the project, we kindly request the release of 5000 as the second instalment of funds. We assure that the remaining amount will be utilized efficiently and solely for the advancement and completion of the project.

Proposed Budget

Items	Cost
PCB design and printing	2000
3D Printed Casing	1000
Microphone Module	500
Camera Module	800
Ergonomic handle and pole	500
Ancillary Expenses	200
Total	5000
Grand Total	9720

Mentor



Leader



INVOICE



Invoice #00253
Date: MAR 15, 2026

BILLED TO:

Geo George
Santham Hostel
Koovalpally
Kanjirappally
Kottayam
686518
9446543476

Description:	Price:	Qty:	Amt:
Esp32 latest (type-c)	550	1	550
ultrasonic- sensor(HC-SR04)	135	2	270
LDR with resistor 5	20	1	20
mpu6050-190	350	1	350
Buzzer	70	1	70
GSM module SIM800L	370	1	370
GSM antenna	190	1	190
sos push button	20	1	20
on/off button	20	2	40
3.7v lion battery	150	2	300
Type-C 3S Lithium Battery Charging Module	120	1	120
jumper wires	4	40	160
Connecting cable-	10	5	50
Battery case single	40	1	40
Battery case double	60	1	60
Breadboard	150	1	150
vibration Motor	40	1	40
Resistors	2	20	40
soldering wire	80	1	80
soldering wax	50	1	50

Subtotal 2970

WWW.ESCLABS.IN

9074213906

create.esclabs@gmail.com

Kattappana PO , Idukki, Kerala, India

Total: 2970-

Estimate

QT-2023-24-1861

BILL TO
CUSTOMER

Estimate Date :

08/01/2026

#	Item	Qty	Rate	Amount
1	ULTRASONIC DISTANCE SENSOR HC-SR04	2.0 Qty	120.00	240.00
2	LDR SENSOR MODULE	1.0 Qty	50.00	50.00
3	VIBRATION MOTOR BMM FLAT 3V DC COIN TYPE	1.0 Qty	30.00	30.00
4	PCB BUZZER MINI 5V DC	1.0 Qty	15.00	15.00
5	GSM GPRS MICRO SIM CARD TTL MODULE SIM800L	1.0 Qty	445.00	445.00
6	BATTERY LIPO 3.7V 3000MAH VIBOW	1.0 Qty	100.00	100.00
7	TP4056 LITHIUM BATTERY CHARGING MODULE(C TYPE)	1.0 Qty	35.00	35.00
8	JUMPER WIRE M/F	20.0 Qty	3.50	70.00
9	BREAD BOARD MB-102, 800 POINT	1.0 Qty	100.00	100.00
10	MPU6050 6 AXIS CYRO MODULE	1.0 Qty	325.00	325.00
Sub Total				1,410.00
Items in Total 30.0				Total ₹1,410.00

Total in Words: Rupees One Thousand Four Hundred Ten Only

Notes

Looking forward for your business.

Bill To
CUSTOMER

Estimate Date : 10/01/2026

Sl	Remarks	QTY	Rate	Amount
1	VIBRATION MOTOR 8MM FLAT 3V DC COIN TYPE	1.0 Qty	30.00	30.00
Items In Total 1.0			Sub Total	30.00
			Total	₹30.00

Total In Words: Rupees Thirty Only

Notes

Looking forward for your business

Bill To
CUSTOMER

Estimate Date : 10/01/2026

Sl	Remarks	QTY	Rate	Amount
1	VIBRATION MOTOR 8MM FLAT 3V DC COIN TYPE	1.0 Qty	30.00	30.00
Items In Total 1.0			Sub Total	30.00
			Total	₹30.00

Total In Words: Rupees Thirty Only

Notes

Looking forward for your business

Estimate

QT-2023-24-2125

RES TO
CUSTOMER

Estimate Date :

14/03/2026

#	Item	Qty	Rate	Amount
1	BATTERY LIPO 3.7V 3000MAH VPOW	1.0 Qty	100.00	100.00
2	LM2596 DC DC BUCK CONVERTER (STEP DOWN)	1.0 Qty	85.00	85.00
Sub Total				185.00
Total				₹185.00

Items in Total 2.0

Total in Words: **Rupees One Hundred Eighty-Five Only**

NOTES

Looking Forward for your business

INVOICE

SHOP ESTIMATE
KPLY

Buyer
LOCAL SALE

Invoice No.	Dated
N:18711	14-Mar-2026
Delivery Note	Mode/Type of Payment
Supplier's Ref.	Other Reference(s)
Buyer's Order No.	Dated
Despatch Document No.	Delivery Note Date
Despatched through	Destination
Terms of Delivery	

S	Description of Goods	Quantity	Rate	per	Amount
1	Tie RETAIL PCS	5,000 NOS	4.00	NOS	20.00
2	HACKSAW BLADE 1" SINGLE SIDE (H)	1,000 NOS	10.00	NOS	10.00
3	INSULATION TAPE ABRO	1,000 NOS	15.00	NOS	15.00
Total		7,000 NOS			₹ 45.00

Amount Chargeable (in words)
INR Forty Five Only

Company's Bank Details
Bank Name: STATE BANK OF INDIA
A/C No.: 36069101726
Branch & PS Code: KANJIRAPALLY

Declaration:
We declare that this invoice shows
the actual price of the goods
described and that all particulars are true and correct.

Authorized Signatory

This is a Computer Generated Invoice

Estimate

QT-2023-24-1890

Estimate Date:

14/01/2024

Billed To
CUSTOMER

#	Item	Qty	Rate	Amount
1	PCB BUZZER MINI 5V DC	1.0 Qty	15.00	15.00
2	LED 5MM W/BUE	2.0 Qty	1.00	2.00
3	1000/25 KIL CAP	1.0 Qty	10.00	10.00
4	247222 PVC	2.0 Qty	8.00	16.00
5	RESISTOR 25W	19.0 Qty	1.00	19.00
6	JUMPER WIRE MIT	10.0 Qty	3.50	35.00
			Sub Total	97.00
			Total	₹97.00

Grand Total 24.0

Total in Words: Rupees Ninety Seven Only

Notes:
Looking forward for your business.