

# SL Corporation

## PHOTOMETRIC RESULTS

Program:	KATRI Regulation No.21-2		H/L DOM PHOTO LED LOW VER013
H/L DOM PHOTO LOW			
Name:	JW1 PE HPV DOM HL LED LOW(STD ASSY-LED) RH#2 2025-09-02		
Number:			
Report:	JO WON JIN		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(LMT #01 GO H-1300)
Voltage:	13.2130 V	Date:	2025-09-03 오전 4:42:09
Current:	0.00000 A	File:	JW1 PE HPV DOM HL LED LOW(STD ASSY- LED) RH#2 2025-09-02

## H/L DOM PHOTO LED LOW VER013

Function	Min	Max	I [cd]	H [°]	V [°]	N. O. K.
B50L	-	350	169.4593	-3.43	0.57	OK
BR	-	1750	211.6492	2.50	1.00	OK
75R	10100	-	20535.0700	1.15	-0.57	OK
75L	-	10600	1146.7250	-3.43	-0.57	OK
50L	-	18500	11147.3200	-3.43	-0.86	OK
50R	10100	-	26633.6100	1.72	-0.86	OK
50V	5100	-	18465.5700	0.00	-0.86	OK
25L	1700	-	7389.2270	-9.00	-1.72	OK
25R	1700	-	11527.2300	9.00	-1.72	OK
1	-	625	83.4800	-8.00	4.00	OK
2	-	625	97.4766	0.00	4.00	OK
3	-	625	165.1604	8.00	4.00	OK
4	-	625	143.3656	-4.00	2.00	OK
5	-	625	138.1668	0.00	2.00	OK
6	-	625	176.5576	4.00	2.00	OK
7	65	625	379.3090	-8.00	0.00	OK
8	125	625	239.5425	-4.00	0.00	OK
ZONE III	-	625	(80.1208) 279.9328	(-8.00) -0.90	(3.80) 0.00	OK
ZONE IV	2500	-	(11451.2500) 27643.3700	(-3.40) 2.00	(-0.86) -1.12	OK
ZONE I	-	2*50R	(4693.0740) 26073.7400	(-9.00) 0.80	(-5.00) -1.72	OK

## Signal

Function	Min	Max	I [cd]	H [°]	V [°]	N. O. K.
1+2+3	190	-	346.1170			OK
4+5+6	375	-	458.0900			OK