

SL Corporation

PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.1 (2016.02) SAE J588		F/T/S NAS LED [1 BULB] 2.5LH
F/T/S NAS PHOTO LED [1 BULB] 2.5LH			
Name:	CT1 NAS HL LED T-SIG (STD ASSY-LED) LH #3 2025-07-01		
Number:			
Report:	Hwang Ji Hoon		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(GO-H1400 Lab 5)
Voltage:	13.5030 V	Date:	2025-07-02 오전 3:33:05
Current:	0.00071 A	File:	CT1 NAS HL LED T-SIG (STD ASSY-LED) LH #3 2025-07-01

F/T/S NAS LED [1 BULB] 2.5LH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
1min H-V	-	-	591.174	0.00	0.00	OK
10min H-V	-	-	528.634	0.00	0.00	OK
30min H-V	-	-	506.120	0.00	0.00	OK
10U - 5L	100	-	367.733	-5.00	10.00	OK
10U - 5R	100	-	389.546	5.00	10.00	OK
5U - 20L	62.5	-	198.025	-20.00	5.00	OK
5U - 10L	187.5	-	347.720	-10.00	5.00	OK
5U - V	437.5	-	484.707	0.00	5.00	OK
5U - 10R	187.5	-	377.139	10.00	5.00	OK
5U - 20R	62.5	-	142.090	20.00	5.00	OK
H - 10L	250	-	352.523	-10.00	0.00	OK
H - 5L	500	-	439.578	-5.00	0.00	NG
H - V	500	-	505.820	0.00	0.00	OK
H - 5R	500	-	490.310	5.00	0.00	NG
H - 10R	250	-	390.947	10.00	0.00	OK
5D - 20L	62.5	-	166.005	-20.00	-5.00	OK
5D - 10L	187.5	-	293.386	-10.00	-5.00	OK
5D - V	437.5	-	403.955	0.00	-5.00	NG
5D - 10R	187.5	-	310.596	10.00	-5.00	OK
5D - 20R	62.5	-	116.874	20.00	-5.00	OK
10D - 5L	100	-	239.151	-5.00	-10.00	OK
10D - 5R	100	-	249.858	5.00	-10.00	OK
Visibility	0.3	-	(6.027) 514.542	(45.00) 1.40	(-14.80) 1.60	OK

ZONE

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
Zone_1	325	-	970.914			OK
Zone_2	625	-	993.628			OK
Zone_3	2375	-	2324.370			NG
Zone_4	625	-	1078.682			OK
Zone_5	325	-	898.368			OK