

SL Corporation

PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.8 (2016.02) SAE J222		F/POSI NAS LED PHOTO_RH
F/POSI NAS LED PHOTO_RH			
Name:	CT1 NAS HL LED PSTN (STD ASSY-LED) RH #1 2025-06-30		
Number:			
Report:	Lee Bong Gyu		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(LMT #01 GO H-1300)
Voltage:	13.5129 V	Date:	2025-07-01 오전 12:38:20
Current:	0.00000 A	File:	CT1 NAS HL LED PSTN (STD ASSY-LED) RH #1 2025-06-30

F/POSI NAS LED PHOTO_RH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
1min H-V	-	-	61.0700	0.00	0.00	OK
30min H-V	-	-	60.9900	0.00	0.00	OK
10U - 5L	0.8	125	43.4900	-5.00	10.00	OK
10U - 5R	0.8	125	44.7500	5.00	10.00	OK
5U - 20L	0.4	125	15.3100	-20.00	5.00	OK
5U - 10L	0.8	125	37.9500	-10.00	5.00	OK
5U - V	2.8	125	59.6500	0.00	5.00	OK
5U - 10R	0.8	125	44.2800	10.00	5.00	OK
5U - 20R	0.4	125	20.4700	20.00	5.00	OK
H - 10L	1.4	125	38.6200	-10.00	0.00	OK
H - 5L	3.6	125	54.4200	-5.00	0.00	OK
H - V	4	125	61.0000	0.00	0.00	OK
H - 5R	3.6	125	55.3800	5.00	0.00	OK
H - 10R	1.4	125	43.8200	10.00	0.00	OK
5D - 20L	0.4	250	12.3100	-20.00	-5.00	OK
5D - 10L	0.8	250	30.1100	-10.00	-5.00	OK
5D - V	2.8	250	45.4600	0.00	-5.00	OK
5D - 10R	0.8	250	33.4400	10.00	-5.00	OK
5D - 20R	0.4	250	16.6500	20.00	-5.00	OK
10D - 5L	0.8	250	25.8200	-5.00	-10.00	OK
10D - 5R	0.8	250	26.1500	5.00	-10.00	OK
above h-h Visibility	0.05	125	(1.0100) 62.7400	(-45.00) -0.30	(4.80) 2.00	OK
below h-h Visibility	0.05	250	(0.6400) 60.9500	(-45.00) -0.30	(-14.80) -0.01	OK

ZONE

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
Zone_1	2.4	-	96.9300			OK
Zone_2	3	-	106.6800			OK
Zone_3	16.8	-	275.9100			OK
Zone_4	3	-	121.5400			OK
Zone_5	2.4	-	108.0200			OK