

SL Corporation

PHOTOMETRIC RESULTS

| | | | |
|----------------------|---|-----------|---|
| Program: | KATRI Regulation No.21-8 | | F/POSI DOM LED COLOR |
| F/POSI DOM LED COLOR | | | |
| Name: | CE FL DOM HL LED PSTN (OPT ASSY-LED) RH #1 COLOR 2025-03-27 | | |
| Number: | | | |
| Report: | GO YUN SOO | | |
| Test no.: | | | |
| Lamp type: | LED | | |
| Lamp no: | PRODUCT | | |
| Lamp flux: | 0 lm | Operator: | James Kim |
| Voltage: | 13.5145 V | Date: | 2025-03-27 오전 5:32:26 |
| Current: | 0.00006 A | File: | CE FL DOM HL LED PSTN (OPT ASSY-LED) RH #1 COLOR 2025-03- 27 |

F/POSI DOM LED COLOR

| No. | Function | H [°] | V [°] | x | y | Tc | N.O .K. |
|-----|----------|--------|--------|--------|--------|------|---------|
| 1 | 10U-5L | -5.00 | 10.00 | 0.3210 | 0.3252 | 6080 | OK |
| 2 | 10U-5R | 5.00 | 10.00 | 0.3200 | 0.3238 | 6143 | OK |
| 3 | 5U-20L | -20.00 | 5.00 | 0.3199 | 0.3247 | 6143 | OK |
| 4 | 5U-10L | -10.00 | 5.00 | 0.3220 | 0.3264 | 6025 | OK |
| 5 | 5U-V | 0.00 | 5.00 | 0.3218 | 0.3257 | 6035 | OK |
| 6 | 5U-10R | 10.00 | 5.00 | 0.3194 | 0.3226 | 6181 | OK |
| 7 | 5U-20R | 20.00 | 5.00 | 0.3135 | 0.3164 | 6562 | OK |
| 8 | H-10L | -10.00 | 0.00 | 0.3216 | 0.3258 | 6045 | OK |
| 9 | H-5L | -5.00 | 0.00 | 0.3219 | 0.3256 | 6034 | OK |
| 10 | HV | 0.00 | 0.00 | 0.3215 | 0.3251 | 6053 | OK |
| 11 | H-5R | 5.00 | 0.00 | 0.3206 | 0.3239 | 6106 | OK |
| 12 | H-10R | 10.00 | 0.00 | 0.3191 | 0.3220 | 6198 | OK |
| 13 | 5D-20L | -20.00 | -5.00 | 0.3183 | 0.3230 | 6240 | OK |
| 14 | 5D-10L | -10.00 | -5.00 | 0.3201 | 0.3237 | 6136 | OK |
| 15 | 5D-V | 0.00 | -5.00 | 0.3198 | 0.3229 | 6156 | OK |
| 16 | 5D-10R | 10.00 | -5.00 | 0.3181 | 0.3205 | 6266 | OK |
| 17 | 5D-20R | 20.00 | -5.00 | 0.3131 | 0.3158 | 6592 | OK |
| 18 | 10D-5L | -5.00 | -10.00 | 0.3177 | 0.3207 | 6286 | OK |
| 19 | 10D-5R | 5.00 | -10.00 | 0.3159 | 0.3182 | 6403 | OK |