

SL Corporation

PHOTOMETRIC RESULTS

Program:	CMVSS108, SAE J2087	DRL NAS CANADA LED PHOTO(WITH)
DRL NAS CANADA LED PHOTO(WITH)		
Name:	CT1 NAS HL LED DRL (STD ASSY-LED) LH #3 2025-07-01	
Number:		
Report:	Hwang Ji Hoon	
Test no.:		
Lamp type:	LED	
Lamp no:	PRODUCT	
Lamp flux:	0 lm	Operator: SL Corp.(GO-H1400 Lab 5)
Voltage:	12.8050 V	Date: 2025-07-01 오후 11:16:01
Current:	0.00071 A	File: CT1 NAS HL LED DRL (STD ASSY-LED) LH #3 2025-07-01

DRL NAS CANADA LED PHOTO(WITH)

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
1MIN	-	-	534.338	0.00	0.00	OK
30MIN	-	-	516.026	0.00	0.00	OK
5U-10L	100	2500	386.244	-10.00	5.00	OK
5U-V	350	2500	529.435	0.00	5.00	OK
5U-10R	100	2500	354.424	10.00	5.00	OK
H-20L	50	2500	178.413	-20.00	0.00	OK
H-10L	350	2500	362.329	-10.00	0.00	OK
H-5L	450	2500	473.700	-5.00	0.00	OK
H-V	500	2500	519.929	0.00	0.00	OK
H-5R	450	2500	471.999	5.00	0.00	OK
H-10R	350	2500	350.221	10.00	0.00	OK
H-20R	50	2500	139.889	20.00	0.00	OK
5D-10L	100	2500	270.271	-10.00	-5.00	OK
5D-V	350	2500	366.832	0.00	-5.00	OK
5D-10R	100	2500	262.566	10.00	-5.00	OK
MAX	-	2500	(0.660) 556.151	(27.50) 0.60	(-2.60) 2.20	OK

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
ZONE1	2100	-	2361.894			OK
ZONE2	600	-	1197.257			OK
ZONE3	600	-	1107.100			OK