## SL Corporation PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.1 (2016.02) SAE J588		F/T/S NAS LED [1 BULB] 2.5LH				
F/T/S NAS PHOTO LED [1 BULB] 2.5LH							
Name:	CT1 NAS HL LED T-SIG (STD ASSY-LED) LH #2 2025-07-01						
Number:							
Report:	Hwang Ji Hoon						
Test no.:							
Lamp type:	LED						
Lamp no:	PRODUCT						
Lamp flux:	0 lm	Operator:	SL Corp.(GO-H1400 Lab 5)				
Voltage:	13.5040 V	Date:	2025-07-02 오전 1:57:25				
Current:	0.00071 A	File:	CT1 NAS HL LED T- SIG (STD ASSY-LED) LH #2 2025-07-01				

## F/T/S NAS LED [1 BULB] 2.5LH

Function	Min	Max	l [cd]	H [°]	V [°]	N.O.K.
1min H-V	-	-	601.480	0.00	0.00	OK
10min H-V	-	-	531.636	0.00	0.00	OK
30min H-V	-	-	501.717	0.00	0.00	OK
10U - 5L	100	-	347.520	-5.00	10.00	OK
10U - 5R	100	-	356.025	5.00	10.00	OK
5U - 20L	62.5	-	196.724	-20.00	5.00	OK
5U - 10L	187.5	-	334.512	-10.00	5.00	OK
5U - V	437.5	=.	468.696	0.00	5.00	OK
5U - 10R	187.5	-	347.620	10.00	5.00	OK
5U - 20R	62.5	-	131.183	20.00	5.00	OK
H - 10L	250	-	343.717	-10.00	0.00	OK
H - 5L	500	=.	433.174	-5.00	0.00	NG
H - V	500	-	501.217	0.00	0.00	OK
H - 5R	500	-	476.601	5.00	0.00	NG
H - 10R	250	-	370.835	10.00	0.00	OK
5D - 20L	62.5	-	168.306	-20.00	-5.00	OK
5D - 10L	187.5	-	290.184	-10.00	-5.00	OK
5D - V	437.5	-	411.760	0.00	-5.00	NG
5D - 10R	187.5	-	305.393	10.00	-5.00	OK
5D - 20R	62.5	-	113.672	20.00	-5.00	OK
10D - 5L	100	-	242.053	-5.00	-10.00	OK
10D - 5R	100	-	254.161	5.00	-10.00	OK
Visibility	0.3	-	(5.722) 503.716	(45.00) 1.20	(- 14.80) 0.80	OK

## ZONE

Function	Min	Max	l [cd]	H [°]	V [°]	N.O.K.
Zone_1	325	=	954.604			OK
Zone_2	625	-	968.412			OK
Zone_3	2375	-	2291.449			NG
Zone_4	625	=	1023.847			OK
Zone_5	325	-	855.041			OK