

SL Corporation

PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.8 (2016.02) SAE J222		F/POSI NAS LED PHOTO_RH
F/POSI NAS LED PHOTO_RH			
Name:	CT1 NAS HL LED PSTN (STD ASSY-LED) RH #2 2025-06-30		
Number:			
Report:	Lee Bong Gyu		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(LMT #01 GO H-1300)
Voltage:	13.5131 V	Date:	2025-07-01 오전 2:30:26
Current:	0.00000 A	File:	CT1 NAS HL LED PSTN (STD ASSY-LED) RH #2 2025-06-30

F/POSI NAS LED PHOTO_RH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
1min H-V	-	-	63.0900	0.00	0.00	OK
30min H-V	-	-	63.0700	0.00	0.00	OK
10U - 5L	0.8	125	45.8300	-5.00	10.00	OK
10U - 5R	0.8	125	47.8700	5.00	10.00	OK
5U - 20L	0.4	125	15.8800	-20.00	5.00	OK
5U - 10L	0.8	125	39.7500	-10.00	5.00	OK
5U - V	2.8	125	62.3200	0.00	5.00	OK
5U - 10R	0.8	125	47.3200	10.00	5.00	OK
5U - 20R	0.4	125	22.1500	20.00	5.00	OK
H - 10L	1.4	125	39.8500	-10.00	0.00	OK
H - 5L	3.6	125	55.9200	-5.00	0.00	OK
H - V	4	125	63.0800	0.00	0.00	OK
H - 5R	3.6	125	57.9400	5.00	0.00	OK
H - 10R	1.4	125	46.5700	10.00	0.00	OK
5D - 20L	0.4	250	12.3300	-20.00	-5.00	OK
5D - 10L	0.8	250	30.6700	-10.00	-5.00	OK
5D - V	2.8	250	46.7900	0.00	-5.00	OK
5D - 10R	0.8	250	35.4700	10.00	-5.00	OK
5D - 20R	0.4	250	17.8200	20.00	-5.00	OK
10D - 5L	0.8	250	26.0400	-5.00	-10.00	OK
10D - 5R	0.8	250	26.9100	5.00	-10.00	OK
above h-h Visibility	0.05	125	(0.9955) 65.0400	(-45.00) 0.00	(0.60) 2.20	OK
below h-h Visibility	0.05	250	(0.6400) 63.0400	(-45.00) 0.00	(-14.80) -0.01	OK

ZONE

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
Zone_1	2.4	-	100.0800			OK
Zone_2	3	-	110.2700			OK
Zone_3	16.8	-	286.0500			OK
Zone_4	3	-	129.3600			OK
Zone_5	2.4	-	114.7500			OK