

SL Corporation

PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.8 (2016.02) SAE J222		F/POSI NAS LED PHOTO_LH
F/POSI NAS LED PHOTO_LH			
Name:	CT1 NAS HL LED PSTN (STD ASSY-LED) LH #1 2025-07-01		
Number:			
Report:	Hwang Ji Hoon		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(GO-H1400 Lab 5)
Voltage:	13.5030 V	Date:	2025-07-02 오전 4:58:40
Current:	0.00071 A	File:	CT1 NAS HL LED PSTN (STD ASSY- LED) LH #1 2025-07-01
Comment:	PWM센서 사용.		

F/POSI NAS LED PHOTO_LH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
1min H-V	-	-	57.452	0.00	0.00	OK
30min H-V	-	-	57.382	0.00	0.00	OK
10U - 5L	0.8	125	47.630	-5.00	10.00	OK
10U - 5R	0.8	125	44.315	5.00	10.00	OK
5U - 20L	0.4	125	19.635	-20.00	5.00	OK
5U - 10L	0.8	125	43.404	-10.00	5.00	OK
5U - V	2.8	125	58.944	0.00	5.00	OK
5U - 10R	0.8	125	37.998	10.00	5.00	OK
5U - 20R	0.4	125	15.720	20.00	5.00	OK
H - 10L	1.4	125	41.091	-10.00	0.00	OK
H - 5L	3.6	125	53.777	-5.00	0.00	OK
H - V	4	125	57.382	0.00	0.00	OK
H - 5R	3.6	125	50.473	5.00	0.00	OK
H - 10R	1.4	125	36.816	10.00	0.00	OK
5D - 20L	0.4	250	15.559	-20.00	-5.00	OK
5D - 10L	0.8	250	30.348	-10.00	-5.00	OK
5D - V	2.8	250	41.212	0.00	-5.00	OK
5D - 10R	0.8	250	27.324	10.00	-5.00	OK
5D - 20R	0.4	250	11.695	20.00	-5.00	OK
10D - 5L	0.8	250	24.130	-5.00	-10.00	OK
10D - 5R	0.8	250	22.809	5.00	-10.00	OK
above h-h Visibility	0.05	125	(1.041) 60.576	(44.10) 0.00	(1.00) 2.80	OK
below h-h Visibility	0.05	250	(0.690) 60.727	(45.00) - 1.50	(- 14.80) - 0.20	OK

ZONE

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
Zone_1	2.4	-	106.954			OK
Zone_2	3	-	114.844			OK
Zone_3	16.8	-	261.788			OK
Zone_4	3	-	102.138			OK
Zone_5	2.4	-	94.538			OK