

SL Corporation

PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.8 (2016.02) SAE J222		F/POSI NAS LED PHOTO_LH
F/POSI NAS LED PHOTO_LH			
Name:	CT1 NAS HL LED PSTN (STD ASSY-LED) LH #3 2025-07-01		
Number:			
Report:	Hwang Ji Hoon		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(GO-H1400 Lab 5)
Voltage:	13.5030 V	Date:	2025-07-02 오전 10:08:46
Current:	0.00071 A	File:	CT1 NAS HL LED PSTN (STD ASSY- LED) LH #3 2025-07-01
Comment:	PWM센서 사용.		

F/POSI NAS LED PHOTO_LH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
1min H-V	-	-	90.013	0.00	0.00	OK
30min H-V	-	-	90.113	0.00	0.00	OK
10U - 5L	0.8	125	72.190	-5.00	10.00	OK
10U - 5R	0.8	125	72.391	5.00	10.00	OK
5U - 20L	0.4	125	32.330	-20.00	5.00	OK
5U - 10L	0.8	125	66.804	-10.00	5.00	OK
5U - V	2.8	125	93.016	0.00	5.00	OK
5U - 10R	0.8	125	62.268	10.00	5.00	OK
5U - 20R	0.4	125	25.272	20.00	5.00	OK
H - 10L	1.4	125	63.359	-10.00	0.00	OK
H - 5L	3.6	125	80.701	-5.00	0.00	OK
H - V	4	125	90.113	0.00	0.00	OK
H - 5R	3.6	125	81.202	5.00	0.00	OK
H - 10R	1.4	125	60.205	10.00	0.00	OK
5D - 20L	0.4	250	25.572	-20.00	-5.00	OK
5D - 10L	0.8	250	47.119	-10.00	-5.00	OK
5D - V	2.8	250	64.751	0.00	-5.00	OK
5D - 10R	0.8	250	44.766	10.00	-5.00	OK
5D - 20R	0.4	250	18.794	20.00	-5.00	OK
10D - 5L	0.8	250	36.866	-5.00	-10.00	OK
10D - 5R	0.8	250	36.966	5.00	-10.00	OK
above h-h Visibility	0.05	125	(1.802) 95.119	(45.00) - 0.40	(2.00) 2.80	OK
below h-h Visibility	0.05	250	(1.121) 90.013	(44.70) 2.40	(- 14.80) - 0.01	OK

ZONE

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
Zone_1	2.4	-	166.959			OK
Zone_2	3	-	177.282			OK
Zone_3	16.8	-	409.783			OK
Zone_4	3	-	167.239			OK
Zone_5	2.4	-	153.422			OK