## SL Corporation PHOTOMETRIC RESULTS

Program:	KATRI Regulation No.21-2	H/L DOM PHOTO LED LOW VER013					
H/L DOM PHOTO LOW							
Name:	OV1 DOM HL LED LOW (STD ASSY-LED) RH #2 2025-04-02						
Number:							
Report:	JO WON JIN						
Test no.:							
Lamp type:	LED						
Lamp no:	PRODUCT						
Lamp flux:	0 lm	Operator:	SL Corp.(LMT #01 GO H-1300)				
Voltage:	13.2120 V	Date:	2025-04-03 오전 12:06:27				
Current:	1.47247 A	File:	OV1 DOM HL LED LOW (STD ASSY-LED) RH #2 2025-04-02				

## **H/L DOM PHOTO LED LOW VER013**

Function	Min	Max	l [cd]	н [°]	V [°]	N.O.K
B50L	-	350	206.351	-3.43	0.57	OK
BR	-	1750	228.845	2.50	1.00	OK
75R	10100	-	16705.990	1.15	-0.57	OK
75L	-	10600	3048.268	-3.43	-0.57	OK
50L	-	18500	9457.729	-3.43	-0.86	OK
50R	10100	-	28253.220	1.72	-0.86	OK
50V	5100	-	25843.800	0.00	-0.86	OK
25L	1700	-	10667.440	-9.00	-1.72	OK
25R	1700	-	12237.060	9.00	-1.72	OK
1	-	625	154.563	-8.00	4.00	OK
2	-	625	234.444	0.00	4.00	OK
3	-	625	232.044	8.00	4.00	OK
4	-	625	245.641	-4.00	2.00	OK
5	-	625	290.430	0.00	2.00	OK
6	-	625	341.718	4.00	2.00	OK
7	65	625	219.847	-8.00	0.00	OK
8	125	625	324.122	-4.00	0.00	OK
ZONE III	-	625	(97.973) 479.885	(-8.00) 0.00	(1.20) 0.00	OK
ZONE IV	2500	-	(8931.469) 41504.810	(-5.15) 0.80	(-0.86) -1.72	ОК
ZONE I	-	2*50R	(4444.800) 41533.890	(-9.00) 0.80	(-5.00) -1.72	ОК

## Signal

Function	Min	Max	l [cd]	н [°]	V [°]	N.O.K
1+2+3	190	-	621.051			OK
4+5+6	375	-	877.789			OK