

SL Corporation

PHOTOMETRIC RESULTS

Program:	ECE Regulation 149.00		H/L ECE PHOTO LOW RHD R149.00
[RHD LOW] Class B			
Name:	CY EV PE ECE HL RHD LED LOW(ASSY-LED) RH #5 2024-04-11		
Number:			
Report:	KANG GI HOON		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp. (LMT #02 GO-H 1600)
Voltage:	28.0557 V	Date:	2024-04-11 오후 8:41:29
Current:	0.70201 A	File:	CY EV PE ECE HL RHD LED LOW(ASSY-LED) RH #5 2024-04-11

H/L ECE PHOTO LOW RHD R149.00

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
B50R (0.57U-3.43R)	-	350	286.0710	3.43	0.57	OK
BL (1U-2.5L)	-	1750	262.2900	-2.50	1.00	OK
Zone III	0	625	(163.7729) 351.8284	(8.00) 0.80	(4.00) 0.00	OK
50L (0.86D-1.72L)	10100	-	25719.4100	-1.72	-0.86	OK
75L (0.57D-1.15L)	10100	-	11849.5100	-1.15	-0.57	OK
50V (0.86D- V)	5100	-	15496.5900	0.00	-0.86	OK
50R (0.86D-3.43R)	-	18500	12348.1200	3.43	-0.86	OK
75R (0.57D-3.43R)	-	10600	2628.8960	3.43	-0.57	OK
25R2 (1.72D-9.00R)	1700	-	11914.4600	9.00	-1.72	OK
25L1 (1.72D-9.00L)	1700	-	17006.3900	-9.00	-1.72	OK
Zone IV	2500	-	(8342.7560) 27236.5400	(5.15) -3.45	-0.86	OK
Zone I (2 x E50L)	0	2 x E50L	(8624.7320) 27155.7800	(9.00) -1.30	(-5.00) -1.72	OK
B1	0	625	182.8536	-8.00	4.00	OK
B2	0	625	233.8128	0.00	4.00	OK
B3	0	625	163.1694	8.00	4.00	OK
B4	0	625	268.4851	-4.00	2.00	OK
B5	0	625	283.3732	0.00	2.00	OK
B6	0	625	288.2692	4.00	2.00	OK
B7	65	625	180.3556	8.00	0.00	OK
B8	125	625	298.8608	4.00	0.00	OK

Signal

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
PT 1+2+3	190	-	579.8358			OK
PT 4+5+6	375	-	840.1274			OK