

SL Corporation

PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.8 (2016.02) SAE J222		F/POSI NAS LED PHOTO_RH
F/POSI NAS LED PHOTO_RH			
Name:	CT1 NAS HL LED PSTN (STD ASSY-LED) RH #3 2025-06-30		
Number:			
Report:	Lee Bong Gyu		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(LMT #01 GO H-1300)
Voltage:	13.5128 V	Date:	2025-07-01 오전 4:20:02
Current:	0.00000 A	File:	CT1 NAS HL LED PSTN (STD ASSY-LED) RH #3 2025-06-30

F/POSI NAS LED PHOTO_RH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
1min H-V	-	-	62.3200	0.00	0.00	OK
30min H-V	-	-	62.2500	0.00	0.00	OK
10U - 5L	0.8	125	44.8100	-5.00	10.00	OK
10U - 5R	0.8	125	44.7400	5.00	10.00	OK
5U - 20L	0.4	125	16.0300	-20.00	5.00	OK
5U - 10L	0.8	125	39.6700	-10.00	5.00	OK
5U - V	2.8	125	60.8400	0.00	5.00	OK
5U - 10R	0.8	125	43.7400	10.00	5.00	OK
5U - 20R	0.4	125	20.7100	20.00	5.00	OK
H - 10L	1.4	125	40.4000	-10.00	0.00	OK
H - 5L	3.6	125	56.3100	-5.00	0.00	OK
H - V	4	125	62.2500	0.00	0.00	OK
H - 5R	3.6	125	55.5000	5.00	0.00	OK
H - 10R	1.4	125	43.2700	10.00	0.00	OK
5D - 20L	0.4	250	12.9200	-20.00	-5.00	OK
5D - 10L	0.8	250	31.4300	-10.00	-5.00	OK
5D - V	2.8	250	46.3700	0.00	-5.00	OK
5D - 10R	0.8	250	33.1600	10.00	-5.00	OK
5D - 20R	0.4	250	17.0300	20.00	-5.00	OK
10D - 5L	0.8	250	26.6200	-5.00	-10.00	OK
10D - 5R	0.8	250	26.2800	5.00	-10.00	OK
above h-h Visibility	0.05	125	(1.0500) 64.0400	(-45.00) -0.30	(0.20) 2.00	OK
below h-h Visibility	0.05	250	(0.7100) 62.2000	(-45.00) -0.20	(-14.80) -0.01	OK

ZONE

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
Zone_1	2.4	-	100.3800			OK
Zone_2	3	-	111.5000			OK
Zone_3	16.8	-	281.2700			OK
Zone_4	3	-	120.1700			OK
Zone_5	2.4	-	108.7600			OK