

SL Corporation

PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.8 (2016.02) SAE J222		F/POSI NAS LED PHOTO_LH
F/POSI NAS LED PHOTO_LH			
Name:	CT1 NAS HL LED PSTN (STD ASSY-LED) LH #2 2025-07-01		
Number:			
Report:	Hwang Ji Hoon		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(GO-H1400 Lab 5)
Voltage:	13.5030 V	Date:	2025-07-02 오전 8:11:37
Current:	0.00071 A	File:	CT1 NAS HL LED PSTN (STD ASSY- LED) LH #2 2025-07-01
Comment:	PWM센서 사용.		

F/POSI NAS LED PHOTO_LH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
1min H-V	-	-	56.511	0.00	0.00	OK
30min H-V	-	-	56.521	0.00	0.00	OK
10U - 5L	0.8	125	41.692	-5.00	10.00	OK
10U - 5R	0.8	125	42.563	5.00	10.00	OK
5U - 20L	0.4	125	20.155	-20.00	5.00	OK
5U - 10L	0.8	125	38.518	-10.00	5.00	OK
5U - V	2.8	125	56.080	0.00	5.00	OK
5U - 10R	0.8	125	37.357	10.00	5.00	OK
5U - 20R	0.4	125	15.359	20.00	5.00	OK
H - 10L	1.4	125	37.707	-10.00	0.00	OK
H - 5L	3.6	125	49.202	-5.00	0.00	OK
H - V	4	125	56.531	0.00	0.00	OK
H - 5R	3.6	125	51.014	5.00	0.00	OK
H - 10R	1.4	125	37.687	10.00	0.00	OK
5D - 20L	0.4	250	16.531	-20.00	-5.00	OK
5D - 10L	0.8	250	29.327	-10.00	-5.00	OK
5D - V	2.8	250	42.633	0.00	-5.00	OK
5D - 10R	0.8	250	29.507	10.00	-5.00	OK
5D - 20R	0.4	250	12.265	20.00	-5.00	OK
10D - 5L	0.8	250	24.100	-5.00	-10.00	OK
10D - 5R	0.8	250	25.202	5.00	-10.00	OK
above h-h Visibility	0.05	125	(1.041) 58.163	(45.00) - 0.70	(0.20) 2.20	OK
below h-h Visibility	0.05	250	(0.741) 56.351	(44.90) - 0.10	(- 10.80) - 0.01	OK

ZONE

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
Zone_1	2.4	-	102.478			OK
Zone_2	3	-	105.552			OK
Zone_3	16.8	-	255.460			OK
Zone_4	3	-	104.551			OK
Zone_5	2.4	-	95.389			OK