

SL Corporation

PHOTOMETRIC RESULTS

| | | | | |
|-------------|--|-----------|--|-------------------|
| Program: | KATRI Regulation No.21-8 | | | DRL DOM LED PHOTO |
| DRL DOM LED | PHOTO | | | |
| Name: | CE FL DOM HL LED DRL (OPT ASSY-LED) RH #1 2025-03-27 | | | |
| Number: | | | | |
| Report: | GO YUN SOO | | | |
| Test no.: | | | | |
| Lamp type: | LED | | | |
| Lamp no: | PRODUCT | | | |
| Lamp flux: | 0 lm | Operator: | James Kim | |
| Voltage: | 13.5147 V | Date: | 2025-03-27 오전 7:13:04 | |
| Current: | 0.00009 A | File: | CE FL DOM HL LED DRL (OPT ASSY-LED) RH #1 2025-03-27 | |

DRL DOM LED PHOTO

| Function | Min | Max | I [cd] | H [°] | V [°] | N.O. K. |
|-----------|-----|------|-------------------|----------------|--------------|---------|
| 1min H-V | - | - | 725.052 | 0.00 | 0.00 | OK |
| 30min H-V | - | - | 684.570 | 0.00 | 0.00 | OK |
| 10U-5L | 80 | 1200 | 538.476 | -5.00 | 10.00 | OK |
| 10U-V | 80 | 1200 | 570.138 | 0.00 | 10.00 | OK |
| 10U-5R | 80 | 1200 | 542.234 | 5.00 | 10.00 | OK |
| 5U-20L | 40 | 1200 | 254.780 | -20.00 | 5.00 | OK |
| 5U-10L | 80 | 1200 | 545.018 | -10.00 | 5.00 | OK |
| 5U-V | 280 | 1200 | 694.690 | 0.00 | 5.00 | OK |
| 5U-10R | 80 | 1200 | 571.078 | 10.00 | 5.00 | OK |
| 5U-20R | 40 | 1200 | 245.708 | 20.00 | 5.00 | OK |
| H-20L | 100 | 1200 | 250.660 | -20.00 | 0.00 | OK |
| H-10L | 280 | 1200 | 532.692 | -10.00 | 0.00 | OK |
| H-5L | 360 | 1200 | 646.980 | -5.00 | 0.00 | OK |
| HV | 400 | 1200 | 684.209 | 0.00 | 0.00 | OK |
| H-5R | 360 | 1200 | 639.751 | 5.00 | 0.00 | OK |
| H-10R | 280 | 1200 | 557.885 | 10.00 | 0.00 | OK |
| H-20R | 100 | 1200 | 244.371 | 20.00 | 0.00 | OK |
| 5D-20L | 40 | 1200 | 211.985 | -20.00 | -5.00 | OK |
| 5D-10L | 80 | 1200 | 431.959 | -10.00 | -5.00 | OK |
| 5D-V | 280 | 1200 | 555.861 | 0.00 | -5.00 | OK |
| 5D-10R | 80 | 1200 | 464.235 | 10.00 | -5.00 | OK |
| 5D-20R | 40 | 1200 | 219.503 | 20.00 | -5.00 | OK |
| MIN/MAX | 1 | 1200 | (212.301) 705.095 | (-20.00) -0.50 | (10.00) 3.00 | OK |