## SL Corporation PHOTOMETRIC RESULTS

Program:	KATRI Regulation No.21-2	H/L DOM PHOTO LED LOW VER013					
H/L DOM PHOTO LOW							
Name:	JW1 PE HPV DOM HL LED LOW(STD ASSY-LED) RH#1 2025-09-04						
Number:	·						
Report:	JO WON JIN						
Test no.:							
Lamp type:	LED						
Lamp no:	PRODUCT						
Lamp flux:	0 lm	Operator:	SL Corp.(LMT #01 GO H-1300)				
Voltage:	13.2132 V	Date:	2025-09-04 오후 8:58:08				
Current:	0.00000 A	File:	JW1 PE HPV DOM HL LED LOW(STD ASSY- LED) RH#1 2025-09-04				

## **H/L DOM PHOTO LED LOW VER013**

						N.
Function	Min	Max	l [cd]	H [°]	V [°]	Ο.
						K.
B50L	-	350	154.3629	-3.43	0.57	OK
BR	-	1750	192.3538	2.50	1.00	OK
75R	10100	-	21084.9400	1.15	-0.57	OK
75L	-	10600	1888.5470	-3.43	-0.57	OK
50L	-	18500	12067.1000	-3.43	-0.86	OK
50R	10100	-	27223.4600	1.72	-0.86	OK
50V	5100	-	19885.2300	0.00	-0.86	OK
25L	1700	-	7457.2100	-9.00	-1.72	OK
25R	1700	-	11597.2200	9.00	-1.72	OK
1	-	625	76.1817	-8.00	4.00	OK
2	-	625	83.3800	0.00	4.00	OK
3	-	625	150.4639	8.00	4.00	OK
4	-	625	134.2678	-4.00	2.00	OK
5	-	625	137.4670	0.00	2.00	OK
6	-	625	154.9628	4.00	2.00	OK
7	65	625	447.6925	-8.00	0.00	OK
8	125	625	219.7473	-4.00	0.00	OK
ZONE III	-	625	(72.8025) 259.9376	(-8.00) -1.20	(3.80) 0.00	OK
ZONE IV	2500	-	(12514.0000) 27930.2900	(-3.30) 1.80	(-0.86) -1.12	OK
ZONE I	-	2*50R	(4712.8690) 26083.7400	(-9.00) 0.80	(-5.00) -1.72	OK

## Signal

Function	Min	Max	l [cd]	H [°]	V [°]	N. O. K.
1+2+3	190	-	310.0256			OK
4+5+6	375	-	426.6976			OK