

SL Corporation

PHOTOMETRIC RESULTS

Program:	KATRI Regulation No.21-2		H/L DOM PHOTO LED LOW VER013
H/L DOM PHOTO LOW			
Name:	JW1 PE HPV DOM HL LED LOW(STD ASSY-LED) LH#1 2025-09-02		
Number:			
Report:	JO WON JIN		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(LMT #01 GO H-1300)
Voltage:	13.2130 V	Date:	2025-09-02 오후 11:49:21
Current:	0.00000 A	File:	JW1 PE HPV DOM HL LED LOW(STD ASSY- LED) LH#1 2025-09-02

H/L DOM PHOTO LED LOW VER013

Function	Min	Max	I [cd]	H [°]	V [°]	N. O. K.
B50L	-	350	269.9352	-3.43	0.57	OK
BR	-	1750	232.7441	2.50	1.00	OK
75R	10100	-	26383.6700	1.15	-0.57	OK
75L	-	10600	3668.1200	-3.43	-0.57	OK
50L	-	18500	14386.5500	-3.43	-0.86	OK
50R	10100	-	26773.5700	1.72	-0.86	OK
50V	5100	-	24154.2000	0.00	-0.86	OK
25L	1700	-	11087.3400	-9.00	-1.72	OK
25R	1700	-	8767.8960	9.00	-1.72	OK
1	-	625	147.7645	-8.00	4.00	OK
2	-	625	119.6713	0.00	4.00	OK
3	-	625	136.1673	8.00	4.00	OK
4	-	625	213.8487	-4.00	2.00	OK
5	-	625	191.1541	0.00	2.00	OK
6	-	625	160.4615	4.00	2.00	OK
7	65	625	280.5327	-8.00	0.00	OK
8	125	625	222.3466	-4.00	0.00	OK
ZONE III	-	625	(114.2926) 322.3226	(2.30) -5.70	(4.00) 0.80	OK
ZONE IV	2500	-	(15870.1900) 30162.7600	(-5.15) -0.25	(-0.86) -1.72	OK
ZONE I	-	2*50R	(4851.2360) 30122.7700	(9.00) -0.20	(-5.00) -1.72	OK

Signal

Function	Min	Max	I [cd]	H [°]	V [°]	N. O. K.
1+2+3	190	-	403.6031			OK
4+5+6	375	-	565.4643			OK