

SL Corporation

PHOTOMETRIC RESULTS

Program:	KATRI Regulation No.21-2		H/L DOM PHOTO LED LOW VER013
H/L DOM PHOTO LOW			
Name:	CE FL DOM HL LED LOW (STD ASSY-LED) LH #1 2025-03-20		
Number:			
Report:	GO YUN SOO		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL CORP.(LAB #3 LMT GO-H1660)
Voltage:	13.2144 V	Date:	2025-03-20 오후 8:22:29
Current:	0.00012 A	File:	CE FL DOM HL LED LOW (STD ASSY-LED) LH #1 2025-03-20

H/L DOM PHOTO LED LOW VER013

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
B50L	-	350	265.115	-3.43	0.57	OK
BR	-	1750	288.708	2.50	1.00	OK
75R	10100	-	13218.770	1.15	-0.57	OK
75L	-	10600	753.059	-3.43	-0.57	OK
50L	-	18500	2057.342	-3.43	-0.86	OK
50R	10100	-	27811.100	1.72	-0.86	OK
50V	5100	-	16484.720	0.00	-0.86	OK
25L	1700	-	10543.630	-9.00	-1.72	OK
25R	1700	-	16226.810	9.00	-1.72	OK
1	-	625	201.336	-8.00	4.00	OK
2	-	625	247.621	0.00	4.00	OK
3	-	625	192.838	8.00	4.00	OK
4	-	625	243.022	-4.00	2.00	OK
5	-	625	234.025	0.00	2.00	OK
6	-	625	219.530	4.00	2.00	OK
7	65	625	270.713	-8.00	0.00	OK
8	125	625	400.472	-4.00	0.00	OK
ZONE III	-	625	(175.526) 476.286	(-8.00) 0.00	(2.00) 0.00	OK
ZONE IV	2500	-	(4715.272) 39368.430	(-5.15) 1.10	(-0.86) -1.52	OK
ZONE I	-	2*50R	(6822.602) 39004.250	(9.00) 1.10	(-5.00) -1.72	OK

Signal

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
1+2+3	190	-	641.795			OK
4+5+6	375	-	696.577			OK