

# SL Corporation

## PHOTOMETRIC RESULTS

Program:	KATRI Regulation No.21-2		H/L DOM PHOTO LED LOW VER013
H/L DOM PHOTO LOW			
Name:	CE FL DOM HL LED LOW (STD ASSY-LED) LH #2 2025-03-20		
Number:			
Report:	GO YUN SOO		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL CORP.(LAB #3 LMT GO-H1660)
Voltage:	13.2144 V	Date:	2025-03-20 오후 11:15:08
Current:	0.00011 A	File:	CE FL DOM HL LED LOW (STD ASSY-LED) LH #2 2025-03-20

## H/L DOM PHOTO LED LOW VER013

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
B50L	-	350	226.727	-3.43	0.57	OK
BR	-	1750	282.010	2.50	1.00	OK
75R	10100	-	13529.670	1.15	-0.57	OK
75L	-	10600	1074.856	-3.43	-0.57	OK
50L	-	18500	2805.102	-3.43	-0.86	OK
50R	10100	-	24792.060	1.72	-0.86	OK
50V	5100	-	10013.790	0.00	-0.86	OK
25L	1700	-	11586.290	-9.00	-1.72	OK
25R	1700	-	16083.850	9.00	-1.72	OK
1	-	625	189.639	-8.00	4.00	OK
2	-	625	264.016	0.00	4.00	OK
3	-	625	208.333	8.00	4.00	OK
4	-	625	251.320	-4.00	2.00	OK
5	-	625	255.718	0.00	2.00	OK
6	-	625	247.421	4.00	2.00	OK
7	65	625	288.108	-8.00	0.00	OK
8	125	625	440.959	-4.00	0.00	OK
ZONE III	-	625	(175.418) 464.756	(-8.00) 0.00	(1.60) 0.00	OK
ZONE IV	2500	-	(4894.636) 44940.110	(-5.15) 1.30	(-0.86) -1.72	OK
ZONE I	-	2*50R	(7672.083) 38200.060	(7.20) 1.40	(-5.00) -1.80	OK

## Signal

Function	Min	Max	I [cd]	H [°]	V [°]	N.O. K.
1+2+3	190	-	661.988			OK
4+5+6	375	-	754.459			OK