

SL Corporation

PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.1 (2016.02) SAE J588		F/T/S NAS LED [1 BULB] 2.5RH
F/T/S NAS PHOTO LED [1 BULB] 2.5RH			
Name:	CT1 NAS HL LED T-SIG (STD ASSY-LED) RH #1 2025-07-02		
Number:			
Report:	Hwang Ji Hoon		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(GO-H1400 Lab 5)
Voltage:	13.5030 V	Date:	2025-07-02 오전 11:22:02
Current:	0.00071 A	File:	CT1 NAS HL LED T-SIG (STD ASSY-LED) RH #1 2025-07-02

F/T/S NAS LED [1 BULB] 2.5RH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
1min H-V	-	-	573.763	0.00	0.00	OK
10min H-V	-	-	518.128	0.00	0.00	OK
30min H-V	-	-	498.515	0.00	0.00	OK
10U - 5L	100	-	360.328	-5.00	10.00	OK
10U - 5R	100	-	360.828	5.00	10.00	OK
5U - 20L	62.5	-	129.982	-20.00	5.00	OK
5U - 10L	187.5	-	354.824	-10.00	5.00	OK
5U - V	437.5	-	470.598	0.00	5.00	OK
5U - 10R	187.5	-	351.422	10.00	5.00	OK
5U - 20R	62.5	-	194.323	20.00	5.00	OK
H - 10L	250	-	377.439	-10.00	0.00	OK
H - 5L	500	-	479.703	-5.00	0.00	NG
H - V	500	-	498.315	0.00	0.00	NG
H - 5R	500	-	442.580	5.00	0.00	NG
H - 10R	250	-	355.625	10.00	0.00	OK
5D - 20L	62.5	-	114.372	-20.00	-5.00	OK
5D - 10L	187.5	-	313.999	-10.00	-5.00	OK
5D - V	437.5	-	410.159	0.00	-5.00	NG
5D - 10R	187.5	-	299.589	10.00	-5.00	OK
5D - 20R	62.5	-	162.903	20.00	-5.00	OK
10D - 5L	100	-	270.471	-5.00	-10.00	OK
10D - 5R	100	-	255.662	5.00	-10.00	OK
Visibility	0.3	-	(5.626) 503.429	(-45.00) - 1.70	(-15.00) 1.00	OK

ZONE

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
Zone_1	325	-	875.153			OK
Zone_2	625	-	1046.262			OK
Zone_3	2375	-	2301.355			NG
Zone_4	625	-	1006.636			OK
Zone_5	325	-	973.716			OK