

# SL Corporation

## PHOTOMETRIC RESULTS

Program:	FMVSS108 (2016.02)	H/L NAS PHOTO HIGH (120%)
H/L NAS PHOTO HIGH UB2		
Name:	CT1 NAS HL LED HIGH (OPT ASSY-LED)(2UP) RH#2 2025-08-04	
Number:		
Report:	Kim Jin Mo	
Test no.:		
Lamp type:	LED	
Lamp no:	PRODUCT	
Lamp flux:	0 lm	Operator: SL Corp.(GO-H1400 Lab 5)
Voltage:	12.8050 V	Date: 2025-08-05 오전 6:29:54
Current:	0.00085 A	File: CT1 NAS HL LED HIGH (OPT ASSY-LED)(2UP) RH#2 2025-08-04

## H/L NAS PHOTO HIGH (120%)

Function	Min	Max	I [cd]	H [°]	V [°]	Reaim I [cd]	H [°]	V [°]	N.O .K.
2U - V (120%)	1800	-	36133.5	0.00	2.00				OK
1U - 3L (120%)	6000	-	40335.3	-3.00	1.00				OK
1U - 3R (120%)	6000	-	20570.9	3.00	1.00				OK
H - V (120%)	4800 0	60000	50660.6	0.00	0.00				OK
H - 3L (120%)	1800 0	-	43720.6	-3.00	0.00				OK
H - 3R (120%)	1800 0	-	24951.9	3.00	0.00				OK
H - 6L (120%)	6000	-	19077.4	-6.00	0.00				OK
H - 6R (120%)	6000	-	10544.3	6.00	0.00				OK
H - 9L (120%)	3600	-	8373.7	-9.00	0.00				OK
H - 9R (120%)	3600	-	6272.8	9.00	0.00				OK
H - 12L (120%)	1800	-	4175.9	-12.00	0.00				OK
H - 12R (120%)	1800	-	3894.1	12.00	0.00				OK
1.5D - V (120%)	6000	-	69479.1	0.00	-1.50				OK
1.5D - 9L (120%)	2400	-	16468.7	-9.00	-1.50				OK
1.5D - 9R (120%)	2400	-	16369.1	9.00	-1.50				OK
2.5D - V (120%)	3000	-	47942.4	0.00	-2.50				OK
2.5D - 12L (120%)	1200	-	8473.3	-12.00	-2.50				OK
2.5D - 12R (120%)	1200	-	10823.1	12.00	-2.50				OK
4D - V (120%)	-	9600	11082.0	0.00	-4.00	8961.2	0.00	-4.25	OK
MAX	-	-	74955.4	-0.20	-0.71				OK