

SL Corporation

PHOTOMETRIC RESULTS

Program:	FMVSS108 S7.1 (2016.02) SAE J588		F/T/S NAS LED [1 BULB] 2.5LH
F/T/S NAS PHOTO LED [1 BULB] 2.5LH			
Name:	CT1 NAS HL LED T-SIG (STD ASSY-LED) LH #1 2025-07-01		
Number:			
Report:	Hwang Ji Hoon		
Test no.:			
Lamp type:	LED		
Lamp no:	PRODUCT		
Lamp flux:	0 lm	Operator:	SL Corp.(GO-H1400 Lab 5)
Voltage:	13.5040 V	Date:	2025-07-02 오전 12:51:26
Current:	0.00071 A	File:	CT1 NAS HL LED T-SIG (STD ASSY-LED) LH #1 2025-07-01

F/T/S NAS LED [1 BULB] 2.5LH

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
1min H-V	-	-	575.464	0.00	0.00	OK
10min H-V	-	-	506.520	0.00	0.00	OK
30min H-V	-	-	486.608	0.00	0.00	OK
10U - 5L	100	-	362.429	-5.00	10.00	OK
10U - 5R	100	-	368.833	5.00	10.00	OK
5U - 20L	62.5	-	191.921	-20.00	5.00	OK
5U - 10L	187.5	-	348.020	-10.00	5.00	OK
5U - V	437.5	-	469.497	0.00	5.00	OK
5U - 10R	187.5	-	351.722	10.00	5.00	OK
5U - 20R	62.5	-	130.883	20.00	5.00	OK
H - 10L	250	-	349.621	-10.00	0.00	OK
H - 5L	500	-	432.373	-5.00	0.00	NG
H - V	500	-	486.107	0.00	0.00	NG
H - 5R	500	-	460.591	5.00	0.00	NG
H - 10R	250	-	361.329	10.00	0.00	OK
5D - 20L	62.5	-	158.200	-20.00	-5.00	OK
5D - 10L	187.5	-	286.581	-10.00	-5.00	OK
5D - V	437.5	-	384.043	0.00	-5.00	NG
5D - 10R	187.5	-	286.381	10.00	-5.00	OK
5D - 20R	62.5	-	106.267	20.00	-5.00	OK
10D - 5L	100	-	232.947	-5.00	-10.00	OK
10D - 5R	100	-	238.751	5.00	-10.00	OK
Visibility	0.3	-	(5.534) 493.119	(45.00) 1.00	(- 14.80) 1.60	OK

ZONE

Function	Min	Max	I [cd]	H [°]	V [°]	N.O.K.
Zone_1	325	-	945.498			OK
Zone_2	625	-	984.222			OK
Zone_3	2375	-	2232.612			NG
Zone_4	625	-	999.432			OK
Zone_5	325	-	844.734			OK